



TETRA TECH

July 10, 2013

VIA FEDERAL EXPRESS 8029161482560215

Ms. Kate Anderson
Chief, Clean Water Regulatory Branch
USEPA Region II
290 Broadway
New York, New York 10007-1866

Subject: National Pollutant Discharge Elimination System (NPDES) Permit Application for the Aguirre Gas Port located offshore from Jobos Bay, Puerto Rico

Dear Ms. Anderson:

Tetra Tech, Inc. on the behalf of its client Aguirre Offshore GasPort LLC (AOGP), a wholly owned subsidiary of Excelerate Energy L.P. (Excelerate Energy) is submitting two (2) copies of the attached draft National Pollutant Discharge Elimination System (NPDES) application for the discharge of non-process and cooling water associated with the proposed Aguirre Offshore Gas Port Project (the Project). The Project will be located in Salinas, along the southern shore of the Commonwealth of Puerto Rico in Commonwealth waters just off shore from Jobos Bay.

As per our e-mail correspondence with USEPA representatives, attached are the following forms with supporting documentation:

- Form 1
- Form 2D (with outfall dedicated profiles)
- Project Location Map
- Water Balance for the AOGP Floating Storage Regasification Unit (FSRU) and Gas Port Platform.
- Thermal Modeling Assessment Report for Outfall 001 and 002
- Form 2F Stormwater (with copy of Form 1)

Project Background


The Project is being developed in cooperation with the Puerto Rico Electric Power Authority ("PREPA") for the purpose of receiving and storing liquefied natural gas ("LNG") to be acquired by PREPA, regasifying the LNG, and delivering natural gas to PREPA's existing Aguirre Power Complex ("Aguirre Plant"). Pursuant to Section 3 of the Natural Gas Act ("NGA"), as amended, and Parts 153 and 380 of the regulations of the Federal Energy Regulatory Commission ("FERC"), AOGP recently filed an application to the FERC for authorization to site, construct and operate the Project.

The Project will utilize Excelerate Energy's proven Energy Bridge™ technology to receive, store and vaporize LNG for delivery as natural gas utilizing one of Excelerate Energy's existing Energy Bridge

Tetra Tech, Inc.
1000 The American Road, Morris Plains, NJ 07950
Tel 973.630.8000 Fax 973.630.8025 www.tetrattech.com

Please contact me at your earliest convenience to discuss the application submittal and to continue the application process. You can reach me at (973) 630-8530 or via email at John.Schaffer@tetrattech.com. I look forward to hearing from you.

Sincerely,



John Schaffer
Principal Aquatic Ecologist

Enc: Aguirre GasPort NPDES Permit Application

cc: Mike Trammel, Excelerate Energy
Ernest Ladkani, Excelerate Energy
Annette Feliberty Ruiz, Chief Point Sources Permits Division, PREQB
Ivelisse C. Sánchez Soultairé, Esq., PREPA
Craig Wolfgang, Tetra Tech

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
GENERAL INSTRUCTIONS														
If a preprinted label has been provided, affix it in the designated space. Review the information carefully, if any of it is incorrect, cross through it and enter the correct data in the appropriate fill-in area below. Also, if any of the preprinted data is absent (the area to the left of the label space lists the information that should appear), please provide it in the proper fill-in area(s) below. If the label is complete and correct, you need not complete Items I, III, V, and VI (except VI B which must be completed regardless). Complete all items if no label has been provided. Refer to the instructions for detailed item descriptions and for the legal authorizations under which this data is collected.														

LABEL ITEMS

I. EPA I.D. NUMBER

III. FACILITY NAME

V. FACILITY MAILING ADDRESS

VI. FACILITY LOCATION

PLEASE PLACE LABEL IN THIS SPACE

II. POLLUTANT CHARACTERISTICS

INSTRUCTIONS: Complete A through J to determine whether you need to submit any permit application forms to the EPA. If you answer "yes" to any questions, you must submit this form and the supplemental form listed in the parenthesis following the question. Mark "X" in the box in the third column if the supplemental form is attached. If you answer "no" to each question, you need not submit any of these forms. You may answer "no" if your activity is excluded from permit requirements; see Section C of the instructions. See also, Section D of the instructions for definitions of bold-faced terms.

SPECIFIC QUESTIONS	Mark "X"			SPECIFIC QUESTIONS	Mark "X"		
	YES	NO	FORM ATTACHED		YES	NO	FORM ATTACHED
A. Is this facility a publicly owned treatment works which results in a discharge to waters of the U.S.? (FORM 2A)		X		B. Does or will this facility (either existing or proposed) include a concentrated animal feeding operation or aquatic animal production facility which results in a discharge to waters of the U.S.? (FORM 2B)		X	
C. Is this a facility which currently results in discharges to waters of the U.S. other than those described in A or B above? (FORM 2C)		X		D. Is this a proposed facility (other than those described in A or B above) which will result in a discharge to waters of the U.S.? (FORM 2D)	X		X
E. Does or will this facility treat, store, or dispose of hazardous wastes? (FORM 3)		X		F. Do you or will you inject at this facility industrial or municipal effluent below the lowermost stratum containing, within one quarter mile of the well bore, underground sources of drinking water? (FORM 4)		X	
G. Do you or will you inject at this facility any produced water or other fluids which are brought to the surface in connection with conventional oil or natural gas production, inject fluids used for enhanced recovery of oil or natural gas, or inject fluids for storage of liquid hydrocarbons? (FORM 4)		X		H. Do you or will you inject at this facility fluids for special processes such as mining of sulfur by the Frasch process, solution mining of minerals, in situ combustion of fossil fuel, or recovery of geothermal energy? (FORM 4)		X	
I. Is this facility a proposed stationary source which is one of the 28 industrial categories listed in the instructions and which will potentially emit 100 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be located in an attainment area? (FORM 5)		X		J. Is this facility a proposed stationary source which is NOT one of the 28 industrial categories listed in the instructions and which will potentially emit 250 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be located in an attainment area? (FORM 5)		X	

III. NAME OF FACILITY

1 SKIP Aguirre Offshore Gas Port

IV. FACILITY CONTACT

A. NAME & TITLE (last, first, & title) Michael Trammel, Senior Director Environmental Affairs

B. PHONE (area code & no.) (832) 813-7629

V. FACILITY MAILING ADDRESS

A. STREET OR P.O. BOX 1450 Lake Robbins Drive, Suite 200

B. CITY OR TOWN The Woodlands

C. STATE TX

D. ZIP CODE 77380

VI. FACILITY LOCATION

A. STREET, ROUTE NO. OR OTHER SPECIFIC IDENTIFIER 3 miles Offshore from Jobos Bay

B. COUNTY NAME Salinas County (Lat. 17 deg. 54' 14" Long. 66 deg. 13' 49")

C. CITY OR TOWN Salinas

D. STATE PR

E. ZIP CODE 00751

F. COUNTY CODE (if known) NA

1-1

THESE ARE THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS. THE RESULTS ARE
AS FOLLOWS:

TEST NO.		10780
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

TEST NO.		10781
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

TEST NO.		10782
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

TEST NO.		10783
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

TEST NO.		10784
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

TEST NO.		10785
DATE		10/10/50
TESTER		W. H. COOK
MATERIAL		
RESULTS		

THE RESULTS OF THE TESTS CONDUCTED ON THE
MATERIALS SUBMITTED FOR ANALYSIS ARE AS FOLLOWS:

CONTINUED FROM THE FRONT

VII. SIC CODES (4-digit, in order of priority)


A. FIRST				B. SECOND			
7	4	9	2	7	4	9	2
Natural Gas Distribution				Natural Gas Transmission and Distribution			
C. THIRD				D. FOURTH			
7	4	4	9	7	1	3	2
Marine Cargo Handling				Natural Gas Liquids			

VIII. OPERATOR INFORMATION


A. NAME															B. Is the name listed in Item VIII-A also the owner? <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO									
Excelerate Energy																								
C. STATUS OF OPERATOR (Enter the appropriate letter into the answer box: If "Other," specify)																								
F = FEDERAL S = STATE P = PRIVATE										M = PUBLIC (other than federal or state) O = OTHER (specify)										D. PHONE (area code & no.) A (832) 813-7629				
E. STREET OR P.O. BOX 1450 Lake Robbins Drive Suite 200																								
F. CITY OR TOWN The Woodlands																								
G. STATE TX										H. ZIP CODE 77380					IX. INDIAN LAND <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO									

X. EXISTING ENVIRONMENTAL PERMITS																								
A. NPDES (Discharges to Surface Water)															D. PSD (Air Emissions from Proposed Sources)									
NA															PFE-TV-4911-63-0796-005**									
B. UIC (Underground Injection of Fluids)															E. OTHER (specify)									
NA															NA									
C. RCRA (Hazardous Wastes)															E. OTHER (specify)									
NA															NA									


XI. MAP																								
<p>Attach to this application a topographic map of the area extending to at least one mile beyond property boundaries. The map must show the outline of the facility, the location of each of its existing and proposed intake and discharge structures, each of its hazardous waste treatment, storage, or disposal facilities, and each well where it injects fluids underground. Include all springs, rivers, and other surface water bodies in the map area. See instructions for precise requirements.</p>																								
<p>XII. NATURE OF BUSINESS (provide a brief description)</p> <p>A floating storage regasification unit (FSRU) will be moored to an offshore GasPort Terminal located in the Caribbean Sea outside of Jobos Bay. The FSRU will regasify liquefied natural gas (LNG) supplied by liquefied natural gas carriers (LNGCs) that will moor to the GasPort Terminal every 1-2 weeks depending upon demand from the Aguirre Power Plant owned by the Puerto Rico Electric Power Authority (PREPA). The regasified natural gas will be delivered via submarine pipeline to the PREPA Aguirre Power Plant.</p>																								
** PREPA Aguirre Power Plant Air Permit Number																								

XIII. CERTIFICATION (see instructions)																																		
<p>I certify under penalty of law that I have personally examined and am familiar with the information submitted in this application and all attachments and that, based on my inquiry of those persons immediately responsible for obtaining the information contained in the application, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.</p>																																		
A. NAME & OFFICIAL TITLE (type or print)															B. SIGNATURE										C. DATE SIGNED									
EDWARD SCOTT, COO																									3 July 2013									

COMMENTS FOR OFFICIAL USE ONLY																								
EPA Form 3510-1 (8-90)																								



Aguirre Gas Port Platform - Preliminary Water Balance V1 5-30-13




Notes:

→ Continuous discharge

- - - Intermittent discharge based on regasification schedule

¹ Minimum water withdrawal for on demand pressure maintenance and service supply will be on routine basis

² Maximum flow based on emergency water supply operational demand .



LOCATION MAP



Legend

- ★ Proposed Offshore Terminal
- Proposed Pipeline Route

Sources:
NOAA Raster Navigational Chart 25687
NOAA Office of Coast Survey

Notes:
Sounding displayed in feet at MLLW



Kilometers

0 0.25 0.5 1

0 0.25 0.5
Statute Miles

excelerate
energy

Figure 1
Project and Outfall Location Map

June 2013

TETRA TECH

FORM
2F
NPDESU.S. Environmental Protection Agency
Washington, DC 20460**Application for Permit to Discharge Storm Water
Discharges Associated with Industrial Activity****Paperwork Reduction Act Notice**

Public reporting burden for this application is estimated to average 28.6 hours per application, including time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding the burden estimate, any other aspect of this collection of information, or suggestions for improving this form, including suggestions which may increase or reduce this burden to: Chief, Information Policy Branch, PM-223, U.S. Environmental Protection Agency, 1200 Pennsylvania Avenue, NW, Washington, DC 20460, or Director, Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

I. Outfall Location

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

A. Outfall Number (list)	B. Latitude			C. Longitude			D. Receiving Water (name)
FSUR Stormwater	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea
Gas Port Stormwater	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea

II. Improvements


A. Are you now required by any Federal, State, or local authority to meet any implementation schedule for the construction, upgrading or operation of wastewater treatment equipment or practices or any other environmental programs which may affect the discharges described in this application? This includes, but is not limited to, permit conditions, administrative or enforcement orders, enforcement compliance schedule letters, stipulations, court orders, and grant or loan conditions.

1. Identification of Conditions, Agreements, Etc.	2. Affected Outfalls		3. Brief Description of Project	4. Final Compliance Date	
	number	source of discharge		a. req.	b. proj.
NONE	NA	NA	NA		

B: You may attach additional sheets describing any additional water pollution (or other environmental projects which may affect your discharges) you now have under way or which you plan. Indicate whether each program is now under way or planned, and indicate your actual or planned schedules for construction.

III. Site Drainage Map

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfalls(s) covered in the application if a topographic map is unavailable) depicting the facility including: each of its intake and discharge structures; the drainage area of each storm water outfall; paved areas and buildings within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage of disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids from the facility are injected underground; springs, and other surface water bodies which received storm water discharges from the facility.



LOCATION MAP



Legend



- ★ Proposed Offshore Terminal
- Proposed Pipeline Route

Sources:
NOAA Raster Navigational Chart 25687
NOAA Office of Coast Survey

Notes:
Sounding displayed in feet at MLLW



Kilometers



Statute Miles

excelerate
energy

Figure 1
Project and Outfall Location Map

June 2013





Figure 2 Jobos Bay Watershed and Drainage Area.




Agency Date, Oct 31, 2006

Adapted from PRDNER, undated. Jobos Bay National Estuarine Research Reserve. Management Plan Final 2010-2015
 (www.dnra.gobierno.pr/.../JobosBayManagementPlanFINALdecember.)

[illegible]

02/01/2012 12:01 PM



11


All Year
NORTH

45%




in/sec
27 - 30
24 - 27

WILLIAMS PLATING CO
TOP DECK +16m




BDS - U/S
PLATFORM LEVEL +15m



LNGC

FSRU



3/10/2018

Technica Limited

[illegible]

411-1000-0-000-010

END PAGE

© COPYRIGHT TECHNICAL LTD. THIS DOCUMENT AND THE INFORMATION CONTAINED UPON IT REMAINS THE INTELLECTUAL PROPERTY OF TECHNICAL LTD. ANY CHANGES OR COPIES OF THIS DOCUMENT OR INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF TECHNICAL LTD.

IV. Narrative Description of Pollutant Sources

A. For each outfall, provide an estimate of the area (include units) of impervious surfaces (including paved areas and building roofs) drained to the outfall, and an estimate of the total surface area drained by the outfall.

Outfall Number	Area of Impervious Surface (provide units)	Total Area Drained (provide units)	Outfall Number	Area of Impervious Surface (provide units)	Total Area Drained (provide units)
FSRU Over deck stormwater	Flat Deck area of FSRU approximates 300 m x 50 m	Approx. 15,000 square meters (m2)	Gas Port Overdeck Stormwater	Gas Port Deck Area estimated to be 7,300 m2 and Gas Port access walk ways estimated to be 1900 m2.	Approx. 9,200 m2

B. Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored or disposed in a manner to allow exposure to storm water; method of treatment, storage, or disposal; past and present materials management practices employed to minimize contact by these materials with storm water runoff; materials loading and access areas, and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied.

This is a proposed facility:

The FSRU will be moored to the Gas Port facility. This will be an operating, moored ship located off the coast of Jobos Bay which will act as a floating storage and regasification unit (FSRU) that will regasify liquidified natural gas (LNG) from LNG carriers for use by the Aguirre Power Station operated by the Puerto Rico Power Authority (PREPA). Operations of this vessel will include the use of machinery requiring lubrication, (oil and grease), hydraulic fluids and similar petroleum based fluids. Routine operation and maintenance of this machinery may result in the incidental/accidental leakage of such fluids onto deck areas. Such leakage will be captured via dip pans and collected and treated accordingly.


The Gas Port platform will be a manned deck platform area supporting diesel fuel generators and diesel fuel tanks. It will also support hydraulic oil tanks. Fuel or oil tank units will have associated bunds (with equivalent volume of 120% for spill/leak containment).

C. For each outfall, provide the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of the treatment the storm water receives, including the schedule and type of maintenance for control and treatment measures and the ultimate disposal of any solid or fluid wastes other than by discharge.

Outfall Number	Treatment	List Codes from Table 2F-1
FSRUSW	Openings of deck drains/ports will be lined with oil and grease absorbent pigs to filter out oil and grease prior to discharge. Equipment and piping connections that have potential to leak will have dedicated drip pan installed below which will capture any incidental leakage of oil or grease. These pans will be inspected regularly. Any accumulated oil or grease will be recovered and treated accordingly.	1-X
GasPortSW	Diesel fuel and hydraulic oil tanks on Gas Port platform will be surrounded by containment bunds equal to 120% of the tank volume.	1-X

V. Nonstormwater Discharges

A. I certify under penalty of law that the outfall(s) covered by this application have been tested or evaluated for the presence of nonstormwater discharges, and that all nonstormwater discharged from these outfall(s) are identified in either an accompanying Form 2C or Form 2E application for the outfall.

Name and Official Title (type or print)	Signature	Date Signed
EDWARD SCOTT, COO		3 July 2013

B. Provide a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test.

Proposed operation - No Data Available

VI. Significant Leaks or Spills

Provide existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years, including the approximate date and location of the spill or leak, and the type and amount of material released.

No data available. This is a proposed facility.

VII. Discharge Information

A, B, C, & D: See instructions before proceeding. Complete one set of tables for each outfall. Annotate the outfall number in the space provided.
Table VII-A, VII-B, VII-C are included on separate sheets numbers VII-1 and VII-2.

E. Potential discharges not covered by analysis — Is any toxic pollutant listed in table 2F-2, 2F-3, or 2F-4, a substance or a component of a substance which you currently use or manufacture as an intermediate or final product or byproduct?

☐ Yes (list all such pollutants below)

☒ No (go to Section IX)

VIII. Biological Toxicity Testing Data

Do you have any knowledge or reason to believe that any biological test for acute or chronic toxicity has been made on any of your discharges or on a receiving water in relation to your discharge within the last 3 years?

☐ Yes (list all such pollutants below)

☒ No (go to Section IX)

IX. Contract Analysis Information

Were any of the analyses reported in Item VII performed by a contract laboratory or consulting firm?

☐ Yes (list the name, address, and telephone number of, and pollutants analyzed by, each such laboratory or firm below)

☒ No (go to Section X)

A. Name	B. Address	C. Area Code & Phone No.	D. Pollutants Analyzed

X. Certification

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.


A. Name & Official Title (Type Or Print)

EDWARD SCOTT, COO

B. Area Code and Phone No.

832-813-7100

C. Signature



D. Date Signed

3 July 2013

Part A – You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

Part B –	List each pollutant that is limited in an effluent guideline which the facility is subject to or any pollutant listed in the facility's NPDES permit for its process wastewater (if the facility is operating under an existing NPDES permit). Complete one table for each outfall. See the instructions for additional details and requirements.	0.00	NA
----------	---	------	----

EPA Form 3510-2F (1-92) Page VII-1 Continue on Reverse

Continued from the Front

Part C - List each pollutant shown in Table 2F-2, 2F-3, and 2F-4 that you know or have reason to believe is present. See the instructions for additional details and requirements. Complete one table for each outfall.

[illegible]

Part D – Provide data for the storm event(s) which resulted in the maximum values for the flow weighted composite sample.

1. Date of Storm Event	2. Duration of Storm Event (in minutes)	3. Total rainfall during storm event (in inches)	4. Number of hours between beginning of storm measured and end of previous measurable rain event	5. Maximum flow rate during rain event (gallons/minute or specify units)	6. Total flow from rain event (gallons or specify units)
NA	NA	NA	NA	NA	NA

7. Provide a description of the method of flow measurement or estimate.

NA

EPA I.D. NUMBER (copy from Item 1 of Form 1)



New Sources and New Dischargers

Application for Permit to Discharge Process Wastewater

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.


Outfall Number (list)	Latitude			Longitude			Receiving Water (name)
	Deg.	Min.	Sec.	Deg.	Min.	Sec.	
001A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
002A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
003A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
004 A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
005 A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)

06/30/2015

A. For each outfall, provide a description of: (1) All operations contributing wastewater to the effluent, including process wastewater, sanitary wastewater, cooling water, and storm water runoff; (2) The average flow contributed by each operation; and (3) The treatment received by the wastewater. Continue on additional sheets if necessary.

[illegible]

Please print or type in the unshaded areas only	EPA I.D. NUMBER (copy from Item 1 of Form 1)	
---	--	--

Form 2D NPDES	 EPA	New Sources and New Dischargers Application for Permit to Discharge Process Wastewater
----------------------------	--	---

I. Outfall Location

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

Outfall Number (list)	Latitude			Longitude			Receiving Water (name)
	Deg.	Min.	Sec.	Deg.	Min.	Sec.	
006A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
007	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long. of Floating Storage and Regasification Unit (FSRU)
008	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long of Gas Port Platform Structure
009A/B	17.00	54.00	14.00	66.00	13.00	49.00	Caribbean Sea - Lat. and Long of Gas Port Platform Structure
010 Hydrstatic Test Water	17.00	57.00	48.00	66.00	13.00	37.00	Jobos Bay - Lat. and Long. of test water discharge

II. Discharge Date (When do you expect to begin discharging?).

06/30/2015

III. Flows, Sources of Pollution, and Treatment Technologies

A. For each outfall, provide a description of: (1) All operations contributing wastewater to the effluent, including process wastewater, sanitary wastewater, cooling water, and storm water runoff; (2) The average flow contributed by each operation; and (3) The treatment received by the wastewater. Continue on additional sheets if necessary.

[illegible]

C. Except for storm runoff, leaks, or spills, will any of the discharges described in Items III-A be intermittent or seasonal?

☐ NO (go to Section IV)

IV. Production

Year	A. Quantity Per Day	B. Units Of Measure	c. Operation, Product, Material, etc. (specify)
0.00	0.00	0	NA
0.00	0.00	0	NA
0.00	0.00	0	NA

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 001A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (*both concentration and mass*) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	17651	11767	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	103,942	55,501	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	1,137	784	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	39,223	11,767	3,4-Need to consider influent concentration
Flow (MGD)	47	47	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	94	47	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	38.2	38.2	Requires mixing zone application
Temperature (Summer) (oC)	44.2	44.2	Requires mixing zone application
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
Residual Chlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res. Chlorine (pounds/day)	59	49	3,4-Need to consider influent concentration

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 002A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	2,250	1,500	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	13,250	7,075	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	145	100	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	5,000	1,500	3,4-Need to consider influent concentration
Flow (MGD)	6	6	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	12	6	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	35.2	35.2	Requires mixing zone application
Temperature (Summer) (oC)	35.2	35.2	Requires mixing zone application
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
Residual Chlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res. Chlorine (pounds/day)	8	6	3,4-Need to consider influent concentration

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 003A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	225	150	3,4-Need to consider influent concentration
Chemical Oxygen Demand(ppm)	265	141.5	3,4-Need to consider influent concentration
COD(pounds/day)	1325	708	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	15	10	3,4-Need to consider influent concentration
Total Suspended Solids(ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	500	150	3,4-Need to consider influent concentration
Flow (MGD)	0.6	0.6	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	1.2	0.6	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
ResidualChlorine (ppm)	0.15	0.13	3,4-Need to considerinfluent concentration
Res.Chlorine (pounds/day)	0.8	0.6	3,4-Need to consider influent concentration

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (*both concentration and mass*) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	101	68	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	596	318	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	6.5	4.5	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	225	68	3,4-Need to consider influent concentration
Flow (MGD)	0.27	0.27	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	0.54	0.27	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
Residual Chlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res. Chlorine (pounds/day)	0.34	0.28	3,4-Need to consider influent concentration

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 005A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	26	17.3	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	153.4	81.4	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	1.7	1.2	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	58	17.3	3,4-Need to consider influent concentration
Flow (MGD)	0.069	0.069	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	0.14	0.07	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
Residual Chlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res. Chlorine (pounds/day)	0.09	0.07	3,4-Need to consider influent concentration
Coliforms (MPN/100 mL)	200	<200	3,4-Need to consider influent concentration

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	713	475	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	4,195	2,240	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	46	32	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	1,584	475	3,4-Need to consider influent concentration
Flow (MGD)	1.9	1.9	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	3.8	1.9	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
ResidualChlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res.Chlorine (pounds/day)	2.4	2.0	3,4-Need to consider influent concentration

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 007A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	23	15	3,4-Need to consider influent concentration
Chemical Oxygen Demand(ppm)	265	141.5	3,4-Need to consider influent concentration
COD(pounds/day)	133	71	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	1.5	1.0	3,4-Need to consider influent concentration
Total Suspended Solids(ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	50	15	3,4-Need to consider influent concentration
Flow (MGD)	0.06	0.06	FSRU Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	0.12	0.06	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
ResidualChlorine (ppm)	0.15	0.13	3,4-Need to considerinfluent concentration
Res.Chlorine (pounds/day)	0.08	0.06	3,4-Need to consider influent concentration

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	36	24	3,4-Need to consider influent concentration
Chemical Oxygen Demand (ppm)	265	141.5	3,4-Need to consider influent concentration
COD (pounds/day)	210	112	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	2.3	1.6	3,4-Need to consider influent concentration
Total Suspended Solids (ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	80	24	3,4-Need to consider influent concentration
Flow (MGD)	0.095	0.095	Gas Port Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	0.19	0.10	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
Residual Chlorine (ppm)	0.15	0.13	3,4-Need to consider influent concentration
Res.Chlorine (pounds/day)	0.12	0.10	3,4-Need to consider influent concentration

CONTINUED FROM THE FRONT	EPA I.D. NUMBER (copy from Item 1 of Form 1)	Outfall Number 009A/B
--------------------------	--	--------------------------

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (both concentration and mass) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	450	300	3,4-Need to consider influent concentration
Chemical Oxygen Demand(ppm)	265	141.5	3,4-Need to consider influent concentration
COD(pounds/day)	2,650	1,415	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	29	20	3,4-Need to consider influent concentration
Total Suspended Solids(ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	1,000	300	3,4-Need to consider influent concentration
Flow (MGD)	1.2	1.2	Gas Port Water Balance
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	2.4	1.2	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
ResidualChlorine (ppm)	0.15	0.13	3,4-Need to considerinfluent concentration
Res.Chlorine (pounds/day)	1.5	1.3	3,4-Need to consider influent concentration

V. Effluent Characteristics

A and B: These items require you to report estimated amounts (*both concentration and mass*) of the pollutants to be discharged from each of your outfalls. Each part of this item addresses a different set of pollutants and should be completed in accordance with the specific instructions for that part. Data for each outfall should be on a separate page. Attach additional sheets of paper if necessary.

General Instructions (See table 2D-2 for Pollutants)

Each part of this item requests you to provide an estimated daily maximum and average for certain pollutants and the source of information. Data for all pollutants in Group A, for all outfalls, must be submitted unless waived by the permitting authority. For all outfalls, data for pollutants in Group B should be reported only for pollutants which you believe will be present or are limited directly by an effluent limitations guideline or NSPS or indirectly through limitations on an indicator pollutant.

1. Pollutant	2. Maximum Daily Value (include units)	3. Average Daily Value (include units)	4. Source (see instructions)
Bio.Oxygen Demand (ppm)	45	30	3,4-Need to consider influent concentration
BOD (pounds/day)	90	60	3,4-Need to consider influent concentration
Chemical Oxygen Demand(ppm)	265	141.5	3,4-Need to consider influent concentration
COD(pounds/day)	530	283	3,4-Need to consider influent concentration
Total Organic Carbon (ppm)	2.9	2.0	3,4-Need to consider influent concentration
TOC (pounds/day)	5.8	4.0	3,4-Need to consider influent concentration
Total Suspended Solids(ppm)	100	30	3,4-Need to consider influent concentration
TSS (pounds/day)	200	60	3,4-Need to consider influent concentration
Flow (MGD)	0.24	0.24	Est. Hydrostatic Water Need/Test
N-Ammonia (ppm)	0.24	0.12	3,4-Need to consider influent concentration
N-Ammonia (pounds/day)	0.48	0.24	3,4-Need to consider influent concentration
Temperature (Winter) (oC)	32.2	32.2	PREQB Standard or ambient
Temperature (Summer) (oC)	32.2	32.2	PREQB Standard or ambient
pH (su)	7.3 to 8.5	7.3 to 8.5	PREQB Standard
ResidualChlorine (ppm)	-	-	No chlorine treatment applied
Res.Chlorine (pounds/day)	-	-	No chlorine treatment applied

CONTINUED FROM THE FRONT		EPA I.D. NUMBER (copy from Item 1 of Form 1)
C. Use the space below to list any of the pollutants listed in Table 2D-3 of the instructions which you know or have reason to believe will be discharged from any outfall. For every pollutant you list, briefly describe the reasons you believe it will be present.		
1. Pollutant	2. Reason for Discharge	
NA	NA	

VI. Engineering Report on Wastewater Treatment

A. If there is any technical evaluation concerning your wastewater treatment, including engineering reports or pilot plant studies, check the appropriate box below.

☐ Report Available

☒ No Report

B. Provide the name and location of any existing plant(s) which, to the best of your knowledge resembles this production facility with respect to production processes, wastewater constituents, or wastewater treatments.

Name	Location
Northeast Gateway Energy Bridge Project NPDES Permit MA0040266	Atlantic Ocean, 13 miles offshore from Gloucester, MA
PREPA Aguirre Power Station Complex NPDES Permit PR0001660	Salinas, Puerto Rico

VII. Other Information (Optional)

Use the space below to expand upon any of the above questions or to bring to the attention of the reviewer any other information you feel should be considered in establishing permit limitations for the proposed facility. Attach additional sheets if necessary.

None of the constituent concentrations consider an influent based contribution which must be considered for ambient surface water conditions at time of withdrawal.

Biological Oxygen Demand (BOD) estimate based on Puerto Rico Electric Power Authority (PREPA) discharge limits in Aguirre Power Plant NPDES permit (PR 0001660)

Chemical Oxygen Demand (COD) estimate based on effluent characteristics provided in USEPA (1999) nature of discharge report.

Total Organic Carbon (TOC) estimate based on effluent characteristics provided in USEPA (1999) nature of discharge report.

Total Suspended Solids (TSS) estimate based on USEPA Storet database data for TSS concentrations in Caribbean Sea waters and the Puerto Rico Environmental Quality Board (PREQB) narrative standard of no net increase in suspended solids other than by natural causes.

Flows based on projected discharge under maximum water use scenario for the FSRU or Gasport.

Ammonia concentration estimates based on USEPA (1999) nature of discharge report (for estimate purposes only).

Temperature (Winter) not to exceed the PREQB maximum standard of 32.2 oC (90oF) within permissible mixing zone. Maximum temperature rise based on discharge monitoring reports for the Northeast Gateway Project NPDES permit modification. Excelerate Energy requests the application for a mixing zone for Outfalls 001A/B and 002A/B.

Temperature (Summer) not to exceed the PREQB maximum standard of 32.2 oC (90oF) within permissible mixing zone. Maximum temperature rise based on discharge monitoring reports for the Northeast Gateway Project NPDES permit modification. Excelerate Energy requests the application for a mixing zone for Outfalls 001A/B and 002A/B.

Ph based on ambient conditions and PREQB standard of not to occur outside the range of 6.3 to 8.5 su

Residual chlorine levels based on anticipated residual levels for effective treatment for control of marine biofouling in water intake systems.

Excelerate Energy requests a PRDEQB mixing zone for Outfall 001A/B and Outfall 002A/B.

VIII. CERTIFICATION

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.


A. Name and Official Title (type or print)

EDWARD SCOTT, GOO

B. Phone No.

832-813-7100

C. Signature



D. Date Signed

3 July 2013



EXCELERATE ENERGY
Aguirre Offshore GasPort Project

**Thermal Plume Modeling Assessment
- Water Use and Quality**

July 11, 2012

Table of Contents

Section	Page
1.0 Introduction	1
2.0 Model Selection and Approach	2
3.0 Model Results for FSRU Outfall 001	3
4.0 Model Results for FSRU Outfall 002	4
5.0 Model Results for LNGC Thermal Discharge	4
6.0 Potential for Bed Scour	5
7.0 Summary and Conclusions	5
References	9
Figures	11
Appendix 1 VISUAL PLUMES Output Files	17
Appendix 2 JETLAG Output Files	30

List of Tables

Table 1	FSRU and LNGC Discharge Properties	2
Table 2	Locations at Which Temperature Criterion Are Met for FSRU Outfall 001 Based on the CORMIX Model	6
Table 3	Locations at Which Temperature Criterion Are Met for FSRU Outfall 001 Based on the VISUAL PLUMES UM3 Model	6
Table 4	Locations at Which Temperature Criterion Are Met for FSRU Outfall 001 Based on the JETLAG Model	6
Table 5	Locations at Which Temperature Criterion Are Met for FSRU Outfall 002 Based on the JETLAG Model	7
Table 6	Locations at Which Temperature Criterion Are Met for LNGC Thermal Discharge Based on the VISUAL PLUMES UM3 Model	7
Table 7	Locations at Which Temperature Criterion Are Met for LNGC Thermal Discharge Based on the JETLAG Model	7

List of Figures

Figure 1	Vertical plane trajectory for FSRU Outfall 001 with Discharge 5.3 meters below surface and no ambient current	9
Figure 2	Vertical plane trajectory for FSRU Outfall 001 with Discharge 5.3 meters below surface and a 0.10 m/s ambient current	10
Figure 3	Vertical plane trajectory for FSRU Outfall 002 with Discharge 6.3 meters below surface and no ambient current	11
Figure 4	Vertical plane trajectory for FSRU Outfall 002 with Discharge 6.3 meters below surface and a 0.10 m/s ambient current	12

Table of Contents (Cont'd)

List of Figures (Cont'd)

Figure 5	Vertical plane trajectory for LNGC Thermal Discharge with Discharge 5.3 meters below surface and no ambient current	13
Figure 6	Vertical plane trajectory for LNGC Thermal Discharge with Discharge 5.3 meters below surface and a 0.10 m/s ambient current	14

1.0 Introduction

The following memorandum documents the results of the thermal discharge modeling for the Aguirre Offshore GasPort Project. This evaluation documents the modeling of the thermal discharges from a Floating Storage and Regasification Unit (FSRU) and a Liquefied Natural Gas Carrier (LNGC) at the Aguirre Offshore GasPort project off the southern coast of Puerto Rico, offshore from the inlet to Jobos Bay. Separate thermal discharges from the fixed FSRU, a permanently moored EBRV continuously providing natural gas to the Aguirre Power Plant, and an intermittently moored LNGC, transferring liquefied natural gas (LNG) to the FSRU will be considered.

Discharge and Ambient Characteristics

Heated discharge properties and ambient conditions were assembled for FSRU Outfalls 001 and 002 and are summarized in Table 1. Flow rates, port diameters, orientations, and depths below the surface were taken for vessel specification. It is assumed that the discharges exist normally beneath the vessel hull and due to the length of the vessels, ambient currents are parallel to the vessel. The temperature rise of 12 °C for the FSRU Outfalls was based on operating records and renewal of the Northeast Gateway National Pollutant Discharge Elimination System (NPDES) Permit. Less information is available for the LNGC discharge. Provided data include the 2.72 cm/sec discharge and the 3 °C temperature rises based on data from the Jordan Cove FEIS. Other port data were taken as the same as the FSRU Outfall 001. Ambient temperature data were taken. Other port data were taken as the same as the FSRU Outfall 001. Ambient temperature data were taken as the maximum mean monthly average surface temperature from the Metocean Study (Forristall, 2010). Mean lower low water (MLLW) depths were taken from the NOAA chart with a depth of approximately 18.3 meters. NOAA Etopo01 (<http://www.ngdc.noaa.gov/mgg/global/global.html>) depths for the region were slightly deeper with a value of 20.95 meters. Generally shallow depths are more critical with respect to plume mixing so a value of 19.2 meters (applying 0.67 chart + 0.33 etopo values for estimating ambient depth to bottom) was used. Detailed bathymetry data collected for the Aguirre Gasport Project confirm 18.8 to 19.1 meter depth intervals at the proposed location. The location of the vessel discharge port for Outfall 001 and 002 was modeled using the minimum and maximum depth ranges presented in Table 1. Discharge port depth for the LNGC was assumed to be similar to that for the FSRU (Table 1).

High current velocities tend to result in rapid mixing and high dilution rates making low current speeds more critical for plume temperature dissipation. For this study, two cases were considered, no ambient currents (0 m/sec) and a low ambient current speed of 0.10 meter/sec parallel to the vessel hull and normal to the discharge port orientation. Tidal current data on the southern coast of Puerto Rico is sparse with Morelock, et al (undated) estimating maximum tidal current speeds of 0.1 to 0.2 meters per second. Mean current are of a similar magnitude. Thus the two current cases considered in this analysis are very conservative.

Puerto Rico has a maximum temperature criteria of 32.2° C (90° F) which with is used to define impacted areas for the plume temperature field and the possible need for a mixing zone. The US EPA Technical Guidance (US EPA, 1991) defines a number of approaches for defining mixing zones based on discharge characteristic. The approach most appropriate for this situation is defining the mixing zone as a distance equal to 50 times the discharge length scale in all directions. The resulting mixing zone lengths are 62 and 17.5 meters (201 and 57 feet) for

Outfalls 001 and 002 respectively for the FSRU and 62 meters for the LNGC main condenser discharge,

2.0 Model Selection and Approach

A number of models are available for thermal jet-plume evaluation including CORMIX (Doneker and Jirka, 2007), VISUAL PLUMES (VP) (Frick, et al., 2003), and JETLAG/VISIJET (JETLAG) (Lee and Cheung, 1990; Lee and Chu, 2003; Choi and Lee, 2007) which model single and multiport discharges into a non-evolving ambient environment. For complex discharge situations where multiple, potentially interacting discharges, or the need to address potential recirculation into intakes, or the presence of evolving ambient conditions, the Environmental Fluid Dynamics Code (EFDC) model (<http://www.epa.gov/ceampubl/swater/efdc/index.html>), is recommended. The EFDC model is three-dimensional hydrodynamic and transport model which includes an embedded version of JETLAG making it possible to simulate multiple intakes and thermal discharges in high complex and evolving ambient environments.

All of the four proposed models are recognized and accepted by regulatory agencies. CORMIX and VISUAL PLUMES were developed by US EPA and are widely used for mixing zone studies. JETLAG is widely used internally and has been accepted for mixing zone studies in US EPA Region 4 (Tetra Tech, 2008a, 2008b, 2010). The modeling approach used in this study is to use all three models, CORMIX, VISUAL PLUMES and JETLAG to simulate the discharge plume primarily since CORMIX fails to provide complex results. The relatively short trajectories to the location meeting the 32.2° C temperature criteria indicate that recirculation into the intake and tidal double dosing are not important and that an embedded buoyant jet in a larger scale EFDC model is not necessary.

Table 1. FSRU and LNGC Discharge Properties

Vessel Discharge Property	FSRU Discharge 1 Outfall 001	FSRU Discharge 2 Outfall 002	LNGC Thermal Discharge
Flow Rate, (cubic meters per second)	2.06	0.26	2.72
Discharge Port Diameter, (meters)	1.4	0.4	1.4
Port Area, (square meters)	1.54	0.126	1.54
Length Scale (square root of area), (meters)	1.24	0.35	1.24
Port Discharge Velocity, (meters/se)	1.34	2.06	1.34
Discharge Angle from Horizontal, (degrees)	-45	-45	-45
Discharge Angle form Ambient Flow, (degrees)	90	90	90
Discharge Depth Range, (meters)	5.3 – 7.4	6.3 -8.4	5.3 – 7.4
Discharge Temperature Above Ambient (° C)	12	12	3
Maximum Ambient Temperature, (° C)	29.6	29.6	29.6
Water Depth, (meters)	19.2	19.2	19.2
Mean Tidal or Ambient Current, (meters/sec)	0.10	0.10	0.10
Not to Exceed Temperature Criteria, (° C)	32.2	32.2	32.2
EPA Guidance Mixing Zone (50 x length scale), (meters)	62	17.5	62

3.0 Model Results for FSRU Outfall 001

Model results for FSRU Outfall 001 are presented in Tables 2 through 4. Results for CORMIX are shown in Table 2. CORMIX predicts that the plume impacts the bottom but provides no vertical trajectory prior to impact. Once the plume impacts the bottom, the plume is modeled as a bottom attached half plume with dilution output as a function of distance from the discharge provided. For the case based on no current and discharge depths below the surface of 5.3 and 6.35 meters, the 32.2 °C temperature criteria is met at 42 meters, which is within the proposed 62 meter mixing zone for Outfall 001. For the 0.10 meter/second current case, the distance to meeting the temperature criteria is reduced to 28 meters. For the 7.4 meter discharge depth CORMIX fails to provide solutions. Given the unsatisfactory performance of CORMIX, this model was not considered appropriate for the set of parameters applied and shallow water depths present. Therefore, additional simulations were conducted with VISUAL PLUMES and JETLAG to assess the thermal discharge

Table 3 shows results for the simulation using the VISUAL UM3 module for FSRU Outfall 001. The model behaves quite differently than CORMIX and does not impact the bottom but approaches the bottom and then rises towards the surface. For the three port depth cases, the no ambient current scenario identifies the temperature criterion to be met at horizontal distances of 12.2 and 13.4 meters. Depths to meet the criteria start at 9.6 meter and decrease by approximately a meter for the successive depths below the surface. With a 0.1 meter/sec ambient velocity, the horizontal distance is reduced 6.3 meters due to an increase in ambient water entrainment caused by the modeled current. Depths to meet the criteria are similar to the no current case with depths to attainment in the range of 9.6 to 11.7 meters (Table 3).

Results for the application of JETLAG to FSRU Outfall 001 are presented in Table 4. The JETLAG model predicts bottom impact of the plume based on the edge of the plume intersecting the bottom. However if bottom impact was based on plume center line impacting the bottom there would be not bottom impact and the plume behavior would be similar to the falling and rising trajectory of VISUAL PLUMES whose impact criteria were not available. For the no ambient current case, JETLAG predicts somewhat larger horizontal distances, (15.3 meters or less), to meeting the temperature criteria. For the 6.35 and 7.4 meter port discharge depths, temperature at bottom impact is slightly over the criteria, but the criteria should be subsequently reached in less than one meter due additional mixing in the bottom boundary layer. Depths at which the temperature criterion are met are also larger than those predicted by VISUAL PLUMES. For the cases with ambient current horizontal distance to meet the temperature criteria are 8.6 meters, again somewhat larger than the VISUAL PLUMES predictions. Depths at which the criteria are met range from 12.4 to 14.5 meters.

From these results it is seen that the VISUAL PLUMES and JETLAG models produce consistent results with JETLAG being slightly more conservative in predicting longer distances to meet the 32.2 °C temperature criterion. However these predicted longer distances remain well within the proposed 62 meter mixing zone for Outfall 001. To provide a feel for VISUAL PLUMES and JETLAG results, Figures 1 and 2 present the vertical plane trajectories for the 5.3 meter below the surface discharge port cases without and with ambient current using JETLAG. JETLAG results are presented due to JETLAG having more refined graphics capabilities than the VISUAL PLUMES software. JETLAG predicts the possibility for the discharge plume to come into contact with the bottom but only when considering the edge of the plume perimeter. Both

models do predict the plume to turn and dissipate with both ambient distance and current conditions

4.0 Model Results for FSRU Outfall 002

The discharge from FSRU Outfall 002 was simulated with only JETLAG due to limitation with CORMIX and VISUAL PLUME handling buoyancy dominated, downward discharge angles. The results of the JETLAG simulations are shown in Table 5. For the no ambient current scenario, the plume is buoyancy dominated and immediately re-orientes from a downward to an upward trajectory as shown in Figure 3. The temperature criterion is met at a horizontal distance of 1.9 meters and a vertical distance of 5.1 to 7.2 meter below the surface for the 6.3, 7.35, and 8.4 meter port discharge depths. In actuality, the near vertical plume from Outfall 002 would hug the vessel hull as it rises to the surface. For the case with a nominal ambient current (0.1 m/sec) the plume is slightly deflected into the horizontal plane due to the influence of the ambient current momentum (see Figure 4) and the increased entrainment reduces the horizontal distance to which the criteria is met is 0.5 meters or less. Depths below the water surface at which the criteria are met range from 6.7 to 8.8 meters. The plume trajectory ends below the surface where the plume density and ambient density differ by less than one per cent. The plume with ambient current will also in actuality hug the vessel hull. In all cases the temperature criterion is met well within the proposed 17.5 meter mixing zone.

5.0 Model Results for LNGC Thermal Discharge

The only information for the LNGC thermal discharge is a discharge rate of 2.72 cm/sec and a projected temperature rise of 3° C based on the characteristics of the Jordan Cove Project (FERC, 2009). In the absence of available data on port characteristics for the LNGC, the port diameter, orientation and discharge depths for FSRU Outfall 001 were used. Due to the 32 % higher discharge rate and four fold reduction in buoyancy, the jet plume will impact the bottom for all discharge depths. Since the CORMIX model does not provide complete information for a bottom impact situation, the LNGC thermal discharge was modeled only with VISUAL PLUMES and JETLAG.

Results for the VISUAL PLUMES simulations are summarized in Table 6. VISUAL PLUMES first output is the horizontal distance to sea bottom impact. Since the corresponding vertical positions are above the bed, it is inferred that bottom impact will be along the plume edges similar to JETLAG results for the FSRU predictions. Temperatures at the point of bottom impact are much lower than the discharge temperature of 32.6° C and the criterion temperature of 32.2° C. Horizontal distances to bottom impact range from 9.4 to 12 meters, well within the proposed 62 meter mixing zone based to 50 times the port length scale.

To get a more detail resolution of the jet-plume and the actual locations at which the temperature criterion will be met, JETLAG was used to simulate the 6 discharge scenarios summarized in Table 7. For the no ambient flow scenario, the temperature criterion is met at a horizontal distance of 0.82 meters. Corresponding depths at which the criteria are met range from 6.1 to 8.2 meters for discharges depths ranging from 5.3 to 7.4 meters. For the scenarios with a 0.1 m/sec ambient current, the temperature criterion is met at a horizontal distance of 0.41 meters (Table 7). Depths at which the temperature criterion are met range from 5.7 to 7.8 meters for discharge depths ranging from 5.3 to 7.4 meters. Graphical results corresponding to the 5.3 meter discharge depth case without and with an ambient current are shown in Figures 5 and 6,

respectively. Due to the high moment flux and small temperature rise, the 32.2° C temperature criterion is met within less than a port diameter distance from the vessel discharge.

6.0 Potential for Bed Scour

The VISUAL PLUMES simulation for FSRU Outfall 001 did not predict interaction of the discharge plume with the sea bottom. JETLAG predicted some potential for interaction of the FSRU and LNGC plume edge with the sea bottom for the main condenser outfalls for all port depths. The 7.4 meter discharge depth cases for the LNGC thermal discharges resulted in the highest jet velocities at the point of bottom impact. Since the ambient current entrains more slower moving ambient water as well as deflecting the plume more to the horizontal, the case with no ambient current results in the higher impact velocity of 0.46 meters/sec. Assuming a conservatively stress coefficient of 0.025, the 0.46 meter/sec velocity produces a bed stress of 0.53 Pa (Newtons/square meter) and a corresponding shear velocity of 0.023 m/sec. For sand beds, the stability of the bed can be determined using the Shield's criteria for incipient motion (Garcia, 2008). For the 0.023 m/sec shear velocity, the stable sediment grain size is approximately 1 mm, which is the boundary between coarse and very coarse sand. When the first discharge of the plume occurs, material finer than 1 mm, if present, will be eroded with coarser material transported as bed load and finer material as suspended load. However with the initial removal of the fine material, the bed will be eventually be sorted and armor as the concentration of coarse material at the bed surface increases.

7.0 Summary and Conclusions

The simulations and analysis summarized in this memoranda indicate that the 32.2° C maximum temperature criteria will be met for the FSRU and LNGC thermal discharges well within calculated mixing zones based on the 50 times the port length scale (square root of port area) US EPA guidance (US EPA 1991). This conclusion is strongly supported by the unique approach of using three different buoyant jet models: CORMIX, VISUAL PLUMES and JETLAG. The unique characteristic of the discharges and ambient conditions results in FSRU Outfall 001 and the LNGC thermal discharge strongly interacting with the bottom or impacting the bottom. This interaction or potential for impact was not adequate in projecting bottom trajectory. For these two discharges, the CORMIX model did not provide the required level of results and the VISUAL PLUMES and JETLAG models were applied and yielded consistent results. For the initially downward but rapidly bending FSRU Outfall 002, the Lagrangian formulation of JETLAG provided detailed information which could not be obtained from the other two models.

For the FSRU and LNGC, the achievement of the 32.2 °C temperature criterion was attained well within the predicted mixing zones for all the modeled outfalls. The potential for interaction of the plumes with the sea bottom could result in some re-suspension and sorting of the bottom sediments. This effect however would be dependent upon the grain size of sediments present and the plume velocity at impact. Fine grained sediments such as silts and clays would be entrained and re-suspended in the water column during the early the initial start-up of the FSRU and LNGC operations. Available data for the sediments at the proposed the offshore terminal location indicate a mixture of coarse and shell fragments of a texture and grain size less prone to erosion based on project plume velocities near the bottom. The discharge velocity selected for the modeling effort chose a conservative value (the higher end of the range observed in similar vessels) and thus affords some degrees of conservativeness in the plume modeling exercise in predicting the interaction of thermal plume with the sea bottom.

Table 1. FSRU and LNGC Discharge Properties

Vessel Discharge Property	FSRU Discharge 1 Outfall 001	FSRU Discharge 2 Outfall 002	LNGC Thermal Discharge
Flow Rate, (cubic meters per second)	2.06	0.26	2.72
Discharge Port Diameter, (meters)	1.4	0.4	1.4
Port Area, (square meters)	1.54	0.126	1.54
Length Scale (square root of area), (meters)	1.24	0.35	1.24
Port Discharge Velocity, (meters/se)	1.34	2.06	1.34
Discharge Angle from Horizontal, (degrees)	-45	-45	-45
Discharge Angle form Ambient Flow, (degrees)	90	90	90
Discharge Depth Range, (meters)	5.3 – 7.4	6.3 -8.4	5.3 – 7.4
Discharge Temperature Above Ambient (° C)	12	12	3
Maximum Ambient Temperature, (° C)	29.6	29.6	29.6
Water Depth, (meters)	19.2	19.2	19.2
Mean Tidal or Ambient Current, (meters/sec)	0.10	0.10	0.10
Not to Exceed Temperature Criteria, (° C)	32.2	32.2	32.2
EPA Guidance Mixing Zone (50 x length scale), (meters)	62	17.5	62

**Table 2. Locations at Which Temperature Criterion Are Met for FSRU Outfall 001
Based on the CORMIX Model**

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/ Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	5.3	0	32.2	42	19.2*
2	6.35	0	32.2	42	19.2*
3	7.4	0	na	na	na
4	5.3	0.1	32.2	28	19.2*
5	6.35	0.1	32.2	28	19.2*
6	7.4	0.1	na	na	na

* Bottom impact with no intermediate trajectory information provided

**Table 3. Locations at Which Temperature Criterion Are Met for FSRU Outfall 001
Based on the VISUAL PLUMES UM3 Model**

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	5.3	0	32.2	12.2	9.6
2	6.35	0	32.2	12.2	10.7
3	7.4	0	32.2	12.2	11.8
4	5.3	0.1	32.2	6.3	9.6
5	6.35	0.1	32.2	6.3	10.8
6	7.4	0.1	32.2	6.3	11.7

**Table 4. Locations at Which Temperature Criterion Are Met for FSRU Outfall 001
Based on the JETLAG Model**

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	5.3	0	32.2	15.2	15.5
2	6.35	0	32.4	13.1	16.0
3	7.4	0	32.6	11.5	16.4
4	5.3	0.1	32.2	8.6	12.4
5	6.35	0.1	32.2	8.6	13.5
6	7.4	0.1	32.2	8.6	14.5

**Table 5. Locations at Which Temperature Criterion Are Met for FSRU Outfall 002
Based on the JETLAG Model**

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	6.3	0	32.2	1.9	5.1
2	7.35	0	32.2	1.9	6.2
3	8.4	0	32.2	1.9	7.2
4	6.3	0.1	32.2	0.5	6.5
5	7.35	0.1	32.2	0.5	7.6
6	8.4	0.1	32.2	0.4	8.8

Table 6. Locations at Which Temperature Criterion Are Met for LNGC Thermal Discharge Based on the VISUAL PLUMES UM3 Model

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	5.3	0	32.2	<12.0*	<16.4*
2	6.35	0	32.2	<11.0*	<16.4*
3	7.4	0	32.2	<10.0*	<16.4*
4	5.3	0.1	32.2	<9.4*	<14.8*
5	6.35	0.1	32.2	<9.4*	<14.8*
6	7.4	0.1	32.2	<9.8*	<15.4*

* Trajectory too coarse to provide near port information

Table 7. Locations at Which Temperature Criterion Are Met for LNGC Thermal Discharge Based on the JETLAG Model

Case	Discharge Depth, (meters)	Ambient Velocity, (meters/Second)	Criteria (32.2° C / 90° F) or Bottom Impact Temperature, (° C)	Horizontal Distance to Meet Criteria or to Bottom Impact, (meters)	Depth to Meet Criteria or to Bottom Impact, (meters)
1	5.3	0	32.2	0.82	6.1
2	6.35	0	32.4	0.82	7.2
3	7.4	0	32.6	0.82	8.2
4	5.3	0.1	32.2	0.41	5.7
5	6.35	0.1	32.2	0.41	6.8
6	7.4	0.1	32.2	0.41	7.8

References

- Choi, K. W., and J. H. W. Lee, 2007. Distributed Entrainment Sink Approach for Modeling Mixing and Transport in the Intermediate Field. *Journal of Hydraulic Engineering*, Vol. 133, No. 7, p 804-815. <http://www.aoe-water.hku.hk/visjet/release-note.htm>
- Doneker, R. L., and G. H. Jirka, 2007. CORMIX User Manual: A Hydrodynamic Mixing Zone Model and Decision Support System for Pollutant Discharges into Surface Waters. EPA-823-K-07-001, 236 pp. <http://www.cormix.info/index.php>
- Federal Energy Regulatory Commission (FERC), 2009. Final Environmental Impact Statement: Jordan Cove Energy and Pacific Connector Gas Pipeline Project. FERC/EIS 0223 F. May 2009.
- Forristall Ocean Engineering, Inc. 2010. Metocean Criteria Study for the South Coast of Puerto Rico. Prepared for Excelerate Energy. 59 pp.
- Frick, W. E., P.J.W. Roberts, L.R. Davis, J. Keyes, D.J. Baumgartner, and K.P. George. 2003. Dilution Models for Effluent Discharges, 4th Edition, (Visual Plumes). EPA/600/R-03/025. 148 pp. <http://www.epa.gov/ceampubl/swater/vplume>
- Garcia, M. (editor), 2008. Sedimentation Engineering: Processes, Measurements, Modeling, and Practice. ASCE Manuals and Reports on Engineering Practice No. 110, American Society of Civil Engineers. 1132 pp.
- Lee, J. H. W., and V. Cheung, 1990. Generalized Lagrangian model for buoyant jets in current. *Journal of Environmental. Engineering*. Vol. 116, No. 6, p 1085-1106. <http://www.aoe-water.hku.hk/visjet/release-note.htm>
- Lee, J. H. W., and V. Chu, 2003. Turbulent Jets and Plumes: A Lagrangian Approach, Kluwer Academic, Dordrecht.
- Morelock, J, J. Capella, J. R. Garcia, and M. Barreto, No Date. Puerto Rico- Seas at the Millennium. University of Puerto, Department of Geology, 13 pp. geology.uprm.edu/Morelock/pdffdoc/morlok2.pdf - Puerto Rico
- US EPA, 1991. Technical Support Document for Water Quality Based Toxic Control. EPA/505/2-90-001. 335 pp.
- Tetra Tech, Inc. 2008a. Mixing Zone Study for the City of Ormond Beach: Proposed Mixing Zone and Effluent Limits. Prepared for the City of Ormond Beach, FL by Tetra Tech Inc., Research Triangle Park, NC, 31 pp.
- Tetra Tech, Inc. 2008b. Proposed Relocation of the Havelock Wastewater Treatment Plant Discharge. Prepared for the City of Havelock, NC, by Tetra Tech Inc., Research Triangle Park, NC, 116 pp.

Tetra Tech, Inc. 2010. CFPUA Proposed Discharge Model Results. Prepared for the Cape Fear Public Utility Authority, Wilmington, NC, by Tetra Tech Inc., Research Triangle Park, NC, 32 pp.

Figures




Figure 1. Vertical plane trajectory for FSRU Outfall 001 with Discharge 5.3 meters below surface and no ambient current




Figure 2. Vertical plane trajectory for FSRU Outfall 001 with Discharge 5.3 meters below surface and a 0.10 m/s ambient current




Figure 3. Vertical plane trajectory for FSRU Outfall 002 with Discharge 6.3 meters below surface and no ambient current




Figure 4. Vertical plane trajectory for FSRU Outfall 002 with Discharge 6.3 meters below surface and a 0.10 m/s ambient current




Figure 5. Vertical plane trajectory for LNGC Thermal Discharge with Discharge 5.3 meters below surface and no ambient current




Figure 6. Vertical plane trajectory for LNGC Thermal Discharge with Discharge 5.3 meters below surface and a 0.10 m/s ambient current

FSRU 001 case 1

/ Windows UM3. 6/29/2012 11:10:06 AM

Case 1; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth    Amb-cur    Amb-dir    Amb-sal    Amb-tem    Amb-pol    Decay
Far-spd    Far-dir    Disprsn
      m          m/s          deg          psu          C          kg/kg          s-1
m/s          deg    m0.67/s2
      0.0          0.0          90.0          0.0          29.6          0.0          0.0
0.0          0.0          0.0
      19.2          0.0          90.0          0.0          29.6          0.0          0.0
0.0          0.0          0.0
P-dia P-elev V-angle H-angle    Ports AcuteMZ ChrncMZ P-depth Ttl-flo Eff-
sal    Temp Polutnt
      (m)      (m)      (deg)      (deg)      ( )      (m)      (m)      (m)      (m3/s)
(psu)      (C) (kg/kg)
      1.4      13.9    -45.0      0.0      1.0      62.0      62.0      5.3      2.06
0.0      41.6    1000.0
Froude number:      5.566
      Depth    Amb-cur    P-dia    Polutnt    Dilutn    x-posn    y-posn
Step      (m)      (m/s)      (m)      (kg/kg)      ( )      (m)      (m)
      0      5.3      0.0      1.4      1000.0      1.0      0.0      0.0; max
dilution reached
Potential for more dilution
100      10.6      0.0      6.288      263.5      3.783      8.749      0.0 104
10.61      0.0      6.396      259.3      3.844      9.003      0.0
107      10.61      0.0      6.472      256.4      3.888      9.191      0.0 152
9.912      0.0      7.191      219.0      4.55      11.97      0.0
200      6.341      0.0      7.826      164.6      6.052      15.92      0.0 220
1.813      0.0      8.595      127.5      7.816      18.57      0.0

```

FSRU 001 case2

/ Windows UM3. 6/29/2012 11:08:33 AM

Case 2; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth  Amb-cur  Amb-dir  Amb-sal  Amb-tem  Amb-pol  Decay
Far-spd  Far-dir  Disprsn
      m      m/s      deg      psu      C      kg/kg      s-1
m/s      deg  m0.67/s2
0.0      0.0      0.0      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0
0.0      19.2      0.0      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0
P-dia  P-elev V-angle H-angle  Ports AcuteMZ ChrnMZ P-depth Ttl-flo Eff-
sal  Temp Polutnt
      (m)      (m)      (deg)      (deg)      ( )      (m)      (m)      (m)      (m3/s)
(psu)      (C) (kg/kg)
1.4      12.85 -45.0      0.0      1.0      62.0      62.0      6.35      2.06
0.0      41.6      1000.0
Froude number:      5.566
      Depth  Amb-cur  P-dia  Polutnt  Dilutn  x-posn  y-posn
Step  (m)      (m/s)      (m)      (kg/kg)      ( )      (m)      (m)
0      6.35      0.0      1.4      1000.0      1.0      0.0      0.0; max
dilution reached
Potential for more dilution
100      11.65      0.0      6.288      263.5      3.783      8.749      0.0 104
11.66      0.0      6.396      259.3      3.844      9.003      0.0
107      11.66      0.0      6.472      256.4      3.888      9.191      0.0 152
10.96      0.0      7.191      219.0      4.55      11.97      0.0
200      7.391      0.0      7.826      164.6      6.052      15.92      0.0 223
1.775      0.0      8.799      120.7      8.256      19.06      0.0

```

FSRU 001 case3

/ Windows UM3. 6/29/2012 11:06:49 AM

Case 3; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth  Amb-cur  Amb-dir*  Amb-sal  Amb-tem  Amb-pol  Decay
Far-spd  Far-dir  Disprsn
      m      m/s      deg      psu      C      kg/kg      s-1
m/s      deg  m0.67/s2
0.0      0.0      0.0      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0
P-dia  P-elev V-angle H-angle  Ports AcuteMZ ChrncMZ P-depth Ttl-flo Eff-
sal  Temp Polutnt
      (m)      (m)      (deg)      (deg)      ( )      (m)      (m)      (m)      (m3/s)
(psu)      (C)      (kg/kg)
1.4      11.8      -45.0      0.0      1.0      62.0      62.0      7.4      2.06
0.0      41.6      1000.0
Froude number:      5.566
      Depth  Amb-cur  P-dia  Polutnt  Dilutn  x-posn  y-posn
Step      (m)      (m/s)      (m)      (kg/kg)      ( )      (m)      (m)
0      7.4      0.0      1.4      1000.0      1.0      0.0      0.0; max
dilution reached
Potential for more dilution
100      12.7      0.0      6.288      263.5      3.783      8.749      0.0 104
12.71      0.0      6.396      259.3      3.844      9.003      0.0
107      12.71      0.0      6.472      256.4      3.888      9.191      0.0 152
12.01      0.0      7.191      219.0      4.55      11.97      0.0
200      8.441      0.0      7.826      164.6      6.052      15.92      0.0 226
1.604      0.0      9.035      113.7      8.759      19.58      0.0

```


FSRU 001 case4

/ Windows UM3. 6/27/2012 2:19:59 PM

Case 4; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Far-spdx	Depth	Amb-cur	Amb-dir	Amb-sal	Amb-tem	Amb-pol	Decay
	Far-dir	Disprsn					
m/s	m	m/s	deg	psu	C	kg/kg	s-1
0.0	0.0	0.1	90.0	0.0	29.6	0.0	0.0
0.0	19.2	0.1	90.0	0.0	29.6	0.0	0.0
0.0	0.0	0.0					

P-dia	P-elev	V-angle	H-angle	Ports	AcuteMZ	ChrnCMZ	P-depth	Ttl-flo	Eff-sal
(m)	(m)	(deg)	(deg)	()	(m)	(m)	(m)	(m3/s)	
1.4	13.9	-45.0	0.0	1.0	62.0	62.0	5.3	2.06	
0.0	41.6	1000.0							

Froude number: 5.566

Step	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn
	(m)	(m/s)	(m)	(kg/kg)	()	(m)	(m)
0	5.3	0.1	1.4	1000.0	1.0	0.0	0.0;
Potential for more dilution							
84	9.535	0.1	6.831	228.0	4.371	5.678	0.976
100	9.788	0.1	7.781	202.8	4.913	6.565	1.321
120	9.881	0.1	8.574	184.2	5.411	7.573	1.769
190	8.07	0.1	10.5	125.4	7.944	11.34	3.946
200	7.256	0.1	11.16	110.8	8.989	12.06	4.519
222	4.036	0.1	13.52	75.29	13.23	14.0	6.572

FSRU 001 case 5

/ Windows UM3. 6/29/2012 10:57:13 AM

Case 5; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth  Amb-cur  Amb-dir  Amb-sal  Amb-tem  Amb-pol  Decay
Far-spd  Far-dir  Disprsn
      m      m/s      deg      psu      C      kg/kg      s-1
m/s      deg  m0.67/s2
0.0      0.0      0.1      90.0      0.0      29.6      0.0      0.0
0.0      19.2      0.1      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0
P-dia  P-elev V-angle H-angle  Ports AcuteMZ ChrnMZ P-depth Ttl-flo Eff-
sal  Temp Polutnt
      (m)      (m)      (deg)      (deg)      ( )      (m)      (m)      (m)      (m3/s)
(psu)      (C)      (kg/kg)
1.4      12.85      -45.0      0.0      1.0      62.0      62.0      6.35      2.06
0.0      41.6      1000.0
Froude number:      5.566
      Depth  Amb-cur  P-dia  Polutnt  Dilutn  x-posn  y-posn
Step      (m)      (m/s)      (m)      (kg/kg)      ( )      (m)      (m)
0      6.35      0.1      1.4      1000.0      1.0      0.0      0.0;
Potential for more dilution
84      10.59      0.1      6.831      228.0      4.371      5.678      0.976
100      10.84      0.1      7.781      202.8      4.913      6.565      1.321
120      10.93      0.1      8.574      184.2      5.411      7.573      1.769
190      9.12      0.1      10.5      125.4      7.944      11.34      3.946
200      8.306      0.1      11.16      110.8      8.989      12.06      4.519
227      4.106      0.1      14.23      68.2      14.61      14.43      7.176

```

FSRU 001 case 6

/ Windows UM3. 6/29/2012 11:03:22 AM

Case 6; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Far-spdx	Depth	Amb-cur	Amb-dir	Amb-sal	Amb-tem	Amb-pol	Decay
m/s	m	m/s	deg	psu	C	kg/kg	s-1
0.0	0.0	0.1	90.0	0.0	29.6	0.0	0.0
0.0	19.2	0.1	90.0	0.0	29.6	0.0	0.0
0.0	0.0	0.0					

P-dia	P-elev	V-angle	H-angle	Ports	AcuteMZ	ChrnMZ	P-depth	Ttl-flo	Eff-sal
(m)	(m)	(deg)	(deg)	()	(m)	(m)	(m)	(m3/s)	
1.4	11.8	-45.0	0.0	1.0	62.0	62.0	7.4	2.06	
0.0	41.6	1000.0							

Froude number: 5.566

Step	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn
	(m)	(m/s)	(m)	(kg/kg)	()	(m)	(m)
0	7.4	0.1	1.4	1000.0	1.0	0.0	0.0;
Potential for more dilution							
84	11.64	0.1	6.831	228.0	4.371	5.678	0.976
100	11.89	0.1	7.781	202.8	4.913	6.565	1.321
120	11.98	0.1	8.574	184.2	5.411	7.573	1.769
190	10.17	0.1	10.5	125.4	7.944	11.34	3.946
200	9.356	0.1	11.16	110.8	8.989	12.06	4.519
231	4.326	0.1	14.83	63.0	15.81	14.77	7.688

LNGC 001 case 1

/ Windows UM3. 6/29/2012 12:45:49 PM

Case 1; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Far-spd	Depth	Amb-cur	Amb-dir	Amb-sal	Amb-tem	Amb-pol	Decay
	Far-dir	Disprsn					
m/s	m	m/s	deg	psu	C	kg/kg	s-1
0.0	0.0	0.001	90.0	0.0	29.6	0.0	0.0
0.0	0.0	0.0					
0.0	19.2	0.001	90.0	0.0	29.6	0.0	0.0
0.0	0.0	0.0					

P-dia	P-elev	V-angle	H-angle	Ports	AcuteMZ	ChrcMZ	P-depth	Ttl-flo	Eff-sal
Temp	Polutnt								
(m)	(m)	(deg)	(deg)	()	(m)	(m)	(m)	(m3/s)	
(psu)	(C)	(kg/kg)							
1.4	13.9	-45.0	0.0	1.0	62.0	62.0	5.3	2.72	
0.0	32.6	1000.0							

Froude number: 15.56

Step	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn
	(m)	(m/s)	(m)	(kg/kg)	()	(m)	(m)
0	5.3	0.001	1.4	1000.0	1.0	0.0	0.0; max

dilution reached

Potential for more dilution

	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn	
87	16.15	0.001	8.199	178.6	5.596	11.95	0.0229	100
19.32	0.001	10.89	140.2	7.128	16.61	0.0432		
154	23.01	0.001	17.22	96.47	10.36	28.59	0.118	199
21.17	0.001	19.3	81.78	12.22	36.12	0.18		
200	21.08	0.001	19.34	81.43	12.27	36.3	0.182	
260	5.228	0.001	22.19	52.92	18.88	50.85	0.347	surface,

LNGC 001 case 2

/ Windows UM3. 6/29/2012 12:51:25 PM
Case 2; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Far-spdx	Depth m	Amb-cur m/s	Amb-dir deg	Amb-sal psu	Amb-tem C	Amb-pol kg/kg	Decay s-1
0.0	0.0	0.001	90.0	0.0	29.6	0.0	0.0
0.0	19.2	0.001	90.0	0.0	29.6	0.0	0.0
0.0	0.0	0.0					

P-dia sal	P-elev Temp	V-angle Polutnt	H-angle (deg)	Ports ()	AcuteMZ (m)	ChrnCMZ (m)	P-depth (m)	Ttl-flo (m3/s)	Eff-
1.4	12.85	-45.0	0.0	1.0	62.0	62.0	6.35	2.72	
0.0	32.6	1000.0							

Froude number: 15.56

Step	Depth (m)	Amb-cur (m/s)	P-dia (m)	Polutnt (kg/kg)	Dilutn ()	x-posn (m)	y-posn (m)
0	6.35	0.001	1.4	1000.0	1.0	0.0	0.0; max

dilution reached

Potential for more dilution

84	16.49	0.001	7.675	189.5	5.273	11.03	0.0196	100
20.37	0.001	10.89	140.2	7.128	16.61	0.0432		
154	24.06	0.001	17.22	96.47	10.36	28.59	0.118	199
22.22	0.001	19.3	81.78	12.22	36.12	0.18		
200	22.13	0.001	19.34	81.43	12.27	36.3	0.182	
262	4.935	0.001	22.43	51.46	19.42	51.59	0.358	

LNGC 001 case 3

/ Windows UM3. 6/29/2012 12:54:42 PM

Case 3; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth    Amb-cur    Amb-dir    Amb-sal    Amb-tem    Amb-pol    Decay
Far-spd  Far-dir  Disprsn
      m          m/s          deg          psu          C          kg/kg          s-1
m/s      deg    m0.67/s2
0.0      0.0      0.001      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0      0.0
0.0      19.2      0.001      90.0      0.0      29.6      0.0      0.0
0.0      0.0      0.0
P-dia  P-elev V-angle H-angle  Ports AcuteMZ ChrcMZ P-depth Ttl-flo Eff-
sal    Temp Polutnt
      (m)      (m)      (deg)      (deg)      ( )      (m)      (m)      (m)      (m3/s)
(psu)      (C)      (kg/kg)
0.0      1.4      11.8      -45.0      0.0      1.0      62.0      62.0      7.4      2.72
0.0      32.6      1000.0
Froude number:      15.56
      Depth    Amb-cur    P-dia    Polutnt    Dilutn    x-posn    y-posn
Step    (m)      (m/s)      (m)      (kg/kg)      ( )      (m)      (m)
0      7.4      0.001      1.4      1000.0      1.0      0.0      0.0 Potential
for more dilution
80      16.63      0.001      7.036      205.1      4.872      9.914      0.0159 100
21.42      0.001      10.89      140.2      7.128      16.61      0.0432
154      25.11      0.001      17.22      96.47      10.36      28.59      0.118 199
23.27      0.001      19.3      81.78      12.22      36.12      0.18
200      23.18      0.001      19.34      81.43      12.27      36.3      0.182
263      5.268      0.001      22.56      50.7      19.7      51.97      0.363

```

LNGC 001 case 4

/ Windows UM3. 6/29/2012 12:40:26 PM
Case 4; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Depth	Amb-cur	Amb-dir	Amb-sal	Amb-tem	Amb-pol	Decay			
Far-spd	Far-dir	Disprsn							
m	m/s	deg	psu	C	kg/kg	s-1			
0.0	0.0	0.1	90.0	0.0	29.6	0.0			
0.0	0.0	0.0	90.0	0.0	29.6	0.0			
0.0	0.0	0.0	90.0	0.0	29.6	0.0			
P-dia	P-elev	V-angle	H-angle	Ports	AcuteMZ	ChrnMZ	P-depth	Ttl-flo	Eff-
sal	Temp	Polutnt							
(m)	(m)	(deg)	(deg)	()	(m)	(m)	(m)	(m3/s)	
(psu)	(C)	(kg/kg)							
1.4	13.9	-45.0	0.0	1.0	62.0	62.0	5.3	2.72	
0.0	32.6	1000.0							
Froude number:		15.56							
Step	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn		
	(m)	(m/s)	(m)	(kg/kg)	()	(m)	(m)		
0	5.3	0.1	1.4	1000.0	1.0	0.0	0.0;		
Potential for more dilution									
100	13.84	0.1	10.19	138.0	7.239	9.232	2.082 106		
14.54	0.1	11.43	122.8	8.133	10.13	2.566			
129	16.46	0.1	16.17	84.99	11.76	12.96	4.584 184		
18.49	0.1	26.64	44.09	22.66	19.27	12.71			
189	18.45	0.1	27.62	41.49	24.08	19.92	13.88 200		
18.12	0.1	29.98	35.85	27.87	21.45	16.95			
217	16.52	0.1	34.8	26.81	37.27	24.21	23.92		

LNGC 001 case 5

/ Windows UM3. 6/29/2012 12:36:49 PM

Case 5; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

```

-----
      Depth    Amb-cur    Amb-dir    Amb-sal    Amb-tem    Amb-pol    Decay
Far-spd    Far-dir    Disprsn
      m        m/s        deg        psu        C        kg/kg        s-1
m/s        deg    m0.67/s2
      0.0        0.1        90.0        0.0        29.6        0.0        0.0
0.0        0.0        0.0
      19.2        0.1        90.0        0.0        29.6        0.0        0.0
0.0        0.0        0.0
      P-dia    P-elev    V-angle    H-angle    Ports    AcuteMZ    ChrnMZ    P-depth    Ttl-flo    Eff-
sal    Temp    Polutnt
      (m)    (m)    (deg)    (deg)    ( )    (m)    (m)    (m)    (m3/s)
      (psu)    (C)    (kg/kg)
      1.4    12.85    -45.0    0.0    1.0    62.0    62.0    6.35    2.72
0.0    32.6    1000.0
Froude number:    15.56
      Depth    Amb-cur    P-dia    Polutnt    Dilutn    x-posn    y-posn
Step    (m)    (m/s)    (m)    (kg/kg)    ( )    (m)    (m)
      0        6.35    0.1    1.4    1000.0    1.0    0.0    0.0
      100    14.89    0.1    10.19    138.0    7.239    9.232    2.082
      101    15.01    0.1    10.39    135.3    7.384    9.383    2.159 129
      17.51    0.1    16.17    84.99    11.76    12.96    4.584
      184    19.54    0.1    26.64    44.09    22.66    19.27    12.71 189
      19.5    0.1    27.62    41.49    24.08    19.92    13.88
      200    19.17    0.1    29.98    35.85    27.87    21.45    16.95
      220    17.1    0.1    35.83    25.26    39.55    24.73    25.49

```

LNGC 001 case 6

/ Windows UM3. 6/29/2012 12:33:20 PM

Case 6; ambient file c:\plumes\VP plume 0.001.db; Diffuser table record 1: --

Depth	Amb-cur	Amb-dir	Amb-sal	Amb-tem	Amb-pol	Decay
Far-spdx	Far-dir	Disprsn				
m	m/s	deg	psu	C	kg/kg	s-1
0.0	0.1	90.0	0.0	29.6	0.0	0.0
19.2	0.1	90.0	0.0	29.6	0.0	0.0

P-dia	P-elev	V-angle	H-angle	Ports	AcuteMZ	ChrnMZ	P-depth	Ttl-flo	Eff-
sal	Temp	Polutnt							
(m)	(m)	(deg)	(deg)	()	(m)	(m)	(m)	(m3/s)	
1.4	11.8	-45.0	0.0	1.0	62.0	62.0	7.4	2.72	
0.0	32.6	1000.0							

Froude number: 15.56

Step	Depth	Amb-cur	P-dia	Polutnt	Dilutn	x-posn	y-posn
	(m)	(m/s)	(m)	(kg/kg)	()	(m)	(m)
0	7.4	0.1	1.4	1000.0	1.0	0.0	0.0
96	15.46	0.1	9.414	149.4	6.688	8.632	1.792 100
15.94	0.1	10.19	138.0	7.239	9.232	2.082	
129	18.56	0.1	16.17	84.99	11.76	12.96	4.584 184
20.59	0.1	26.64	44.09	22.66	19.27	12.71	
189	20.55	0.1	27.62	41.49	24.08	19.92	13.88 200
20.22	0.1	29.98	35.85	27.87	21.45	16.95	
224	17.45	0.1	37.25	23.34	42.81	25.4	27.67

Appendix 2 JETLAG Output Files

Appendix 2 JETLAG Output Files

NE = Plume Element
XJ = X Coordinate, meters
YJ = Y Coordinate, meters
ZJ = Z Coordinate, meters
RJ = Plume Radius, meters
QJ = Plume Velocity, meters/second
DIL = Dilution, dimensionless
TEMP = Temperature °C

FSRU Outfall 001 – Case 1 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.5300E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4872E-01	0.0000E+00	-0.5349E+01	0.7112E+00	0.2027E+01	0.1016E+01	0.4141E+02
10	0.4145E+00	0.0000E+00	-0.5713E+01	0.7955E+00	0.1808E+01	0.1134E+01	0.4018E+02
20	0.8247E+00	0.0000E+00	-0.6117E+01	0.8894E+00	0.1613E+01	0.1266E+01	0.3908E+02
30	0.1197E+01	0.0000E+00	-0.6481E+01	0.9742E+00	0.1469E+01	0.1383E+01	0.3828E+02
40	0.1540E+01	0.0000E+00	-0.6813E+01	0.1052E+01	0.1357E+01	0.1491E+01	0.3765E+02
50	0.1860E+01	0.0000E+00	-0.7120E+01	0.1125E+01	0.1267E+01	0.1590E+01	0.3715E+02
60	0.2162E+01	0.0000E+00	-0.7406E+01	0.1192E+01	0.1192E+01	0.1682E+01	0.3673E+02
70	0.2448E+01	0.0000E+00	-0.7676E+01	0.1257E+01	0.1128E+01	0.1769E+01	0.3639E+02
80	0.2721E+01	0.0000E+00	-0.7930E+01	0.1318E+01	0.1074E+01	0.1850E+01	0.3609E+02
90	0.2983E+01	0.0000E+00	-0.8171E+01	0.1376E+01	0.1026E+01	0.1928E+01	0.3582E+02
100	0.3234E+01	0.0000E+00	-0.8401E+01	0.1431E+01	0.9837E+00	0.2002E+01	0.3560E+02
110	0.3477E+01	0.0000E+00	-0.8620E+01	0.1485E+01	0.9461E+00	0.2072E+01	0.3539E+02
120	0.3711E+01	0.0000E+00	-0.8830E+01	0.1537E+01	0.9123E+00	0.2139E+01	0.3521E+02
130	0.3939E+01	0.0000E+00	-0.9032E+01	0.1587E+01	0.8816E+00	0.2204E+01	0.3504E+02
140	0.4160E+01	0.0000E+00	-0.9226E+01	0.1635E+01	0.8537E+00	0.2266E+01	0.3490E+02
150	0.4375E+01	0.0000E+00	-0.9413E+01	0.1682E+01	0.8280E+00	0.2326E+01	0.3476E+02
160	0.4585E+01	0.0000E+00	-0.9594E+01	0.1727E+01	0.8044E+00	0.2384E+01	0.3463E+02
170	0.4790E+01	0.0000E+00	-0.9769E+01	0.1772E+01	0.7826E+00	0.2440E+01	0.3452E+02
180	0.4991E+01	0.0000E+00	-0.9938E+01	0.1815E+01	0.7623E+00	0.2494E+01	0.3441E+02
190	0.5187E+01	0.0000E+00	-0.1010E+02	0.1857E+01	0.7434E+00	0.2546E+01	0.3431E+02
200	0.5379E+01	0.0000E+00	-0.1026E+02	0.1898E+01	0.7257E+00	0.2597E+01	0.3422E+02
210	0.5568E+01	0.0000E+00	-0.1041E+02	0.1938E+01	0.7091E+00	0.2647E+01	0.3413E+02
220	0.5753E+01	0.0000E+00	-0.1056E+02	0.1978E+01	0.6935E+00	0.2695E+01	0.3405E+02
230	0.5935E+01	0.0000E+00	-0.1071E+02	0.2016E+01	0.6788E+00	0.2741E+01	0.3398E+02
240	0.6114E+01	0.0000E+00	-0.1085E+02	0.2054E+01	0.6649E+00	0.2787E+01	0.3391E+02
250	0.6290E+01	0.0000E+00	-0.1099E+02	0.2091E+01	0.6517E+00	0.2831E+01	0.3384E+02
260	0.6463E+01	0.0000E+00	-0.1112E+02	0.2127E+01	0.6393E+00	0.2874E+01	0.3378E+02
270	0.6634E+01	0.0000E+00	-0.1125E+02	0.2163E+01	0.6274E+00	0.2916E+01	0.3372E+02
280	0.6803E+01	0.0000E+00	-0.1138E+02	0.2198E+01	0.6161E+00	0.2957E+01	0.3366E+02
290	0.6969E+01	0.0000E+00	-0.1150E+02	0.2232E+01	0.6053E+00	0.2997E+01	0.3360E+02
300	0.7133E+01	0.0000E+00	-0.1162E+02	0.2266E+01	0.5950E+00	0.3037E+01	0.3355E+02
310	0.7294E+01	0.0000E+00	-0.1174E+02	0.2300E+01	0.5852E+00	0.3075E+01	0.3350E+02
320	0.7454E+01	0.0000E+00	-0.1186E+02	0.2333E+01	0.5757E+00	0.3113E+01	0.3346E+02
330	0.7612E+01	0.0000E+00	-0.1197E+02	0.2365E+01	0.5667E+00	0.3149E+01	0.3341E+02
340	0.7769E+01	0.0000E+00	-0.1208E+02	0.2397E+01	0.5580E+00	0.3185E+01	0.3337E+02
350	0.7923E+01	0.0000E+00	-0.1219E+02	0.2428E+01	0.5497E+00	0.3220E+01	0.3333E+02
360	0.8076E+01	0.0000E+00	-0.1229E+02	0.2459E+01	0.5416E+00	0.3255E+01	0.3329E+02

370	0.8227E+01	0.0000E+00	-0.1239E+02	0.2490E+01	0.5339E+00	0.3289E+01	0.3325E+02
380	0.8377E+01	0.0000E+00	-0.1249E+02	0.2520E+01	0.5265E+00	0.3322E+01	0.3321E+02
390	0.8525E+01	0.0000E+00	-0.1259E+02	0.2550E+01	0.5193E+00	0.3354E+01	0.3318E+02
400	0.8672E+01	0.0000E+00	-0.1269E+02	0.2579E+01	0.5124E+00	0.3386E+01	0.3314E+02
410	0.8817E+01	0.0000E+00	-0.1278E+02	0.2608E+01	0.5057E+00	0.3418E+01	0.3311E+02
420	0.8961E+01	0.0000E+00	-0.1287E+02	0.2637E+01	0.4992E+00	0.3449E+01	0.3308E+02
430	0.9104E+01	0.0000E+00	-0.1296E+02	0.2665E+01	0.4929E+00	0.3479E+01	0.3305E+02
440	0.9246E+01	0.0000E+00	-0.1305E+02	0.2693E+01	0.4869E+00	0.3509E+01	0.3302E+02
450	0.9386E+01	0.0000E+00	-0.1313E+02	0.2721E+01	0.4810E+00	0.3538E+01	0.3299E+02
460	0.9525E+01	0.0000E+00	-0.1322E+02	0.2748E+01	0.4753E+00	0.3567E+01	0.3296E+02
470	0.9664E+01	0.0000E+00	-0.1330E+02	0.2775E+01	0.4698E+00	0.3595E+01	0.3294E+02
480	0.9801E+01	0.0000E+00	-0.1338E+02	0.2802E+01	0.4644E+00	0.3623E+01	0.3291E+02
490	0.9937E+01	0.0000E+00	-0.1346E+02	0.2828E+01	0.4592E+00	0.3650E+01	0.3289E+02
500	0.1007E+02	0.0000E+00	-0.1353E+02	0.2854E+01	0.4542E+00	0.3677E+01	0.3286E+02
510	0.1021E+02	0.0000E+00	-0.1361E+02	0.2880E+01	0.4493E+00	0.3704E+01	0.3284E+02
520	0.1034E+02	0.0000E+00	-0.1368E+02	0.2906E+01	0.4445E+00	0.3730E+01	0.3282E+02
530	0.1047E+02	0.0000E+00	-0.1375E+02	0.2931E+01	0.4399E+00	0.3756E+01	0.3280E+02
540	0.1060E+02	0.0000E+00	-0.1382E+02	0.2956E+01	0.4354E+00	0.3781E+01	0.3277E+02
550	0.1073E+02	0.0000E+00	-0.1389E+02	0.2981E+01	0.4310E+00	0.3806E+01	0.3275E+02
560	0.1086E+02	0.0000E+00	-0.1396E+02	0.3006E+01	0.4267E+00	0.3831E+01	0.3273E+02
570	0.1099E+02	0.0000E+00	-0.1402E+02	0.3030E+01	0.4225E+00	0.3856E+01	0.3271E+02
580	0.1112E+02	0.0000E+00	-0.1408E+02	0.3054E+01	0.4185E+00	0.3880E+01	0.3269E+02
590	0.1125E+02	0.0000E+00	-0.1415E+02	0.3078E+01	0.4145E+00	0.3903E+01	0.3267E+02
600	0.1137E+02	0.0000E+00	-0.1421E+02	0.3102E+01	0.4106E+00	0.3927E+01	0.3266E+02
610	0.1150E+02	0.0000E+00	-0.1427E+02	0.3125E+01	0.4069E+00	0.3950E+01	0.3264E+02
620	0.1162E+02	0.0000E+00	-0.1432E+02	0.3149E+01	0.4032E+00	0.3973E+01	0.3262E+02
630	0.1175E+02	0.0000E+00	-0.1438E+02	0.3172E+01	0.3996E+00	0.3996E+01	0.3260E+02
640	0.1187E+02	0.0000E+00	-0.1444E+02	0.3195E+01	0.3961E+00	0.4018E+01	0.3259E+02
650	0.1199E+02	0.0000E+00	-0.1449E+02	0.3217E+01	0.3927E+00	0.4041E+01	0.3257E+02
660	0.1212E+02	0.0000E+00	-0.1454E+02	0.3240E+01	0.3894E+00	0.4063E+01	0.3255E+02
670	0.1224E+02	0.0000E+00	-0.1459E+02	0.3262E+01	0.3861E+00	0.4084E+01	0.3254E+02
680	0.1236E+02	0.0000E+00	-0.1464E+02	0.3284E+01	0.3829E+00	0.4106E+01	0.3252E+02
690	0.1248E+02	0.0000E+00	-0.1469E+02	0.3306E+01	0.3798E+00	0.4127E+01	0.3251E+02
700	0.1260E+02	0.0000E+00	-0.1474E+02	0.3328E+01	0.3768E+00	0.4148E+01	0.3249E+02
710	0.1272E+02	0.0000E+00	-0.1478E+02	0.3350E+01	0.3738E+00	0.4169E+01	0.3248E+02
720	0.1284E+02	0.0000E+00	-0.1483E+02	0.3371E+01	0.3709E+00	0.4190E+01	0.3246E+02
730	0.1295E+02	0.0000E+00	-0.1487E+02	0.3392E+01	0.3681E+00	0.4211E+01	0.3245E+02
740	0.1307E+02	0.0000E+00	-0.1491E+02	0.3414E+01	0.3653E+00	0.4231E+01	0.3244E+02
750	0.1319E+02	0.0000E+00	-0.1495E+02	0.3434E+01	0.3626E+00	0.4251E+01	0.3242E+02
760	0.1330E+02	0.0000E+00	-0.1499E+02	0.3455E+01	0.3599E+00	0.4271E+01	0.3241E+02
770	0.1342E+02	0.0000E+00	-0.1503E+02	0.3476E+01	0.3573E+00	0.4291E+01	0.3240E+02
780	0.1353E+02	0.0000E+00	-0.1507E+02	0.3496E+01	0.3548E+00	0.4311E+01	0.3238E+02
790	0.1365E+02	0.0000E+00	-0.1510E+02	0.3517E+01	0.3523E+00	0.4331E+01	0.3237E+02
800	0.1376E+02	0.0000E+00	-0.1514E+02	0.3537E+01	0.3499E+00	0.4351E+01	0.3236E+02
810	0.1388E+02	0.0000E+00	-0.1517E+02	0.3557E+01	0.3475E+00	0.4370E+01	0.3235E+02
820	0.1399E+02	0.0000E+00	-0.1521E+02	0.3577E+01	0.3452E+00	0.4389E+01	0.3233E+02
830	0.1410E+02	0.0000E+00	-0.1524E+02	0.3596E+01	0.3429E+00	0.4409E+01	0.3232E+02
840	0.1421E+02	0.0000E+00	-0.1527E+02	0.3616E+01	0.3407E+00	0.4428E+01	0.3231E+02
850	0.1432E+02	0.0000E+00	-0.1530E+02	0.3635E+01	0.3385E+00	0.4447E+01	0.3230E+02
860	0.1444E+02	0.0000E+00	-0.1533E+02	0.3655E+01	0.3364E+00	0.4466E+01	0.3229E+02
870	0.1455E+02	0.0000E+00	-0.1535E+02	0.3674E+01	0.3343E+00	0.4485E+01	0.3228E+02
880	0.1466E+02	0.0000E+00	-0.1538E+02	0.3693E+01	0.3322E+00	0.4504E+01	0.3226E+02
890	0.1477E+02	0.0000E+00	-0.1541E+02	0.3712E+01	0.3302E+00	0.4523E+01	0.3225E+02

900 0.1488E+02 0.0000E+00 -0.1543E+02 0.3731E+01 0.3283E+00 0.4541E+01 0.3224E+02
910 0.1498E+02 0.0000E+00 -0.1545E+02 0.3749E+01 0.3264E+00 0.4560E+01 0.3223E+02
920 0.1509E+02 0.0000E+00 -0.1548E+02 0.3768E+01 0.3245E+00 0.4579E+01 0.3222E+02
927 0.1517E+02 0.0000E+00 -0.1549E+02 0.3781E+01 0.3232E+00 0.4592E+01 0.3221E+02

FSRU Outfall 001 – Case 2 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6350E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4872E-01	0.0000E+00	-0.6399E+01	0.7112E+00	0.2027E+01	0.1016E+01	0.4141E+02
10	0.4145E+00	0.0000E+00	-0.6763E+01	0.7955E+00	0.1808E+01	0.1134E+01	0.4018E+02
20	0.8247E+00	0.0000E+00	-0.7167E+01	0.8894E+00	0.1613E+01	0.1266E+01	0.3908E+02
30	0.1197E+01	0.0000E+00	-0.7531E+01	0.9742E+00	0.1469E+01	0.1383E+01	0.3828E+02
40	0.1540E+01	0.0000E+00	-0.7863E+01	0.1052E+01	0.1357E+01	0.1491E+01	0.3765E+02
50	0.1860E+01	0.0000E+00	-0.8170E+01	0.1125E+01	0.1267E+01	0.1590E+01	0.3715E+02
60	0.2162E+01	0.0000E+00	-0.8456E+01	0.1192E+01	0.1192E+01	0.1682E+01	0.3673E+02
70	0.2448E+01	0.0000E+00	-0.8726E+01	0.1257E+01	0.1128E+01	0.1769E+01	0.3639E+02
80	0.2721E+01	0.0000E+00	-0.8980E+01	0.1318E+01	0.1074E+01	0.1850E+01	0.3609E+02
90	0.2983E+01	0.0000E+00	-0.9221E+01	0.1376E+01	0.1026E+01	0.1928E+01	0.3582E+02
100	0.3234E+01	0.0000E+00	-0.9451E+01	0.1431E+01	0.9837E+00	0.2002E+01	0.3560E+02
110	0.3477E+01	0.0000E+00	-0.9670E+01	0.1485E+01	0.9461E+00	0.2072E+01	0.3539E+02
120	0.3711E+01	0.0000E+00	-0.9880E+01	0.1537E+01	0.9123E+00	0.2139E+01	0.3521E+02
130	0.3939E+01	0.0000E+00	-0.1008E+02	0.1587E+01	0.8816E+00	0.2204E+01	0.3504E+02
140	0.4160E+01	0.0000E+00	-0.1028E+02	0.1635E+01	0.8537E+00	0.2266E+01	0.3490E+02
150	0.4375E+01	0.0000E+00	-0.1046E+02	0.1682E+01	0.8280E+00	0.2326E+01	0.3476E+02
160	0.4585E+01	0.0000E+00	-0.1064E+02	0.1727E+01	0.8044E+00	0.2384E+01	0.3463E+02
170	0.4790E+01	0.0000E+00	-0.1082E+02	0.1772E+01	0.7826E+00	0.2440E+01	0.3452E+02
180	0.4991E+01	0.0000E+00	-0.1099E+02	0.1815E+01	0.7623E+00	0.2494E+01	0.3441E+02
190	0.5187E+01	0.0000E+00	-0.1115E+02	0.1857E+01	0.7434E+00	0.2546E+01	0.3431E+02
200	0.5379E+01	0.0000E+00	-0.1131E+02	0.1898E+01	0.7257E+00	0.2597E+01	0.3422E+02
210	0.5568E+01	0.0000E+00	-0.1146E+02	0.1938E+01	0.7091E+00	0.2647E+01	0.3413E+02
220	0.5753E+01	0.0000E+00	-0.1161E+02	0.1978E+01	0.6935E+00	0.2695E+01	0.3405E+02
230	0.5935E+01	0.0000E+00	-0.1176E+02	0.2016E+01	0.6788E+00	0.2741E+01	0.3398E+02
240	0.6114E+01	0.0000E+00	-0.1190E+02	0.2054E+01	0.6649E+00	0.2787E+01	0.3391E+02
250	0.6290E+01	0.0000E+00	-0.1204E+02	0.2091E+01	0.6517E+00	0.2831E+01	0.3384E+02
260	0.6463E+01	0.0000E+00	-0.1217E+02	0.2127E+01	0.6393E+00	0.2874E+01	0.3378E+02
270	0.6634E+01	0.0000E+00	-0.1230E+02	0.2163E+01	0.6274E+00	0.2916E+01	0.3372E+02
280	0.6803E+01	0.0000E+00	-0.1243E+02	0.2198E+01	0.6161E+00	0.2957E+01	0.3366E+02
290	0.6969E+01	0.0000E+00	-0.1255E+02	0.2232E+01	0.6053E+00	0.2997E+01	0.3360E+02
300	0.7133E+01	0.0000E+00	-0.1267E+02	0.2266E+01	0.5950E+00	0.3037E+01	0.3355E+02
310	0.7294E+01	0.0000E+00	-0.1279E+02	0.2300E+01	0.5852E+00	0.3075E+01	0.3350E+02
320	0.7454E+01	0.0000E+00	-0.1291E+02	0.2333E+01	0.5757E+00	0.3113E+01	0.3346E+02
330	0.7612E+01	0.0000E+00	-0.1302E+02	0.2365E+01	0.5667E+00	0.3149E+01	0.3341E+02
340	0.7769E+01	0.0000E+00	-0.1313E+02	0.2397E+01	0.5580E+00	0.3185E+01	0.3337E+02
350	0.7923E+01	0.0000E+00	-0.1324E+02	0.2428E+01	0.5497E+00	0.3220E+01	0.3333E+02
360	0.8076E+01	0.0000E+00	-0.1334E+02	0.2459E+01	0.5416E+00	0.3255E+01	0.3329E+02
370	0.8227E+01	0.0000E+00	-0.1344E+02	0.2490E+01	0.5339E+00	0.3289E+01	0.3325E+02
380	0.8377E+01	0.0000E+00	-0.1354E+02	0.2520E+01	0.5265E+00	0.3322E+01	0.3321E+02
390	0.8525E+01	0.0000E+00	-0.1364E+02	0.2550E+01	0.5193E+00	0.3354E+01	0.3318E+02
400	0.8672E+01	0.0000E+00	-0.1374E+02	0.2579E+01	0.5124E+00	0.3386E+01	0.3314E+02
410	0.8817E+01	0.0000E+00	-0.1383E+02	0.2608E+01	0.5057E+00	0.3418E+01	0.3311E+02
420	0.8961E+01	0.0000E+00	-0.1392E+02	0.2637E+01	0.4992E+00	0.3449E+01	0.3308E+02
430	0.9104E+01	0.0000E+00	-0.1401E+02	0.2665E+01	0.4929E+00	0.3479E+01	0.3305E+02
440	0.9246E+01	0.0000E+00	-0.1410E+02	0.2693E+01	0.4869E+00	0.3509E+01	0.3302E+02
450	0.9386E+01	0.0000E+00	-0.1418E+02	0.2721E+01	0.4810E+00	0.3538E+01	0.3299E+02
460	0.9525E+01	0.0000E+00	-0.1427E+02	0.2748E+01	0.4753E+00	0.3567E+01	0.3296E+02
470	0.9664E+01	0.0000E+00	-0.1435E+02	0.2775E+01	0.4698E+00	0.3595E+01	0.3294E+02

480	0.9801E+01	0.0000E+00	-0.1443E+02	0.2802E+01	0.4644E+00	0.3623E+01	0.3291E+02
490	0.9937E+01	0.0000E+00	-0.1451E+02	0.2828E+01	0.4592E+00	0.3650E+01	0.3289E+02
500	0.1007E+02	0.0000E+00	-0.1458E+02	0.2854E+01	0.4542E+00	0.3677E+01	0.3286E+02
510	0.1021E+02	0.0000E+00	-0.1466E+02	0.2880E+01	0.4493E+00	0.3704E+01	0.3284E+02
520	0.1034E+02	0.0000E+00	-0.1473E+02	0.2906E+01	0.4445E+00	0.3730E+01	0.3282E+02
530	0.1047E+02	0.0000E+00	-0.1480E+02	0.2931E+01	0.4399E+00	0.3756E+01	0.3280E+02
540	0.1060E+02	0.0000E+00	-0.1487E+02	0.2956E+01	0.4354E+00	0.3781E+01	0.3277E+02
550	0.1073E+02	0.0000E+00	-0.1494E+02	0.2981E+01	0.4310E+00	0.3806E+01	0.3275E+02
560	0.1086E+02	0.0000E+00	-0.1501E+02	0.3006E+01	0.4267E+00	0.3831E+01	0.3273E+02
570	0.1099E+02	0.0000E+00	-0.1507E+02	0.3030E+01	0.4225E+00	0.3856E+01	0.3271E+02
580	0.1112E+02	0.0000E+00	-0.1513E+02	0.3054E+01	0.4185E+00	0.3880E+01	0.3269E+02
590	0.1125E+02	0.0000E+00	-0.1520E+02	0.3078E+01	0.4145E+00	0.3903E+01	0.3267E+02
600	0.1137E+02	0.0000E+00	-0.1526E+02	0.3102E+01	0.4106E+00	0.3927E+01	0.3266E+02
610	0.1150E+02	0.0000E+00	-0.1532E+02	0.3125E+01	0.4069E+00	0.3950E+01	0.3264E+02
620	0.1162E+02	0.0000E+00	-0.1537E+02	0.3149E+01	0.4032E+00	0.3973E+01	0.3262E+02
630	0.1175E+02	0.0000E+00	-0.1543E+02	0.3172E+01	0.3996E+00	0.3996E+01	0.3260E+02
640	0.1187E+02	0.0000E+00	-0.1549E+02	0.3195E+01	0.3961E+00	0.4018E+01	0.3259E+02
650	0.1199E+02	0.0000E+00	-0.1554E+02	0.3217E+01	0.3927E+00	0.4041E+01	0.3257E+02
660	0.1212E+02	0.0000E+00	-0.1559E+02	0.3240E+01	0.3894E+00	0.4063E+01	0.3255E+02
670	0.1224E+02	0.0000E+00	-0.1564E+02	0.3262E+01	0.3861E+00	0.4084E+01	0.3254E+02
680	0.1236E+02	0.0000E+00	-0.1569E+02	0.3284E+01	0.3829E+00	0.4106E+01	0.3252E+02
690	0.1248E+02	0.0000E+00	-0.1574E+02	0.3306E+01	0.3798E+00	0.4127E+01	0.3251E+02
700	0.1260E+02	0.0000E+00	-0.1579E+02	0.3328E+01	0.3768E+00	0.4148E+01	0.3249E+02
710	0.1272E+02	0.0000E+00	-0.1583E+02	0.3350E+01	0.3738E+00	0.4169E+01	0.3248E+02
720	0.1284E+02	0.0000E+00	-0.1588E+02	0.3371E+01	0.3709E+00	0.4190E+01	0.3246E+02
730	0.1295E+02	0.0000E+00	-0.1592E+02	0.3392E+01	0.3681E+00	0.4211E+01	0.3245E+02
740	0.1307E+02	0.0000E+00	-0.1596E+02	0.3414E+01	0.3653E+00	0.4231E+01	0.3244E+02
744	0.1312E+02	0.0000E+00	-0.1598E+02	0.3422E+01	0.3642E+00	0.4239E+01	0.3243E+02

FSRU Outfall 001 – Case 3 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7400E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4872E-01	0.0000E+00	-0.7449E+01	0.7112E+00	0.2027E+01	0.1016E+01	0.4141E+02
10	0.4145E+00	0.0000E+00	-0.7813E+01	0.7955E+00	0.1808E+01	0.1134E+01	0.4018E+02
20	0.8247E+00	0.0000E+00	-0.8217E+01	0.8894E+00	0.1613E+01	0.1266E+01	0.3908E+02
30	0.1197E+01	0.0000E+00	-0.8581E+01	0.9742E+00	0.1469E+01	0.1383E+01	0.3828E+02
40	0.1540E+01	0.0000E+00	-0.8913E+01	0.1052E+01	0.1357E+01	0.1491E+01	0.3765E+02
50	0.1860E+01	0.0000E+00	-0.9220E+01	0.1125E+01	0.1267E+01	0.1590E+01	0.3715E+02
60	0.2162E+01	0.0000E+00	-0.9506E+01	0.1192E+01	0.1192E+01	0.1682E+01	0.3673E+02
70	0.2448E+01	0.0000E+00	-0.9776E+01	0.1257E+01	0.1128E+01	0.1769E+01	0.3639E+02
80	0.2721E+01	0.0000E+00	-0.1003E+02	0.1318E+01	0.1074E+01	0.1850E+01	0.3609E+02
90	0.2983E+01	0.0000E+00	-0.1027E+02	0.1376E+01	0.1026E+01	0.1928E+01	0.3582E+02
100	0.3234E+01	0.0000E+00	-0.1050E+02	0.1431E+01	0.9837E+00	0.2002E+01	0.3560E+02
110	0.3477E+01	0.0000E+00	-0.1072E+02	0.1485E+01	0.9461E+00	0.2072E+01	0.3539E+02
120	0.3711E+01	0.0000E+00	-0.1093E+02	0.1537E+01	0.9123E+00	0.2139E+01	0.3521E+02
130	0.3939E+01	0.0000E+00	-0.1113E+02	0.1587E+01	0.8816E+00	0.2204E+01	0.3504E+02
140	0.4160E+01	0.0000E+00	-0.1133E+02	0.1635E+01	0.8537E+00	0.2266E+01	0.3490E+02
150	0.4375E+01	0.0000E+00	-0.1151E+02	0.1682E+01	0.8280E+00	0.2326E+01	0.3476E+02
160	0.4585E+01	0.0000E+00	-0.1169E+02	0.1727E+01	0.8044E+00	0.2384E+01	0.3463E+02
170	0.4790E+01	0.0000E+00	-0.1187E+02	0.1772E+01	0.7826E+00	0.2440E+01	0.3452E+02
180	0.4991E+01	0.0000E+00	-0.1204E+02	0.1815E+01	0.7623E+00	0.2494E+01	0.3441E+02
190	0.5187E+01	0.0000E+00	-0.1220E+02	0.1857E+01	0.7434E+00	0.2546E+01	0.3431E+02
200	0.5379E+01	0.0000E+00	-0.1236E+02	0.1898E+01	0.7257E+00	0.2597E+01	0.3422E+02
210	0.5568E+01	0.0000E+00	-0.1251E+02	0.1938E+01	0.7091E+00	0.2647E+01	0.3413E+02
220	0.5753E+01	0.0000E+00	-0.1266E+02	0.1978E+01	0.6935E+00	0.2695E+01	0.3405E+02
230	0.5935E+01	0.0000E+00	-0.1281E+02	0.2016E+01	0.6788E+00	0.2741E+01	0.3398E+02
240	0.6114E+01	0.0000E+00	-0.1295E+02	0.2054E+01	0.6649E+00	0.2787E+01	0.3391E+02
250	0.6290E+01	0.0000E+00	-0.1309E+02	0.2091E+01	0.6517E+00	0.2831E+01	0.3384E+02
260	0.6463E+01	0.0000E+00	-0.1322E+02	0.2127E+01	0.6393E+00	0.2874E+01	0.3378E+02
270	0.6634E+01	0.0000E+00	-0.1335E+02	0.2163E+01	0.6274E+00	0.2916E+01	0.3372E+02
280	0.6803E+01	0.0000E+00	-0.1348E+02	0.2198E+01	0.6161E+00	0.2957E+01	0.3366E+02
290	0.6969E+01	0.0000E+00	-0.1360E+02	0.2232E+01	0.6053E+00	0.2997E+01	0.3360E+02
300	0.7133E+01	0.0000E+00	-0.1372E+02	0.2266E+01	0.5950E+00	0.3037E+01	0.3355E+02
310	0.7294E+01	0.0000E+00	-0.1384E+02	0.2300E+01	0.5852E+00	0.3075E+01	0.3350E+02
320	0.7454E+01	0.0000E+00	-0.1396E+02	0.2333E+01	0.5757E+00	0.3113E+01	0.3346E+02
330	0.7612E+01	0.0000E+00	-0.1407E+02	0.2365E+01	0.5667E+00	0.3149E+01	0.3341E+02
340	0.7769E+01	0.0000E+00	-0.1418E+02	0.2397E+01	0.5580E+00	0.3185E+01	0.3337E+02
350	0.7923E+01	0.0000E+00	-0.1429E+02	0.2428E+01	0.5497E+00	0.3220E+01	0.3333E+02
360	0.8076E+01	0.0000E+00	-0.1439E+02	0.2459E+01	0.5416E+00	0.3255E+01	0.3329E+02
370	0.8227E+01	0.0000E+00	-0.1449E+02	0.2490E+01	0.5339E+00	0.3289E+01	0.3325E+02
380	0.8377E+01	0.0000E+00	-0.1459E+02	0.2520E+01	0.5265E+00	0.3322E+01	0.3321E+02
390	0.8525E+01	0.0000E+00	-0.1469E+02	0.2550E+01	0.5193E+00	0.3354E+01	0.3318E+02
400	0.8672E+01	0.0000E+00	-0.1479E+02	0.2579E+01	0.5124E+00	0.3386E+01	0.3314E+02
410	0.8817E+01	0.0000E+00	-0.1488E+02	0.2608E+01	0.5057E+00	0.3418E+01	0.3311E+02
420	0.8961E+01	0.0000E+00	-0.1497E+02	0.2637E+01	0.4992E+00	0.3449E+01	0.3308E+02
430	0.9104E+01	0.0000E+00	-0.1506E+02	0.2665E+01	0.4929E+00	0.3479E+01	0.3305E+02
440	0.9246E+01	0.0000E+00	-0.1515E+02	0.2693E+01	0.4869E+00	0.3509E+01	0.3302E+02
450	0.9386E+01	0.0000E+00	-0.1523E+02	0.2721E+01	0.4810E+00	0.3538E+01	0.3299E+02
460	0.9525E+01	0.0000E+00	-0.1532E+02	0.2748E+01	0.4753E+00	0.3567E+01	0.3296E+02
470	0.9664E+01	0.0000E+00	-0.1540E+02	0.2775E+01	0.4698E+00	0.3595E+01	0.3294E+02

480	0.9801E+01	0.0000E+00	-0.1548E+02	0.2802E+01	0.4644E+00	0.3623E+01	0.3291E+02
490	0.9937E+01	0.0000E+00	-0.1556E+02	0.2828E+01	0.4592E+00	0.3650E+01	0.3289E+02
500	0.1007E+02	0.0000E+00	-0.1563E+02	0.2854E+01	0.4542E+00	0.3677E+01	0.3286E+02
510	0.1021E+02	0.0000E+00	-0.1571E+02	0.2880E+01	0.4493E+00	0.3704E+01	0.3284E+02
520	0.1034E+02	0.0000E+00	-0.1578E+02	0.2906E+01	0.4445E+00	0.3730E+01	0.3282E+02
530	0.1047E+02	0.0000E+00	-0.1585E+02	0.2931E+01	0.4399E+00	0.3756E+01	0.3280E+02
540	0.1060E+02	0.0000E+00	-0.1592E+02	0.2956E+01	0.4354E+00	0.3781E+01	0.3277E+02
550	0.1073E+02	0.0000E+00	-0.1599E+02	0.2981E+01	0.4310E+00	0.3806E+01	0.3275E+02
560	0.1086E+02	0.0000E+00	-0.1606E+02	0.3006E+01	0.4267E+00	0.3831E+01	0.3273E+02
570	0.1099E+02	0.0000E+00	-0.1612E+02	0.3030E+01	0.4225E+00	0.3856E+01	0.3271E+02
580	0.1112E+02	0.0000E+00	-0.1618E+02	0.3054E+01	0.4185E+00	0.3880E+01	0.3269E+02
590	0.1125E+02	0.0000E+00	-0.1625E+02	0.3078E+01	0.4145E+00	0.3903E+01	0.3267E+02
600	0.1137E+02	0.0000E+00	-0.1631E+02	0.3102E+01	0.4106E+00	0.3927E+01	0.3266E+02
610	0.1150E+02	0.0000E+00	-0.1637E+02	0.3125E+01	0.4069E+00	0.3950E+01	0.3264E+02
611	0.1151E+02	0.0000E+00	-0.1637E+02	0.3128E+01	0.4065E+00	0.3953E+01	0.3264E+02

FSRU Outfall 001 – Case 4 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.5300E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4858E-01	0.6325E-04	-0.5349E+01	0.7134E+00	0.2021E+01	0.1019E+01	0.4138E+02
10	0.4090E+00	0.2501E-02	-0.5707E+01	0.8139E+00	0.1767E+01	0.1161E+01	0.3994E+02
20	0.8059E+00	0.9238E-02	-0.6099E+01	0.9265E+00	0.1549E+01	0.1318E+01	0.3870E+02
30	0.1160E+01	0.1889E-01	-0.6445E+01	0.1029E+01	0.1391E+01	0.1461E+01	0.3781E+02
40	0.1483E+01	0.3070E-01	-0.6757E+01	0.1123E+01	0.1271E+01	0.1592E+01	0.3714E+02
50	0.1782E+01	0.4420E-01	-0.7044E+01	0.1212E+01	0.1176E+01	0.1714E+01	0.3660E+02
60	0.2060E+01	0.5906E-01	-0.7308E+01	0.1296E+01	0.1097E+01	0.1829E+01	0.3616E+02
70	0.2322E+01	0.7504E-01	-0.7555E+01	0.1375E+01	0.1031E+01	0.1937E+01	0.3579E+02
80	0.2570E+01	0.9198E-01	-0.7786E+01	0.1452E+01	0.9751E+00	0.2040E+01	0.3548E+02
90	0.2807E+01	0.1097E+00	-0.8004E+01	0.1525E+01	0.9263E+00	0.2139E+01	0.3521E+02
100	0.3033E+01	0.1282E+00	-0.8211E+01	0.1596E+01	0.8833E+00	0.2234E+01	0.3497E+02
110	0.3249E+01	0.1473E+00	-0.8407E+01	0.1664E+01	0.8452E+00	0.2325E+01	0.3476E+02
120	0.3458E+01	0.1670E+00	-0.8594E+01	0.1731E+01	0.8111E+00	0.2413E+01	0.3457E+02
130	0.3659E+01	0.1872E+00	-0.8772E+01	0.1795E+01	0.7803E+00	0.2498E+01	0.3440E+02
140	0.3854E+01	0.2078E+00	-0.8943E+01	0.1858E+01	0.7524E+00	0.2581E+01	0.3425E+02
150	0.4042E+01	0.2288E+00	-0.9107E+01	0.1920E+01	0.7268E+00	0.2661E+01	0.3411E+02
160	0.4225E+01	0.2502E+00	-0.9265E+01	0.1980E+01	0.7034E+00	0.2739E+01	0.3398E+02
170	0.4403E+01	0.2720E+00	-0.9417E+01	0.2039E+01	0.6818E+00	0.2815E+01	0.3386E+02
180	0.4577E+01	0.2941E+00	-0.9563E+01	0.2096E+01	0.6617E+00	0.2889E+01	0.3375E+02
190	0.4746E+01	0.3164E+00	-0.9704E+01	0.2153E+01	0.6431E+00	0.2961E+01	0.3365E+02
200	0.4911E+01	0.3391E+00	-0.9841E+01	0.2208E+01	0.6257E+00	0.3031E+01	0.3356E+02
210	0.5072E+01	0.3620E+00	-0.9972E+01	0.2263E+01	0.6095E+00	0.3100E+01	0.3347E+02
220	0.5230E+01	0.3852E+00	-0.1010E+02	0.2316E+01	0.5942E+00	0.3168E+01	0.3339E+02
230	0.5384E+01	0.4085E+00	-0.1022E+02	0.2369E+01	0.5799E+00	0.3234E+01	0.3331E+02
240	0.5536E+01	0.4321E+00	-0.1034E+02	0.2421E+01	0.5664E+00	0.3299E+01	0.3324E+02
250	0.5684E+01	0.4559E+00	-0.1046E+02	0.2472E+01	0.5536E+00	0.3363E+01	0.3317E+02
260	0.5830E+01	0.4799E+00	-0.1057E+02	0.2523E+01	0.5415E+00	0.3425E+01	0.3310E+02
270	0.5973E+01	0.5040E+00	-0.1068E+02	0.2573E+01	0.5300E+00	0.3487E+01	0.3304E+02
280	0.6113E+01	0.5284E+00	-0.1079E+02	0.2622E+01	0.5191E+00	0.3547E+01	0.3298E+02
290	0.6252E+01	0.5529E+00	-0.1089E+02	0.2671E+01	0.5087E+00	0.3607E+01	0.3293E+02
300	0.6388E+01	0.5775E+00	-0.1099E+02	0.2719E+01	0.4988E+00	0.3665E+01	0.3287E+02
310	0.6522E+01	0.6023E+00	-0.1109E+02	0.2767E+01	0.4893E+00	0.3723E+01	0.3282E+02
320	0.6653E+01	0.6272E+00	-0.1119E+02	0.2814E+01	0.4803E+00	0.3780E+01	0.3278E+02
330	0.6783E+01	0.6523E+00	-0.1128E+02	0.2861E+01	0.4716E+00	0.3835E+01	0.3273E+02
340	0.6911E+01	0.6775E+00	-0.1137E+02	0.2907E+01	0.4633E+00	0.3891E+01	0.3268E+02
350	0.7038E+01	0.7028E+00	-0.1146E+02	0.2952E+01	0.4554E+00	0.3945E+01	0.3264E+02
360	0.7162E+01	0.7282E+00	-0.1154E+02	0.2998E+01	0.4477E+00	0.3999E+01	0.3260E+02
370	0.7285E+01	0.7538E+00	-0.1163E+02	0.3043E+01	0.4404E+00	0.4052E+01	0.3256E+02
380	0.7406E+01	0.7794E+00	-0.1171E+02	0.3087E+01	0.4333E+00	0.4104E+01	0.3252E+02
390	0.7526E+01	0.8052E+00	-0.1179E+02	0.3131E+01	0.4265E+00	0.4156E+01	0.3249E+02
400	0.7644E+01	0.8310E+00	-0.1186E+02	0.3175E+01	0.4199E+00	0.4207E+01	0.3245E+02
410	0.7761E+01	0.8570E+00	-0.1194E+02	0.3218E+01	0.4136E+00	0.4258E+01	0.3242E+02
420	0.7877E+01	0.8830E+00	-0.1201E+02	0.3262E+01	0.4074E+00	0.4308E+01	0.3239E+02
430	0.7991E+01	0.9092E+00	-0.1208E+02	0.3304E+01	0.4015E+00	0.4358E+01	0.3235E+02
440	0.8104E+01	0.9354E+00	-0.1215E+02	0.3347E+01	0.3958E+00	0.4407E+01	0.3232E+02
450	0.8215E+01	0.9617E+00	-0.1222E+02	0.3389E+01	0.3903E+00	0.4456E+01	0.3229E+02
460	0.8326E+01	0.9881E+00	-0.1229E+02	0.3431E+01	0.3849E+00	0.4504E+01	0.3226E+02
470	0.8435E+01	0.1015E+01	-0.1235E+02	0.3472E+01	0.3797E+00	0.4551E+01	0.3224E+02

480	0.8543E+01	0.1041E+01	-0.1242E+02	0.3514E+01	0.3747E+00	0.4599E+01	0.3221E+02
490	0.8650E+01	0.1068E+01	-0.1248E+02	0.3555E+01	0.3698E+00	0.4646E+01	0.3218E+02
500	0.8756E+01	0.1095E+01	-0.1254E+02	0.3596E+01	0.3651E+00	0.4692E+01	0.3216E+02
510	0.8861E+01	0.1121E+01	-0.1260E+02	0.3636E+01	0.3605E+00	0.4738E+01	0.3213E+02
520	0.8965E+01	0.1148E+01	-0.1266E+02	0.3677E+01	0.3560E+00	0.4784E+01	0.3211E+02
530	0.9068E+01	0.1175E+01	-0.1271E+02	0.3717E+01	0.3517E+00	0.4830E+01	0.3208E+02
540	0.9170E+01	0.1202E+01	-0.1277E+02	0.3757E+01	0.3475E+00	0.4875E+01	0.3206E+02
550	0.9271E+01	0.1229E+01	-0.1282E+02	0.3797E+01	0.3433E+00	0.4920E+01	0.3204E+02
560	0.9371E+01	0.1256E+01	-0.1287E+02	0.3836E+01	0.3394E+00	0.4965E+01	0.3202E+02
570	0.9470E+01	0.1283E+01	-0.1292E+02	0.3876E+01	0.3355E+00	0.5009E+01	0.3200E+02
580	0.9569E+01	0.1311E+01	-0.1297E+02	0.3915E+01	0.3317E+00	0.5053E+01	0.3197E+02
590	0.9666E+01	0.1338E+01	-0.1302E+02	0.3954E+01	0.3280E+00	0.5097E+01	0.3195E+02
600	0.9763E+01	0.1365E+01	-0.1307E+02	0.3992E+01	0.3244E+00	0.5141E+01	0.3193E+02
610	0.9859E+01	0.1393E+01	-0.1311E+02	0.4031E+01	0.3209E+00	0.5184E+01	0.3191E+02
620	0.9954E+01	0.1420E+01	-0.1316E+02	0.4070E+01	0.3175E+00	0.5227E+01	0.3190E+02
630	0.1005E+02	0.1448E+01	-0.1320E+02	0.4108E+01	0.3142E+00	0.5270E+01	0.3188E+02
640	0.1014E+02	0.1475E+01	-0.1324E+02	0.4146E+01	0.3109E+00	0.5313E+01	0.3186E+02
650	0.1023E+02	0.1503E+01	-0.1328E+02	0.4184E+01	0.3078E+00	0.5356E+01	0.3184E+02
660	0.1033E+02	0.1530E+01	-0.1332E+02	0.4222E+01	0.3047E+00	0.5398E+01	0.3182E+02
670	0.1042E+02	0.1558E+01	-0.1336E+02	0.4259E+01	0.3016E+00	0.5440E+01	0.3181E+02
680	0.1051E+02	0.1586E+01	-0.1340E+02	0.4297E+01	0.2987E+00	0.5483E+01	0.3179E+02
690	0.1060E+02	0.1614E+01	-0.1343E+02	0.4334E+01	0.2958E+00	0.5525E+01	0.3177E+02
700	0.1069E+02	0.1642E+01	-0.1347E+02	0.4371E+01	0.2930E+00	0.5566E+01	0.3176E+02
710	0.1078E+02	0.1669E+01	-0.1350E+02	0.4408E+01	0.2903E+00	0.5608E+01	0.3174E+02
720	0.1086E+02	0.1697E+01	-0.1354E+02	0.4445E+01	0.2876E+00	0.5650E+01	0.3172E+02
730	0.1095E+02	0.1725E+01	-0.1357E+02	0.4482E+01	0.2850E+00	0.5691E+01	0.3171E+02
740	0.1104E+02	0.1753E+01	-0.1360E+02	0.4518E+01	0.2824E+00	0.5733E+01	0.3169E+02
750	0.1112E+02	0.1782E+01	-0.1363E+02	0.4555E+01	0.2799E+00	0.5774E+01	0.3168E+02
760	0.1121E+02	0.1810E+01	-0.1366E+02	0.4591E+01	0.2775E+00	0.5815E+01	0.3166E+02
770	0.1129E+02	0.1838E+01	-0.1369E+02	0.4627E+01	0.2751E+00	0.5857E+01	0.3165E+02
780	0.1138E+02	0.1866E+01	-0.1372E+02	0.4663E+01	0.2728E+00	0.5898E+01	0.3163E+02
790	0.1146E+02	0.1894E+01	-0.1375E+02	0.4699E+01	0.2705E+00	0.5939E+01	0.3162E+02
800	0.1154E+02	0.1923E+01	-0.1377E+02	0.4735E+01	0.2683E+00	0.5980E+01	0.3161E+02
810	0.1163E+02	0.1951E+01	-0.1380E+02	0.4771E+01	0.2661E+00	0.6021E+01	0.3159E+02
820	0.1171E+02	0.1979E+01	-0.1382E+02	0.4806E+01	0.2640E+00	0.6062E+01	0.3158E+02
830	0.1179E+02	0.2008E+01	-0.1384E+02	0.4841E+01	0.2619E+00	0.6103E+01	0.3157E+02
840	0.1187E+02	0.2036E+01	-0.1387E+02	0.4877E+01	0.2598E+00	0.6143E+01	0.3155E+02
850	0.1195E+02	0.2064E+01	-0.1389E+02	0.4912E+01	0.2578E+00	0.6184E+01	0.3154E+02
860	0.1203E+02	0.2093E+01	-0.1391E+02	0.4946E+01	0.2559E+00	0.6225E+01	0.3153E+02
870	0.1211E+02	0.2122E+01	-0.1393E+02	0.4981E+01	0.2540E+00	0.6266E+01	0.3152E+02
880	0.1219E+02	0.2150E+01	-0.1395E+02	0.5016E+01	0.2521E+00	0.6306E+01	0.3150E+02
890	0.1227E+02	0.2179E+01	-0.1397E+02	0.5050E+01	0.2503E+00	0.6347E+01	0.3149E+02
900	0.1235E+02	0.2207E+01	-0.1399E+02	0.5085E+01	0.2485E+00	0.6388E+01	0.3148E+02
910	0.1242E+02	0.2236E+01	-0.1400E+02	0.5119E+01	0.2468E+00	0.6428E+01	0.3147E+02
920	0.1250E+02	0.2265E+01	-0.1402E+02	0.5153E+01	0.2450E+00	0.6469E+01	0.3145E+02
930	0.1258E+02	0.2293E+01	-0.1403E+02	0.5187E+01	0.2434E+00	0.6510E+01	0.3144E+02
940	0.1265E+02	0.2322E+01	-0.1405E+02	0.5220E+01	0.2417E+00	0.6550E+01	0.3143E+02
943	0.1267E+02	0.2331E+01	-0.1405E+02	0.5228E+01	0.2414E+00	0.6559E+01	0.3143E+02

FSRU Outfall 001 – Case 5 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6350E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4858E-01	0.6325E-04	-0.6399E+01	0.7134E+00	0.2021E+01	0.1019E+01	0.4138E+02
10	0.4090E+00	0.2501E-02	-0.6757E+01	0.8139E+00	0.1767E+01	0.1161E+01	0.3994E+02
20	0.8059E+00	0.9238E-02	-0.7149E+01	0.9265E+00	0.1549E+01	0.1318E+01	0.3870E+02
30	0.1160E+01	0.1889E-01	-0.7495E+01	0.1029E+01	0.1391E+01	0.1461E+01	0.3781E+02
40	0.1483E+01	0.3070E-01	-0.7807E+01	0.1123E+01	0.1271E+01	0.1592E+01	0.3714E+02
50	0.1782E+01	0.4420E-01	-0.8094E+01	0.1212E+01	0.1176E+01	0.1714E+01	0.3660E+02
60	0.2060E+01	0.5906E-01	-0.8358E+01	0.1296E+01	0.1097E+01	0.1829E+01	0.3616E+02
70	0.2322E+01	0.7504E-01	-0.8605E+01	0.1375E+01	0.1031E+01	0.1937E+01	0.3579E+02
80	0.2570E+01	0.9198E-01	-0.8836E+01	0.1452E+01	0.9751E+00	0.2040E+01	0.3548E+02
90	0.2807E+01	0.1097E+00	-0.9054E+01	0.1525E+01	0.9263E+00	0.2139E+01	0.3521E+02
100	0.3033E+01	0.1282E+00	-0.9261E+01	0.1596E+01	0.8833E+00	0.2234E+01	0.3497E+02
110	0.3249E+01	0.1473E+00	-0.9457E+01	0.1664E+01	0.8452E+00	0.2325E+01	0.3476E+02
120	0.3458E+01	0.1670E+00	-0.9644E+01	0.1731E+01	0.8111E+00	0.2413E+01	0.3457E+02
130	0.3659E+01	0.1872E+00	-0.9822E+01	0.1795E+01	0.7803E+00	0.2498E+01	0.3440E+02
140	0.3854E+01	0.2078E+00	-0.9993E+01	0.1858E+01	0.7524E+00	0.2581E+01	0.3425E+02
150	0.4042E+01	0.2288E+00	-0.1016E+02	0.1920E+01	0.7268E+00	0.2661E+01	0.3411E+02
160	0.4225E+01	0.2502E+00	-0.1031E+02	0.1980E+01	0.7034E+00	0.2739E+01	0.3398E+02
170	0.4403E+01	0.2720E+00	-0.1047E+02	0.2039E+01	0.6818E+00	0.2815E+01	0.3386E+02
180	0.4577E+01	0.2941E+00	-0.1061E+02	0.2096E+01	0.6617E+00	0.2889E+01	0.3375E+02
190	0.4746E+01	0.3164E+00	-0.1075E+02	0.2153E+01	0.6431E+00	0.2961E+01	0.3365E+02
200	0.4911E+01	0.3391E+00	-0.1089E+02	0.2208E+01	0.6257E+00	0.3031E+01	0.3356E+02
210	0.5072E+01	0.3620E+00	-0.1102E+02	0.2263E+01	0.6095E+00	0.3100E+01	0.3347E+02
220	0.5230E+01	0.3852E+00	-0.1115E+02	0.2316E+01	0.5942E+00	0.3168E+01	0.3339E+02
230	0.5384E+01	0.4085E+00	-0.1127E+02	0.2369E+01	0.5799E+00	0.3234E+01	0.3331E+02
240	0.5536E+01	0.4321E+00	-0.1139E+02	0.2421E+01	0.5664E+00	0.3299E+01	0.3324E+02
250	0.5684E+01	0.4559E+00	-0.1151E+02	0.2472E+01	0.5536E+00	0.3363E+01	0.3317E+02
260	0.5830E+01	0.4799E+00	-0.1162E+02	0.2523E+01	0.5415E+00	0.3425E+01	0.3310E+02
270	0.5973E+01	0.5040E+00	-0.1173E+02	0.2573E+01	0.5300E+00	0.3487E+01	0.3304E+02
280	0.6113E+01	0.5284E+00	-0.1184E+02	0.2622E+01	0.5191E+00	0.3547E+01	0.3298E+02
290	0.6252E+01	0.5529E+00	-0.1194E+02	0.2671E+01	0.5087E+00	0.3607E+01	0.3293E+02
300	0.6388E+01	0.5775E+00	-0.1204E+02	0.2719E+01	0.4988E+00	0.3665E+01	0.3287E+02
310	0.6522E+01	0.6023E+00	-0.1214E+02	0.2767E+01	0.4893E+00	0.3723E+01	0.3282E+02
320	0.6653E+01	0.6272E+00	-0.1224E+02	0.2814E+01	0.4803E+00	0.3780E+01	0.3278E+02
330	0.6783E+01	0.6523E+00	-0.1233E+02	0.2861E+01	0.4716E+00	0.3835E+01	0.3273E+02
340	0.6911E+01	0.6775E+00	-0.1242E+02	0.2907E+01	0.4633E+00	0.3891E+01	0.3268E+02
350	0.7038E+01	0.7028E+00	-0.1251E+02	0.2952E+01	0.4554E+00	0.3945E+01	0.3264E+02
360	0.7162E+01	0.7282E+00	-0.1259E+02	0.2998E+01	0.4477E+00	0.3999E+01	0.3260E+02
370	0.7285E+01	0.7538E+00	-0.1268E+02	0.3043E+01	0.4404E+00	0.4052E+01	0.3256E+02
380	0.7406E+01	0.7794E+00	-0.1276E+02	0.3087E+01	0.4333E+00	0.4104E+01	0.3252E+02
390	0.7526E+01	0.8052E+00	-0.1284E+02	0.3131E+01	0.4265E+00	0.4156E+01	0.3249E+02
400	0.7644E+01	0.8310E+00	-0.1291E+02	0.3175E+01	0.4199E+00	0.4207E+01	0.3245E+02
410	0.7761E+01	0.8570E+00	-0.1299E+02	0.3218E+01	0.4136E+00	0.4258E+01	0.3242E+02
420	0.7877E+01	0.8830E+00	-0.1306E+02	0.3262E+01	0.4074E+00	0.4308E+01	0.3239E+02
430	0.7991E+01	0.9092E+00	-0.1313E+02	0.3304E+01	0.4015E+00	0.4358E+01	0.3235E+02
440	0.8104E+01	0.9354E+00	-0.1320E+02	0.3347E+01	0.3958E+00	0.4407E+01	0.3232E+02
450	0.8215E+01	0.9617E+00	-0.1327E+02	0.3389E+01	0.3903E+00	0.4456E+01	0.3229E+02
460	0.8326E+01	0.9881E+00	-0.1334E+02	0.3431E+01	0.3849E+00	0.4504E+01	0.3226E+02
470	0.8435E+01	0.1015E+01	-0.1340E+02	0.3472E+01	0.3797E+00	0.4551E+01	0.3224E+02

480	0.8543E+01	0.1041E+01	-0.1347E+02	0.3514E+01	0.3747E+00	0.4599E+01	0.3221E+02
490	0.8650E+01	0.1068E+01	-0.1353E+02	0.3555E+01	0.3698E+00	0.4646E+01	0.3218E+02
500	0.8756E+01	0.1095E+01	-0.1359E+02	0.3596E+01	0.3651E+00	0.4692E+01	0.3216E+02
510	0.8861E+01	0.1121E+01	-0.1365E+02	0.3636E+01	0.3605E+00	0.4738E+01	0.3213E+02
520	0.8965E+01	0.1148E+01	-0.1371E+02	0.3677E+01	0.3560E+00	0.4784E+01	0.3211E+02
530	0.9068E+01	0.1175E+01	-0.1376E+02	0.3717E+01	0.3517E+00	0.4830E+01	0.3208E+02
540	0.9170E+01	0.1202E+01	-0.1382E+02	0.3757E+01	0.3475E+00	0.4875E+01	0.3206E+02
550	0.9271E+01	0.1229E+01	-0.1387E+02	0.3797E+01	0.3433E+00	0.4920E+01	0.3204E+02
560	0.9371E+01	0.1256E+01	-0.1392E+02	0.3836E+01	0.3394E+00	0.4965E+01	0.3202E+02
570	0.9470E+01	0.1283E+01	-0.1397E+02	0.3876E+01	0.3355E+00	0.5009E+01	0.3200E+02
580	0.9569E+01	0.1311E+01	-0.1402E+02	0.3915E+01	0.3317E+00	0.5053E+01	0.3197E+02
590	0.9666E+01	0.1338E+01	-0.1407E+02	0.3954E+01	0.3280E+00	0.5097E+01	0.3195E+02
600	0.9763E+01	0.1365E+01	-0.1412E+02	0.3992E+01	0.3244E+00	0.5141E+01	0.3193E+02
610	0.9859E+01	0.1393E+01	-0.1416E+02	0.4031E+01	0.3209E+00	0.5184E+01	0.3191E+02
620	0.9954E+01	0.1420E+01	-0.1421E+02	0.4070E+01	0.3175E+00	0.5227E+01	0.3190E+02
630	0.1005E+02	0.1448E+01	-0.1425E+02	0.4108E+01	0.3142E+00	0.5270E+01	0.3188E+02
640	0.1014E+02	0.1475E+01	-0.1429E+02	0.4146E+01	0.3109E+00	0.5313E+01	0.3186E+02
650	0.1023E+02	0.1503E+01	-0.1433E+02	0.4184E+01	0.3078E+00	0.5356E+01	0.3184E+02
660	0.1033E+02	0.1530E+01	-0.1437E+02	0.4222E+01	0.3047E+00	0.5398E+01	0.3182E+02
670	0.1042E+02	0.1558E+01	-0.1441E+02	0.4259E+01	0.3016E+00	0.5440E+01	0.3181E+02
680	0.1051E+02	0.1586E+01	-0.1445E+02	0.4297E+01	0.2987E+00	0.5483E+01	0.3179E+02
690	0.1060E+02	0.1614E+01	-0.1448E+02	0.4334E+01	0.2958E+00	0.5525E+01	0.3177E+02
700	0.1069E+02	0.1642E+01	-0.1452E+02	0.4371E+01	0.2930E+00	0.5566E+01	0.3176E+02
710	0.1078E+02	0.1669E+01	-0.1455E+02	0.4408E+01	0.2903E+00	0.5608E+01	0.3174E+02
720	0.1086E+02	0.1697E+01	-0.1459E+02	0.4445E+01	0.2876E+00	0.5650E+01	0.3172E+02
730	0.1095E+02	0.1725E+01	-0.1462E+02	0.4482E+01	0.2850E+00	0.5691E+01	0.3171E+02
740	0.1104E+02	0.1753E+01	-0.1465E+02	0.4518E+01	0.2824E+00	0.5733E+01	0.3169E+02
750	0.1112E+02	0.1782E+01	-0.1468E+02	0.4555E+01	0.2799E+00	0.5774E+01	0.3168E+02
760	0.1121E+02	0.1810E+01	-0.1471E+02	0.4591E+01	0.2775E+00	0.5815E+01	0.3166E+02
770	0.1129E+02	0.1838E+01	-0.1474E+02	0.4627E+01	0.2751E+00	0.5857E+01	0.3165E+02
777	0.1135E+02	0.1858E+01	-0.1476E+02	0.4652E+01	0.2735E+00	0.5885E+01	0.3164E+02

FSRU Outfall 001 – Case 6 (Table 4)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7400E+01	0.7000E+00	0.2060E+01	0.1000E+01	0.4160E+02
2	0.4858E-01	0.6325E-04	-0.7449E+01	0.7134E+00	0.2021E+01	0.1019E+01	0.4138E+02
10	0.4090E+00	0.2501E-02	-0.7807E+01	0.8139E+00	0.1767E+01	0.1161E+01	0.3994E+02
20	0.8059E+00	0.9238E-02	-0.8199E+01	0.9265E+00	0.1549E+01	0.1318E+01	0.3870E+02
30	0.1160E+01	0.1889E-01	-0.8545E+01	0.1029E+01	0.1391E+01	0.1461E+01	0.3781E+02
40	0.1483E+01	0.3070E-01	-0.8857E+01	0.1123E+01	0.1271E+01	0.1592E+01	0.3714E+02
50	0.1782E+01	0.4420E-01	-0.9144E+01	0.1212E+01	0.1176E+01	0.1714E+01	0.3660E+02
60	0.2060E+01	0.5906E-01	-0.9408E+01	0.1296E+01	0.1097E+01	0.1829E+01	0.3616E+02
70	0.2322E+01	0.7504E-01	-0.9655E+01	0.1375E+01	0.1031E+01	0.1937E+01	0.3579E+02
80	0.2570E+01	0.9198E-01	-0.9886E+01	0.1452E+01	0.9751E+00	0.2040E+01	0.3548E+02
90	0.2807E+01	0.1097E+00	-0.1010E+02	0.1525E+01	0.9263E+00	0.2139E+01	0.3521E+02
100	0.3033E+01	0.1282E+00	-0.1031E+02	0.1596E+01	0.8833E+00	0.2234E+01	0.3497E+02
110	0.3249E+01	0.1473E+00	-0.1051E+02	0.1664E+01	0.8452E+00	0.2325E+01	0.3476E+02
120	0.3458E+01	0.1670E+00	-0.1069E+02	0.1731E+01	0.8111E+00	0.2413E+01	0.3457E+02
130	0.3659E+01	0.1872E+00	-0.1087E+02	0.1795E+01	0.7803E+00	0.2498E+01	0.3440E+02
140	0.3854E+01	0.2078E+00	-0.1104E+02	0.1858E+01	0.7524E+00	0.2581E+01	0.3425E+02
150	0.4042E+01	0.2288E+00	-0.1121E+02	0.1920E+01	0.7268E+00	0.2661E+01	0.3411E+02
160	0.4225E+01	0.2502E+00	-0.1136E+02	0.1980E+01	0.7034E+00	0.2739E+01	0.3398E+02
170	0.4403E+01	0.2720E+00	-0.1152E+02	0.2039E+01	0.6818E+00	0.2815E+01	0.3386E+02
180	0.4577E+01	0.2941E+00	-0.1166E+02	0.2096E+01	0.6617E+00	0.2889E+01	0.3375E+02
190	0.4746E+01	0.3164E+00	-0.1180E+02	0.2153E+01	0.6431E+00	0.2961E+01	0.3365E+02
200	0.4911E+01	0.3391E+00	-0.1194E+02	0.2208E+01	0.6257E+00	0.3031E+01	0.3356E+02
210	0.5072E+01	0.3620E+00	-0.1207E+02	0.2263E+01	0.6095E+00	0.3100E+01	0.3347E+02
220	0.5230E+01	0.3852E+00	-0.1220E+02	0.2316E+01	0.5942E+00	0.3168E+01	0.3339E+02
230	0.5384E+01	0.4085E+00	-0.1232E+02	0.2369E+01	0.5799E+00	0.3234E+01	0.3331E+02
240	0.5536E+01	0.4321E+00	-0.1244E+02	0.2421E+01	0.5664E+00	0.3299E+01	0.3324E+02
250	0.5684E+01	0.4559E+00	-0.1256E+02	0.2472E+01	0.5536E+00	0.3363E+01	0.3317E+02
260	0.5830E+01	0.4799E+00	-0.1267E+02	0.2523E+01	0.5415E+00	0.3425E+01	0.3310E+02
270	0.5973E+01	0.5040E+00	-0.1278E+02	0.2573E+01	0.5300E+00	0.3487E+01	0.3304E+02
280	0.6113E+01	0.5284E+00	-0.1289E+02	0.2622E+01	0.5191E+00	0.3547E+01	0.3298E+02
290	0.6252E+01	0.5529E+00	-0.1299E+02	0.2671E+01	0.5087E+00	0.3607E+01	0.3293E+02
300	0.6388E+01	0.5775E+00	-0.1309E+02	0.2719E+01	0.4988E+00	0.3665E+01	0.3287E+02
310	0.6522E+01	0.6023E+00	-0.1319E+02	0.2767E+01	0.4893E+00	0.3723E+01	0.3282E+02
320	0.6653E+01	0.6272E+00	-0.1329E+02	0.2814E+01	0.4803E+00	0.3780E+01	0.3278E+02
330	0.6783E+01	0.6523E+00	-0.1338E+02	0.2861E+01	0.4716E+00	0.3835E+01	0.3273E+02
340	0.6911E+01	0.6775E+00	-0.1347E+02	0.2907E+01	0.4633E+00	0.3891E+01	0.3268E+02
350	0.7038E+01	0.7028E+00	-0.1356E+02	0.2952E+01	0.4554E+00	0.3945E+01	0.3264E+02
360	0.7162E+01	0.7282E+00	-0.1364E+02	0.2998E+01	0.4477E+00	0.3999E+01	0.3260E+02
370	0.7285E+01	0.7538E+00	-0.1373E+02	0.3043E+01	0.4404E+00	0.4052E+01	0.3256E+02
380	0.7406E+01	0.7794E+00	-0.1381E+02	0.3087E+01	0.4333E+00	0.4104E+01	0.3252E+02
390	0.7526E+01	0.8052E+00	-0.1389E+02	0.3131E+01	0.4265E+00	0.4156E+01	0.3249E+02
400	0.7644E+01	0.8310E+00	-0.1396E+02	0.3175E+01	0.4199E+00	0.4207E+01	0.3245E+02
410	0.7761E+01	0.8570E+00	-0.1404E+02	0.3218E+01	0.4136E+00	0.4258E+01	0.3242E+02
420	0.7877E+01	0.8830E+00	-0.1411E+02	0.3262E+01	0.4074E+00	0.4308E+01	0.3239E+02
430	0.7991E+01	0.9092E+00	-0.1418E+02	0.3304E+01	0.4015E+00	0.4358E+01	0.3235E+02
440	0.8104E+01	0.9354E+00	-0.1425E+02	0.3347E+01	0.3958E+00	0.4407E+01	0.3232E+02
450	0.8215E+01	0.9617E+00	-0.1432E+02	0.3389E+01	0.3903E+00	0.4456E+01	0.3229E+02
460	0.8326E+01	0.9881E+00	-0.1439E+02	0.3431E+01	0.3849E+00	0.4504E+01	0.3226E+02
470	0.8435E+01	0.1015E+01	-0.1445E+02	0.3472E+01	0.3797E+00	0.4551E+01	0.3224E+02

480	0.8543E+01	0.1041E+01	-0.1452E+02	0.3514E+01	0.3747E+00	0.4599E+01	0.3221E+02
490	0.8650E+01	0.1068E+01	-0.1458E+02	0.3555E+01	0.3698E+00	0.4646E+01	0.3218E+02
500	0.8756E+01	0.1095E+01	-0.1464E+02	0.3596E+01	0.3651E+00	0.4692E+01	0.3216E+02
510	0.8861E+01	0.1121E+01	-0.1470E+02	0.3636E+01	0.3605E+00	0.4738E+01	0.3213E+02
520	0.8965E+01	0.1148E+01	-0.1476E+02	0.3677E+01	0.3560E+00	0.4784E+01	0.3211E+02
530	0.9068E+01	0.1175E+01	-0.1481E+02	0.3717E+01	0.3517E+00	0.4830E+01	0.3208E+02
540	0.9170E+01	0.1202E+01	-0.1487E+02	0.3757E+01	0.3475E+00	0.4875E+01	0.3206E+02
550	0.9271E+01	0.1229E+01	-0.1492E+02	0.3797E+01	0.3433E+00	0.4920E+01	0.3204E+02
560	0.9371E+01	0.1256E+01	-0.1497E+02	0.3836E+01	0.3394E+00	0.4965E+01	0.3202E+02
570	0.9470E+01	0.1283E+01	-0.1502E+02	0.3876E+01	0.3355E+00	0.5009E+01	0.3200E+02
580	0.9569E+01	0.1311E+01	-0.1507E+02	0.3915E+01	0.3317E+00	0.5053E+01	0.3197E+02
590	0.9666E+01	0.1338E+01	-0.1512E+02	0.3954E+01	0.3280E+00	0.5097E+01	0.3195E+02
600	0.9763E+01	0.1365E+01	-0.1517E+02	0.3992E+01	0.3244E+00	0.5141E+01	0.3193E+02
610	0.9859E+01	0.1393E+01	-0.1521E+02	0.4031E+01	0.3209E+00	0.5184E+01	0.3191E+02
620	0.9954E+01	0.1420E+01	-0.1526E+02	0.4070E+01	0.3175E+00	0.5227E+01	0.3190E+02
630	0.1005E+02	0.1448E+01	-0.1530E+02	0.4108E+01	0.3142E+00	0.5270E+01	0.3188E+02
640	0.1014E+02	0.1475E+01	-0.1534E+02	0.4146E+01	0.3109E+00	0.5313E+01	0.3186E+02
646	0.1020E+02	0.1492E+01	-0.1537E+02	0.4166E+01	0.3092E+00	0.5335E+01	0.3185E+02

FSRU Outfall 002 – Case 1 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6300E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1397E-01	0.0000E+00	-0.6314E+01	0.2034E+00	0.2546E+00	0.1013E+01	0.4145E+02
10	0.1204E+00	0.0000E+00	-0.6410E+01	0.2284E+00	0.2191E+00	0.1099E+01	0.4052E+02
20	0.2438E+00	0.0000E+00	-0.6503E+01	0.2557E+00	0.1879E+00	0.1182E+01	0.3975E+02
30	0.3599E+00	0.0000E+00	-0.6571E+01	0.2797E+00	0.1656E+00	0.1246E+01	0.3923E+02
40	0.4707E+00	0.0000E+00	-0.6618E+01	0.3010E+00	0.1493E+00	0.1302E+01	0.3882E+02
50	0.5768E+00	0.0000E+00	-0.6644E+01	0.3201E+00	0.1376E+00	0.1357E+01	0.3844E+02
60	0.6786E+00	0.0000E+00	-0.6653E+01	0.3372E+00	0.1296E+00	0.1419E+01	0.3806E+02
70	0.7756E+00	0.0000E+00	-0.6646E+01	0.3525E+00	0.1247E+00	0.1492E+01	0.3764E+02
80	0.8675E+00	0.0000E+00	-0.6623E+01	0.3664E+00	0.1221E+00	0.1579E+01	0.3720E+02
90	0.9541E+00	0.0000E+00	-0.6588E+01	0.3793E+00	0.1213E+00	0.1681E+01	0.3674E+02
100	0.1035E+01	0.0000E+00	-0.6542E+01	0.3915E+00	0.1216E+00	0.1796E+01	0.3628E+02
110	0.1111E+01	0.0000E+00	-0.6487E+01	0.4034E+00	0.1226E+00	0.1923E+01	0.3584E+02
120	0.1182E+01	0.0000E+00	-0.6424E+01	0.4152E+00	0.1240E+00	0.2059E+01	0.3543E+02
130	0.1248E+01	0.0000E+00	-0.6354E+01	0.4270E+00	0.1254E+00	0.2204E+01	0.3504E+02
140	0.1310E+01	0.0000E+00	-0.6279E+01	0.4390E+00	0.1268E+00	0.2356E+01	0.3469E+02
150	0.1368E+01	0.0000E+00	-0.6200E+01	0.4512E+00	0.1281E+00	0.2515E+01	0.3437E+02
160	0.1422E+01	0.0000E+00	-0.6117E+01	0.4636E+00	0.1293E+00	0.2679E+01	0.3408E+02
170	0.1473E+01	0.0000E+00	-0.6032E+01	0.4762E+00	0.1302E+00	0.2848E+01	0.3381E+02
180	0.1521E+01	0.0000E+00	-0.5943E+01	0.4890E+00	0.1311E+00	0.3023E+01	0.3357E+02
190	0.1567E+01	0.0000E+00	-0.5853E+01	0.5020E+00	0.1317E+00	0.3201E+01	0.3335E+02
200	0.1609E+01	0.0000E+00	-0.5761E+01	0.5151E+00	0.1323E+00	0.3384E+01	0.3315E+02
210	0.1650E+01	0.0000E+00	-0.5667E+01	0.5283E+00	0.1326E+00	0.3571E+01	0.3296E+02
220	0.1689E+01	0.0000E+00	-0.5573E+01	0.5417E+00	0.1329E+00	0.3762E+01	0.3279E+02
230	0.1725E+01	0.0000E+00	-0.5477E+01	0.5551E+00	0.1331E+00	0.3956E+01	0.3263E+02
240	0.1760E+01	0.0000E+00	-0.5381E+01	0.5686E+00	0.1332E+00	0.4154E+01	0.3249E+02
250	0.1793E+01	0.0000E+00	-0.5284E+01	0.5822E+00	0.1331E+00	0.4354E+01	0.3236E+02
260	0.1825E+01	0.0000E+00	-0.5187E+01	0.5959E+00	0.1331E+00	0.4558E+01	0.3223E+02
270	0.1855E+01	0.0000E+00	-0.5089E+01	0.6095E+00	0.1329E+00	0.4765E+01	0.3212E+02
280	0.1884E+01	0.0000E+00	-0.4991E+01	0.6232E+00	0.1327E+00	0.4975E+01	0.3201E+02
290	0.1912E+01	0.0000E+00	-0.4893E+01	0.6370E+00	0.1325E+00	0.5187E+01	0.3191E+02
300	0.1938E+01	0.0000E+00	-0.4794E+01	0.6507E+00	0.1322E+00	0.5402E+01	0.3182E+02
310	0.1964E+01	0.0000E+00	-0.4696E+01	0.6644E+00	0.1319E+00	0.5620E+01	0.3174E+02
320	0.1989E+01	0.0000E+00	-0.4598E+01	0.6782E+00	0.1316E+00	0.5840E+01	0.3165E+02
330	0.2012E+01	0.0000E+00	-0.4500E+01	0.6919E+00	0.1312E+00	0.6063E+01	0.3158E+02
340	0.2035E+01	0.0000E+00	-0.4401E+01	0.7056E+00	0.1309E+00	0.6288E+01	0.3151E+02
350	0.2057E+01	0.0000E+00	-0.4303E+01	0.7193E+00	0.1305E+00	0.6515E+01	0.3144E+02
360	0.2079E+01	0.0000E+00	-0.4206E+01	0.7330E+00	0.1301E+00	0.6744E+01	0.3138E+02
370	0.2099E+01	0.0000E+00	-0.4108E+01	0.7467E+00	0.1297E+00	0.6976E+01	0.3132E+02
380	0.2119E+01	0.0000E+00	-0.4010E+01	0.7603E+00	0.1292E+00	0.7209E+01	0.3126E+02
390	0.2138E+01	0.0000E+00	-0.3913E+01	0.7739E+00	0.1288E+00	0.7445E+01	0.3121E+02
400	0.2157E+01	0.0000E+00	-0.3816E+01	0.7875E+00	0.1284E+00	0.7682E+01	0.3116E+02
410	0.2175E+01	0.0000E+00	-0.3719E+01	0.8010E+00	0.1279E+00	0.7922E+01	0.3111E+02
420	0.2193E+01	0.0000E+00	-0.3622E+01	0.8146E+00	0.1275E+00	0.8163E+01	0.3107E+02
430	0.2210E+01	0.0000E+00	-0.3526E+01	0.8280E+00	0.1270E+00	0.8407E+01	0.3103E+02
440	0.2226E+01	0.0000E+00	-0.3430E+01	0.8415E+00	0.1266E+00	0.8652E+01	0.3099E+02
450	0.2242E+01	0.0000E+00	-0.3334E+01	0.8549E+00	0.1261E+00	0.8898E+01	0.3095E+02
460	0.2258E+01	0.0000E+00	-0.3238E+01	0.8683E+00	0.1257E+00	0.9147E+01	0.3091E+02
470	0.2273E+01	0.0000E+00	-0.3143E+01	0.8816E+00	0.1253E+00	0.9397E+01	0.3088E+02

480	0.2288E+01	0.0000E+00	-0.3048E+01	0.8949E+00	0.1248E+00	0.9649E+01	0.3084E+02
490	0.2303E+01	0.0000E+00	-0.2953E+01	0.9082E+00	0.1244E+00	0.9902E+01	0.3081E+02
500	0.2317E+01	0.0000E+00	-0.2859E+01	0.9214E+00	0.1239E+00	0.1016E+02	0.3078E+02
510	0.2330E+01	0.0000E+00	-0.2765E+01	0.9346E+00	0.1235E+00	0.1041E+02	0.3075E+02
520	0.2344E+01	0.0000E+00	-0.2671E+01	0.9478E+00	0.1231E+00	0.1067E+02	0.3072E+02
530	0.2357E+01	0.0000E+00	-0.2577E+01	0.9609E+00	0.1227E+00	0.1093E+02	0.3070E+02
540	0.2370E+01	0.0000E+00	-0.2484E+01	0.9739E+00	0.1222E+00	0.1119E+02	0.3067E+02
550	0.2382E+01	0.0000E+00	-0.2391E+01	0.9870E+00	0.1218E+00	0.1145E+02	0.3065E+02
560	0.2394E+01	0.0000E+00	-0.2298E+01	0.1000E+01	0.1214E+00	0.1172E+02	0.3062E+02
570	0.2406E+01	0.0000E+00	-0.2206E+01	0.1013E+01	0.1210E+00	0.1198E+02	0.3060E+02
580	0.2418E+01	0.0000E+00	-0.2114E+01	0.1026E+01	0.1206E+00	0.1225E+02	0.3058E+02
590	0.2429E+01	0.0000E+00	-0.2022E+01	0.1039E+01	0.1202E+00	0.1252E+02	0.3056E+02
600	0.2440E+01	0.0000E+00	-0.1930E+01	0.1052E+01	0.1198E+00	0.1279E+02	0.3054E+02
610	0.2451E+01	0.0000E+00	-0.1839E+01	0.1064E+01	0.1194E+00	0.1306E+02	0.3052E+02
620	0.2462E+01	0.0000E+00	-0.1748E+01	0.1077E+01	0.1190E+00	0.1333E+02	0.3050E+02
630	0.2473E+01	0.0000E+00	-0.1657E+01	0.1090E+01	0.1186E+00	0.1360E+02	0.3048E+02
640	0.2483E+01	0.0000E+00	-0.1566E+01	0.1103E+01	0.1183E+00	0.1388E+02	0.3046E+02
650	0.2493E+01	0.0000E+00	-0.1476E+01	0.1115E+01	0.1179E+00	0.1415E+02	0.3045E+02
660	0.2503E+01	0.0000E+00	-0.1386E+01	0.1128E+01	0.1175E+00	0.1443E+02	0.3043E+02
670	0.2513E+01	0.0000E+00	-0.1296E+01	0.1140E+01	0.1171E+00	0.1471E+02	0.3042E+02
680	0.2522E+01	0.0000E+00	-0.1207E+01	0.1153E+01	0.1168E+00	0.1499E+02	0.3040E+02
690	0.2531E+01	0.0000E+00	-0.1118E+01	0.1166E+01	0.1164E+00	0.1527E+02	0.3039E+02
700	0.2541E+01	0.0000E+00	-0.1029E+01	0.1178E+01	0.1161E+00	0.1555E+02	0.3037E+02
710	0.2550E+01	0.0000E+00	-0.9402E+00	0.1190E+01	0.1157E+00	0.1583E+02	0.3036E+02
720	0.2558E+01	0.0000E+00	-0.8518E+00	0.1203E+01	0.1154E+00	0.1612E+02	0.3034E+02
730	0.2567E+01	0.0000E+00	-0.7636E+00	0.1215E+01	0.1150E+00	0.1640E+02	0.3033E+02
740	0.2576E+01	0.0000E+00	-0.6757E+00	0.1228E+01	0.1147E+00	0.1669E+02	0.3032E+02
750	0.2584E+01	0.0000E+00	-0.5880E+00	0.1240E+01	0.1144E+00	0.1697E+02	0.3031E+02
760	0.2592E+01	0.0000E+00	-0.5005E+00	0.1252E+01	0.1140E+00	0.1726E+02	0.3030E+02
770	0.2600E+01	0.0000E+00	-0.4133E+00	0.1264E+01	0.1137E+00	0.1755E+02	0.3028E+02
780	0.2608E+01	0.0000E+00	-0.3264E+00	0.1277E+01	0.1134E+00	0.1784E+02	0.3027E+02
790	0.2616E+01	0.0000E+00	-0.2396E+00	0.1289E+01	0.1131E+00	0.1813E+02	0.3026E+02
800	0.2624E+01	0.0000E+00	-0.1531E+00	0.1301E+01	0.1128E+00	0.1843E+02	0.3025E+02
805	0.2628E+01	0.0000E+00	-0.1100E+00	0.1307E+01	0.1126E+00	0.1857E+02	0.3025E+02

FSRU Outfall 002 – Case 2 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7350E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1397E-01	0.0000E+00	-0.7364E+01	0.2034E+00	0.2546E+00	0.1013E+01	0.4145E+02
10	0.1204E+00	0.0000E+00	-0.7460E+01	0.2284E+00	0.2191E+00	0.1099E+01	0.4052E+02
20	0.2438E+00	0.0000E+00	-0.7553E+01	0.2557E+00	0.1879E+00	0.1182E+01	0.3975E+02
30	0.3599E+00	0.0000E+00	-0.7621E+01	0.2797E+00	0.1656E+00	0.1246E+01	0.3923E+02
40	0.4707E+00	0.0000E+00	-0.7668E+01	0.3010E+00	0.1493E+00	0.1302E+01	0.3882E+02
50	0.5768E+00	0.0000E+00	-0.7694E+01	0.3201E+00	0.1376E+00	0.1357E+01	0.3844E+02
60	0.6786E+00	0.0000E+00	-0.7703E+01	0.3372E+00	0.1296E+00	0.1419E+01	0.3806E+02
70	0.7756E+00	0.0000E+00	-0.7696E+01	0.3525E+00	0.1247E+00	0.1492E+01	0.3764E+02
80	0.8675E+00	0.0000E+00	-0.7673E+01	0.3664E+00	0.1221E+00	0.1579E+01	0.3720E+02
90	0.9541E+00	0.0000E+00	-0.7638E+01	0.3793E+00	0.1213E+00	0.1681E+01	0.3674E+02
100	0.1035E+01	0.0000E+00	-0.7592E+01	0.3915E+00	0.1216E+00	0.1796E+01	0.3628E+02
110	0.1111E+01	0.0000E+00	-0.7537E+01	0.4034E+00	0.1226E+00	0.1923E+01	0.3584E+02
120	0.1182E+01	0.0000E+00	-0.7474E+01	0.4152E+00	0.1240E+00	0.2059E+01	0.3543E+02
130	0.1248E+01	0.0000E+00	-0.7404E+01	0.4270E+00	0.1254E+00	0.2204E+01	0.3504E+02
140	0.1310E+01	0.0000E+00	-0.7329E+01	0.4390E+00	0.1268E+00	0.2356E+01	0.3469E+02
150	0.1368E+01	0.0000E+00	-0.7250E+01	0.4512E+00	0.1281E+00	0.2515E+01	0.3437E+02
160	0.1422E+01	0.0000E+00	-0.7167E+01	0.4636E+00	0.1293E+00	0.2679E+01	0.3408E+02
170	0.1473E+01	0.0000E+00	-0.7082E+01	0.4762E+00	0.1302E+00	0.2848E+01	0.3381E+02
180	0.1521E+01	0.0000E+00	-0.6993E+01	0.4890E+00	0.1311E+00	0.3023E+01	0.3357E+02
190	0.1567E+01	0.0000E+00	-0.6903E+01	0.5020E+00	0.1317E+00	0.3201E+01	0.3335E+02
200	0.1609E+01	0.0000E+00	-0.6811E+01	0.5151E+00	0.1323E+00	0.3384E+01	0.3315E+02
210	0.1650E+01	0.0000E+00	-0.6717E+01	0.5283E+00	0.1326E+00	0.3571E+01	0.3296E+02
220	0.1689E+01	0.0000E+00	-0.6623E+01	0.5417E+00	0.1329E+00	0.3762E+01	0.3279E+02
230	0.1725E+01	0.0000E+00	-0.6527E+01	0.5551E+00	0.1331E+00	0.3956E+01	0.3263E+02
240	0.1760E+01	0.0000E+00	-0.6431E+01	0.5686E+00	0.1332E+00	0.4154E+01	0.3249E+02
250	0.1793E+01	0.0000E+00	-0.6334E+01	0.5822E+00	0.1331E+00	0.4354E+01	0.3236E+02
260	0.1825E+01	0.0000E+00	-0.6237E+01	0.5959E+00	0.1331E+00	0.4558E+01	0.3223E+02
270	0.1855E+01	0.0000E+00	-0.6139E+01	0.6095E+00	0.1329E+00	0.4765E+01	0.3212E+02
280	0.1884E+01	0.0000E+00	-0.6041E+01	0.6232E+00	0.1327E+00	0.4975E+01	0.3201E+02
290	0.1912E+01	0.0000E+00	-0.5943E+01	0.6370E+00	0.1325E+00	0.5187E+01	0.3191E+02
300	0.1938E+01	0.0000E+00	-0.5844E+01	0.6507E+00	0.1322E+00	0.5402E+01	0.3182E+02
310	0.1964E+01	0.0000E+00	-0.5746E+01	0.6644E+00	0.1319E+00	0.5620E+01	0.3174E+02
320	0.1989E+01	0.0000E+00	-0.5648E+01	0.6782E+00	0.1316E+00	0.5840E+01	0.3165E+02
330	0.2012E+01	0.0000E+00	-0.5550E+01	0.6919E+00	0.1312E+00	0.6063E+01	0.3158E+02
340	0.2035E+01	0.0000E+00	-0.5451E+01	0.7056E+00	0.1309E+00	0.6288E+01	0.3151E+02
350	0.2057E+01	0.0000E+00	-0.5353E+01	0.7193E+00	0.1305E+00	0.6515E+01	0.3144E+02
360	0.2079E+01	0.0000E+00	-0.5256E+01	0.7330E+00	0.1301E+00	0.6744E+01	0.3138E+02
370	0.2099E+01	0.0000E+00	-0.5158E+01	0.7467E+00	0.1297E+00	0.6976E+01	0.3132E+02
380	0.2119E+01	0.0000E+00	-0.5060E+01	0.7603E+00	0.1292E+00	0.7209E+01	0.3126E+02
390	0.2138E+01	0.0000E+00	-0.4963E+01	0.7739E+00	0.1288E+00	0.7445E+01	0.3121E+02
400	0.2157E+01	0.0000E+00	-0.4866E+01	0.7875E+00	0.1284E+00	0.7682E+01	0.3116E+02
410	0.2175E+01	0.0000E+00	-0.4769E+01	0.8010E+00	0.1279E+00	0.7922E+01	0.3111E+02
420	0.2193E+01	0.0000E+00	-0.4672E+01	0.8146E+00	0.1275E+00	0.8163E+01	0.3107E+02
430	0.2210E+01	0.0000E+00	-0.4576E+01	0.8280E+00	0.1270E+00	0.8407E+01	0.3103E+02
440	0.2226E+01	0.0000E+00	-0.4480E+01	0.8415E+00	0.1266E+00	0.8652E+01	0.3099E+02
450	0.2242E+01	0.0000E+00	-0.4384E+01	0.8549E+00	0.1261E+00	0.8898E+01	0.3095E+02
460	0.2258E+01	0.0000E+00	-0.4288E+01	0.8683E+00	0.1257E+00	0.9147E+01	0.3091E+02
470	0.2273E+01	0.0000E+00	-0.4193E+01	0.8816E+00	0.1253E+00	0.9397E+01	0.3088E+02

480	0.2288E+01	0.0000E+00	-0.4098E+01	0.8949E+00	0.1248E+00	0.9649E+01	0.3084E+02
490	0.2303E+01	0.0000E+00	-0.4003E+01	0.9082E+00	0.1244E+00	0.9902E+01	0.3081E+02
500	0.2317E+01	0.0000E+00	-0.3909E+01	0.9214E+00	0.1239E+00	0.1016E+02	0.3078E+02
510	0.2330E+01	0.0000E+00	-0.3815E+01	0.9346E+00	0.1235E+00	0.1041E+02	0.3075E+02
520	0.2344E+01	0.0000E+00	-0.3721E+01	0.9478E+00	0.1231E+00	0.1067E+02	0.3072E+02
530	0.2357E+01	0.0000E+00	-0.3627E+01	0.9609E+00	0.1227E+00	0.1093E+02	0.3070E+02
540	0.2370E+01	0.0000E+00	-0.3534E+01	0.9739E+00	0.1222E+00	0.1119E+02	0.3067E+02
550	0.2382E+01	0.0000E+00	-0.3441E+01	0.9870E+00	0.1218E+00	0.1145E+02	0.3065E+02
560	0.2394E+01	0.0000E+00	-0.3348E+01	0.1000E+01	0.1214E+00	0.1172E+02	0.3062E+02
570	0.2406E+01	0.0000E+00	-0.3256E+01	0.1013E+01	0.1210E+00	0.1198E+02	0.3060E+02
580	0.2418E+01	0.0000E+00	-0.3164E+01	0.1026E+01	0.1206E+00	0.1225E+02	0.3058E+02
590	0.2429E+01	0.0000E+00	-0.3072E+01	0.1039E+01	0.1202E+00	0.1252E+02	0.3056E+02
600	0.2440E+01	0.0000E+00	-0.2980E+01	0.1052E+01	0.1198E+00	0.1279E+02	0.3054E+02
610	0.2451E+01	0.0000E+00	-0.2889E+01	0.1064E+01	0.1194E+00	0.1306E+02	0.3052E+02
620	0.2462E+01	0.0000E+00	-0.2798E+01	0.1077E+01	0.1190E+00	0.1333E+02	0.3050E+02
630	0.2473E+01	0.0000E+00	-0.2707E+01	0.1090E+01	0.1186E+00	0.1360E+02	0.3048E+02
640	0.2483E+01	0.0000E+00	-0.2616E+01	0.1103E+01	0.1183E+00	0.1388E+02	0.3046E+02
650	0.2493E+01	0.0000E+00	-0.2526E+01	0.1115E+01	0.1179E+00	0.1415E+02	0.3045E+02
660	0.2503E+01	0.0000E+00	-0.2436E+01	0.1128E+01	0.1175E+00	0.1443E+02	0.3043E+02
670	0.2513E+01	0.0000E+00	-0.2346E+01	0.1140E+01	0.1171E+00	0.1471E+02	0.3042E+02
680	0.2522E+01	0.0000E+00	-0.2257E+01	0.1153E+01	0.1168E+00	0.1499E+02	0.3040E+02
690	0.2531E+01	0.0000E+00	-0.2168E+01	0.1166E+01	0.1164E+00	0.1527E+02	0.3039E+02
700	0.2541E+01	0.0000E+00	-0.2079E+01	0.1178E+01	0.1161E+00	0.1555E+02	0.3037E+02
710	0.2550E+01	0.0000E+00	-0.1990E+01	0.1190E+01	0.1157E+00	0.1583E+02	0.3036E+02
720	0.2558E+01	0.0000E+00	-0.1902E+01	0.1203E+01	0.1154E+00	0.1612E+02	0.3034E+02
730	0.2567E+01	0.0000E+00	-0.1814E+01	0.1215E+01	0.1150E+00	0.1640E+02	0.3033E+02
740	0.2576E+01	0.0000E+00	-0.1726E+01	0.1228E+01	0.1147E+00	0.1669E+02	0.3032E+02
750	0.2584E+01	0.0000E+00	-0.1638E+01	0.1240E+01	0.1144E+00	0.1697E+02	0.3031E+02
760	0.2592E+01	0.0000E+00	-0.1551E+01	0.1252E+01	0.1140E+00	0.1726E+02	0.3030E+02
770	0.2600E+01	0.0000E+00	-0.1463E+01	0.1264E+01	0.1137E+00	0.1755E+02	0.3028E+02
780	0.2608E+01	0.0000E+00	-0.1376E+01	0.1277E+01	0.1134E+00	0.1784E+02	0.3027E+02
790	0.2616E+01	0.0000E+00	-0.1290E+01	0.1289E+01	0.1131E+00	0.1813E+02	0.3026E+02
800	0.2624E+01	0.0000E+00	-0.1203E+01	0.1301E+01	0.1128E+00	0.1843E+02	0.3025E+02
810	0.2632E+01	0.0000E+00	-0.1117E+01	0.1313E+01	0.1124E+00	0.1872E+02	0.3024E+02
820	0.2639E+01	0.0000E+00	-0.1031E+01	0.1325E+01	0.1121E+00	0.1901E+02	0.3023E+02
830	0.2646E+01	0.0000E+00	-0.9450E+00	0.1337E+01	0.1118E+00	0.1931E+02	0.3022E+02
840	0.2654E+01	0.0000E+00	-0.8594E+00	0.1349E+01	0.1115E+00	0.1960E+02	0.3021E+02
850	0.2661E+01	0.0000E+00	-0.7740E+00	0.1361E+01	0.1112E+00	0.1990E+02	0.3020E+02
860	0.2668E+01	0.0000E+00	-0.6889E+00	0.1373E+01	0.1110E+00	0.2020E+02	0.3019E+02
870	0.2675E+01	0.0000E+00	-0.6039E+00	0.1385E+01	0.1107E+00	0.2050E+02	0.3019E+02
880	0.2682E+01	0.0000E+00	-0.5192E+00	0.1397E+01	0.1104E+00	0.2080E+02	0.3018E+02
890	0.2688E+01	0.0000E+00	-0.4347E+00	0.1409E+01	0.1101E+00	0.2110E+02	0.3017E+02
900	0.2695E+01	0.0000E+00	-0.3504E+00	0.1421E+01	0.1098E+00	0.2140E+02	0.3016E+02
910	0.2702E+01	0.0000E+00	-0.2663E+00	0.1433E+01	0.1095E+00	0.2170E+02	0.3015E+02
920	0.2708E+01	0.0000E+00	-0.1824E+00	0.1444E+01	0.1093E+00	0.2201E+02	0.3015E+02
929	0.2714E+01	0.0000E+00	-0.1070E+00	0.1455E+01	0.1090E+00	0.2228E+02	0.3014E+02

FSRU Outfall 002 – Case 3 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.8400E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1397E-01	0.0000E+00	-0.8414E+01	0.2034E+00	0.2546E+00	0.1013E+01	0.4145E+02
10	0.1204E+00	0.0000E+00	-0.8510E+01	0.2284E+00	0.2191E+00	0.1099E+01	0.4052E+02
20	0.2438E+00	0.0000E+00	-0.8603E+01	0.2557E+00	0.1879E+00	0.1182E+01	0.3975E+02
30	0.3599E+00	0.0000E+00	-0.8671E+01	0.2797E+00	0.1656E+00	0.1246E+01	0.3923E+02
40	0.4707E+00	0.0000E+00	-0.8718E+01	0.3010E+00	0.1493E+00	0.1302E+01	0.3882E+02
50	0.5768E+00	0.0000E+00	-0.8744E+01	0.3201E+00	0.1376E+00	0.1357E+01	0.3844E+02
60	0.6786E+00	0.0000E+00	-0.8753E+01	0.3372E+00	0.1296E+00	0.1419E+01	0.3806E+02
70	0.7756E+00	0.0000E+00	-0.8746E+01	0.3525E+00	0.1247E+00	0.1492E+01	0.3764E+02
80	0.8675E+00	0.0000E+00	-0.8723E+01	0.3664E+00	0.1221E+00	0.1579E+01	0.3720E+02
90	0.9541E+00	0.0000E+00	-0.8688E+01	0.3793E+00	0.1213E+00	0.1681E+01	0.3674E+02
100	0.1035E+01	0.0000E+00	-0.8642E+01	0.3915E+00	0.1216E+00	0.1796E+01	0.3628E+02
110	0.1111E+01	0.0000E+00	-0.8587E+01	0.4034E+00	0.1226E+00	0.1923E+01	0.3584E+02
120	0.1182E+01	0.0000E+00	-0.8524E+01	0.4152E+00	0.1240E+00	0.2059E+01	0.3543E+02
130	0.1248E+01	0.0000E+00	-0.8454E+01	0.4270E+00	0.1254E+00	0.2204E+01	0.3504E+02
140	0.1310E+01	0.0000E+00	-0.8379E+01	0.4390E+00	0.1268E+00	0.2356E+01	0.3469E+02
150	0.1368E+01	0.0000E+00	-0.8300E+01	0.4512E+00	0.1281E+00	0.2515E+01	0.3437E+02
160	0.1422E+01	0.0000E+00	-0.8217E+01	0.4636E+00	0.1293E+00	0.2679E+01	0.3408E+02
170	0.1473E+01	0.0000E+00	-0.8132E+01	0.4762E+00	0.1302E+00	0.2848E+01	0.3381E+02
180	0.1521E+01	0.0000E+00	-0.8043E+01	0.4890E+00	0.1311E+00	0.3023E+01	0.3357E+02
190	0.1567E+01	0.0000E+00	-0.7953E+01	0.5020E+00	0.1317E+00	0.3201E+01	0.3335E+02
200	0.1609E+01	0.0000E+00	-0.7861E+01	0.5151E+00	0.1323E+00	0.3384E+01	0.3315E+02
210	0.1650E+01	0.0000E+00	-0.7767E+01	0.5283E+00	0.1326E+00	0.3571E+01	0.3296E+02
220	0.1689E+01	0.0000E+00	-0.7673E+01	0.5417E+00	0.1329E+00	0.3762E+01	0.3279E+02
230	0.1725E+01	0.0000E+00	-0.7577E+01	0.5551E+00	0.1331E+00	0.3956E+01	0.3263E+02
240	0.1760E+01	0.0000E+00	-0.7481E+01	0.5686E+00	0.1332E+00	0.4154E+01	0.3249E+02
250	0.1793E+01	0.0000E+00	-0.7384E+01	0.5822E+00	0.1331E+00	0.4354E+01	0.3236E+02
260	0.1825E+01	0.0000E+00	-0.7287E+01	0.5959E+00	0.1331E+00	0.4558E+01	0.3223E+02
270	0.1855E+01	0.0000E+00	-0.7189E+01	0.6095E+00	0.1329E+00	0.4765E+01	0.3212E+02
280	0.1884E+01	0.0000E+00	-0.7091E+01	0.6232E+00	0.1327E+00	0.4975E+01	0.3201E+02
290	0.1912E+01	0.0000E+00	-0.6993E+01	0.6370E+00	0.1325E+00	0.5187E+01	0.3191E+02
300	0.1938E+01	0.0000E+00	-0.6894E+01	0.6507E+00	0.1322E+00	0.5402E+01	0.3182E+02
310	0.1964E+01	0.0000E+00	-0.6796E+01	0.6644E+00	0.1319E+00	0.5620E+01	0.3174E+02
320	0.1989E+01	0.0000E+00	-0.6698E+01	0.6782E+00	0.1316E+00	0.5840E+01	0.3165E+02
330	0.2012E+01	0.0000E+00	-0.6600E+01	0.6919E+00	0.1312E+00	0.6063E+01	0.3158E+02
340	0.2035E+01	0.0000E+00	-0.6501E+01	0.7056E+00	0.1309E+00	0.6288E+01	0.3151E+02
350	0.2057E+01	0.0000E+00	-0.6403E+01	0.7193E+00	0.1305E+00	0.6515E+01	0.3144E+02
360	0.2079E+01	0.0000E+00	-0.6305E+01	0.7330E+00	0.1301E+00	0.6744E+01	0.3138E+02
370	0.2099E+01	0.0000E+00	-0.6208E+01	0.7467E+00	0.1297E+00	0.6976E+01	0.3132E+02
380	0.2119E+01	0.0000E+00	-0.6110E+01	0.7603E+00	0.1292E+00	0.7209E+01	0.3126E+02
390	0.2138E+01	0.0000E+00	-0.6013E+01	0.7739E+00	0.1288E+00	0.7445E+01	0.3121E+02
400	0.2157E+01	0.0000E+00	-0.5916E+01	0.7875E+00	0.1284E+00	0.7682E+01	0.3116E+02
410	0.2175E+01	0.0000E+00	-0.5819E+01	0.8010E+00	0.1279E+00	0.7922E+01	0.3111E+02
420	0.2193E+01	0.0000E+00	-0.5722E+01	0.8146E+00	0.1275E+00	0.8163E+01	0.3107E+02
430	0.2210E+01	0.0000E+00	-0.5626E+01	0.8280E+00	0.1270E+00	0.8407E+01	0.3103E+02
440	0.2226E+01	0.0000E+00	-0.5530E+01	0.8415E+00	0.1266E+00	0.8652E+01	0.3099E+02
450	0.2242E+01	0.0000E+00	-0.5434E+01	0.8549E+00	0.1261E+00	0.8898E+01	0.3095E+02
460	0.2258E+01	0.0000E+00	-0.5338E+01	0.8683E+00	0.1257E+00	0.9147E+01	0.3091E+02
470	0.2273E+01	0.0000E+00	-0.5243E+01	0.8816E+00	0.1253E+00	0.9397E+01	0.3088E+02

480	0.2288E+01	0.0000E+00	-0.5148E+01	0.8949E+00	0.1248E+00	0.9649E+01	0.3084E+02
490	0.2303E+01	0.0000E+00	-0.5053E+01	0.9082E+00	0.1244E+00	0.9902E+01	0.3081E+02
500	0.2317E+01	0.0000E+00	-0.4959E+01	0.9214E+00	0.1239E+00	0.1016E+02	0.3078E+02
510	0.2330E+01	0.0000E+00	-0.4865E+01	0.9346E+00	0.1235E+00	0.1041E+02	0.3075E+02
520	0.2344E+01	0.0000E+00	-0.4771E+01	0.9478E+00	0.1231E+00	0.1067E+02	0.3072E+02
530	0.2357E+01	0.0000E+00	-0.4677E+01	0.9609E+00	0.1227E+00	0.1093E+02	0.3070E+02
540	0.2370E+01	0.0000E+00	-0.4584E+01	0.9739E+00	0.1222E+00	0.1119E+02	0.3067E+02
550	0.2382E+01	0.0000E+00	-0.4491E+01	0.9870E+00	0.1218E+00	0.1145E+02	0.3065E+02
560	0.2394E+01	0.0000E+00	-0.4398E+01	0.1000E+01	0.1214E+00	0.1172E+02	0.3062E+02
570	0.2406E+01	0.0000E+00	-0.4306E+01	0.1013E+01	0.1210E+00	0.1198E+02	0.3060E+02
580	0.2418E+01	0.0000E+00	-0.4214E+01	0.1026E+01	0.1206E+00	0.1225E+02	0.3058E+02
590	0.2429E+01	0.0000E+00	-0.4122E+01	0.1039E+01	0.1202E+00	0.1252E+02	0.3056E+02
600	0.2440E+01	0.0000E+00	-0.4030E+01	0.1052E+01	0.1198E+00	0.1279E+02	0.3054E+02
610	0.2451E+01	0.0000E+00	-0.3939E+01	0.1064E+01	0.1194E+00	0.1306E+02	0.3052E+02
620	0.2462E+01	0.0000E+00	-0.3848E+01	0.1077E+01	0.1190E+00	0.1333E+02	0.3050E+02
630	0.2473E+01	0.0000E+00	-0.3757E+01	0.1090E+01	0.1186E+00	0.1360E+02	0.3048E+02
640	0.2483E+01	0.0000E+00	-0.3666E+01	0.1103E+01	0.1183E+00	0.1388E+02	0.3046E+02
650	0.2493E+01	0.0000E+00	-0.3576E+01	0.1115E+01	0.1179E+00	0.1415E+02	0.3045E+02
660	0.2503E+01	0.0000E+00	-0.3486E+01	0.1128E+01	0.1175E+00	0.1443E+02	0.3043E+02
670	0.2513E+01	0.0000E+00	-0.3396E+01	0.1140E+01	0.1171E+00	0.1471E+02	0.3042E+02
680	0.2522E+01	0.0000E+00	-0.3307E+01	0.1153E+01	0.1168E+00	0.1499E+02	0.3040E+02
690	0.2531E+01	0.0000E+00	-0.3218E+01	0.1166E+01	0.1164E+00	0.1527E+02	0.3039E+02
700	0.2541E+01	0.0000E+00	-0.3129E+01	0.1178E+01	0.1161E+00	0.1555E+02	0.3037E+02
710	0.2550E+01	0.0000E+00	-0.3040E+01	0.1190E+01	0.1157E+00	0.1583E+02	0.3036E+02
720	0.2558E+01	0.0000E+00	-0.2952E+01	0.1203E+01	0.1154E+00	0.1612E+02	0.3034E+02
730	0.2567E+01	0.0000E+00	-0.2864E+01	0.1215E+01	0.1150E+00	0.1640E+02	0.3033E+02
740	0.2576E+01	0.0000E+00	-0.2776E+01	0.1228E+01	0.1147E+00	0.1669E+02	0.3032E+02
750	0.2584E+01	0.0000E+00	-0.2688E+01	0.1240E+01	0.1144E+00	0.1697E+02	0.3031E+02
760	0.2592E+01	0.0000E+00	-0.2601E+01	0.1252E+01	0.1140E+00	0.1726E+02	0.3030E+02
770	0.2600E+01	0.0000E+00	-0.2513E+01	0.1264E+01	0.1137E+00	0.1755E+02	0.3028E+02
780	0.2608E+01	0.0000E+00	-0.2426E+01	0.1277E+01	0.1134E+00	0.1784E+02	0.3027E+02
790	0.2616E+01	0.0000E+00	-0.2340E+01	0.1289E+01	0.1131E+00	0.1813E+02	0.3026E+02
800	0.2624E+01	0.0000E+00	-0.2253E+01	0.1301E+01	0.1128E+00	0.1843E+02	0.3025E+02
810	0.2632E+01	0.0000E+00	-0.2167E+01	0.1313E+01	0.1124E+00	0.1872E+02	0.3024E+02
820	0.2639E+01	0.0000E+00	-0.2081E+01	0.1325E+01	0.1121E+00	0.1901E+02	0.3023E+02
830	0.2646E+01	0.0000E+00	-0.1995E+01	0.1337E+01	0.1118E+00	0.1931E+02	0.3022E+02
840	0.2654E+01	0.0000E+00	-0.1909E+01	0.1349E+01	0.1115E+00	0.1960E+02	0.3021E+02
850	0.2661E+01	0.0000E+00	-0.1824E+01	0.1361E+01	0.1112E+00	0.1990E+02	0.3020E+02
860	0.2668E+01	0.0000E+00	-0.1739E+01	0.1373E+01	0.1110E+00	0.2020E+02	0.3019E+02
870	0.2675E+01	0.0000E+00	-0.1654E+01	0.1385E+01	0.1107E+00	0.2050E+02	0.3019E+02
880	0.2682E+01	0.0000E+00	-0.1569E+01	0.1397E+01	0.1104E+00	0.2080E+02	0.3018E+02
890	0.2688E+01	0.0000E+00	-0.1485E+01	0.1409E+01	0.1101E+00	0.2110E+02	0.3017E+02
900	0.2695E+01	0.0000E+00	-0.1400E+01	0.1421E+01	0.1098E+00	0.2140E+02	0.3016E+02
910	0.2702E+01	0.0000E+00	-0.1316E+01	0.1433E+01	0.1095E+00	0.2170E+02	0.3015E+02
920	0.2708E+01	0.0000E+00	-0.1232E+01	0.1444E+01	0.1093E+00	0.2201E+02	0.3015E+02
930	0.2715E+01	0.0000E+00	-0.1149E+01	0.1456E+01	0.1090E+00	0.2231E+02	0.3014E+02
940	0.2721E+01	0.0000E+00	-0.1065E+01	0.1468E+01	0.1087E+00	0.2262E+02	0.3013E+02
950	0.2727E+01	0.0000E+00	-0.9819E+00	0.1480E+01	0.1085E+00	0.2293E+02	0.3012E+02
960	0.2733E+01	0.0000E+00	-0.8988E+00	0.1491E+01	0.1082E+00	0.2323E+02	0.3012E+02
970	0.2739E+01	0.0000E+00	-0.8159E+00	0.1503E+01	0.1079E+00	0.2354E+02	0.3011E+02
980	0.2745E+01	0.0000E+00	-0.7332E+00	0.1515E+01	0.1077E+00	0.2385E+02	0.3010E+02
990	0.2751E+01	0.0000E+00	-0.6507E+00	0.1526E+01	0.1074E+00	0.2416E+02	0.3010E+02
1000	0.2757E+01	0.0000E+00	-0.5683E+00	0.1538E+01	0.1072E+00	0.2447E+02	0.3009E+02

1010	0.2763E+01	0.0000E+00	-0.4862E+00	0.1549E+01	0.1069E+00	0.2478E+02	0.3008E+02
1020	0.2768E+01	0.0000E+00	-0.4042E+00	0.1561E+01	0.1067E+00	0.2509E+02	0.3008E+02
1030	0.2774E+01	0.0000E+00	-0.3225E+00	0.1572E+01	0.1064E+00	0.2541E+02	0.3007E+02
1040	0.2779E+01	0.0000E+00	-0.2409E+00	0.1584E+01	0.1062E+00	0.2572E+02	0.3007E+02
1050	0.2785E+01	0.0000E+00	-0.1594E+00	0.1595E+01	0.1060E+00	0.2604E+02	0.3006E+02
1057	0.2789E+01	0.0000E+00	-0.1026E+00	0.1603E+01	0.1058E+00	0.2626E+02	0.3006E+02

FSRU Outfall 002 – Case 4 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6300E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1360E-01	0.2967E-03	-0.6313E+01	0.2089E+00	0.2479E+00	0.1040E+01	0.4114E+02
10	0.1075E+00	0.1076E-01	-0.6399E+01	0.2768E+00	0.1817E+00	0.1340E+01	0.3855E+02
20	0.1991E+00	0.3788E-01	-0.6469E+01	0.3663E+00	0.1348E+00	0.1742E+01	0.3649E+02
30	0.2682E+00	0.7722E-01	-0.6510E+01	0.4876E+00	0.1045E+00	0.2395E+01	0.3461E+02
40	0.3168E+00	0.1277E+00	-0.6532E+01	0.6183E+00	0.9127E-01	0.3365E+01	0.3317E+02
50	0.3544E+00	0.1841E+00	-0.6542E+01	0.6891E+00	0.8847E-01	0.4052E+01	0.3256E+02
60	0.3871E+00	0.2433E+00	-0.6547E+01	0.7307E+00	0.8789E-01	0.4528E+01	0.3225E+02
70	0.4170E+00	0.3039E+00	-0.6546E+01	0.7585E+00	0.8805E-01	0.4889E+01	0.3205E+02
80	0.4450E+00	0.3656E+00	-0.6541E+01	0.7784E+00	0.8858E-01	0.5179E+01	0.3192E+02
90	0.4716E+00	0.4281E+00	-0.6532E+01	0.7933E+00	0.8935E-01	0.5426E+01	0.3181E+02
100	0.4971E+00	0.4911E+00	-0.6520E+01	0.8050E+00	0.9029E-01	0.5646E+01	0.3173E+02
110	0.5217E+00	0.5547E+00	-0.6505E+01	0.8147E+00	0.9136E-01	0.5852E+01	0.3165E+02
120	0.5454E+00	0.6187E+00	-0.6486E+01	0.8234E+00	0.9253E-01	0.6054E+01	0.3158E+02
130	0.5683E+00	0.6832E+00	-0.6465E+01	0.8317E+00	0.9377E-01	0.6259E+01	0.3152E+02
140	0.5905E+00	0.7480E+00	-0.6440E+01	0.8402E+00	0.9505E-01	0.6474E+01	0.3145E+02
150	0.6119E+00	0.8133E+00	-0.6414E+01	0.8492E+00	0.9632E-01	0.6703E+01	0.3139E+02
160	0.6326E+00	0.8790E+00	-0.6385E+01	0.8590E+00	0.9757E-01	0.6948E+01	0.3133E+02
170	0.6526E+00	0.9451E+00	-0.6354E+01	0.8699E+00	0.9876E-01	0.7212E+01	0.3126E+02
180	0.6718E+00	0.1012E+01	-0.6322E+01	0.8818E+00	0.9989E-01	0.7495E+01	0.3120E+02
190	0.6902E+00	0.1078E+01	-0.6288E+01	0.8947E+00	0.1009E+00	0.7798E+01	0.3114E+02
200	0.7080E+00	0.1146E+01	-0.6252E+01	0.9087E+00	0.1019E+00	0.8120E+01	0.3108E+02
210	0.7250E+00	0.1213E+01	-0.6216E+01	0.9236E+00	0.1028E+00	0.8461E+01	0.3102E+02
220	0.7413E+00	0.1281E+01	-0.6178E+01	0.9394E+00	0.1036E+00	0.8821E+01	0.3096E+02
230	0.7570E+00	0.1350E+01	-0.6140E+01	0.9560E+00	0.1043E+00	0.9197E+01	0.3090E+02
240	0.7720E+00	0.1419E+01	-0.6101E+01	0.9733E+00	0.1049E+00	0.9591E+01	0.3085E+02
250	0.7864E+00	0.1488E+01	-0.6061E+01	0.9913E+00	0.1054E+00	0.1000E+02	0.3080E+02
260	0.8003E+00	0.1557E+01	-0.6021E+01	0.1010E+01	0.1059E+00	0.1042E+02	0.3075E+02
270	0.8135E+00	0.1627E+01	-0.5981E+01	0.1029E+01	0.1063E+00	0.1086E+02	0.3070E+02
280	0.8263E+00	0.1697E+01	-0.5940E+01	0.1048E+01	0.1067E+00	0.1132E+02	0.3066E+02
290	0.8385E+00	0.1767E+01	-0.5899E+01	0.1068E+01	0.1070E+00	0.1178E+02	0.3062E+02
300	0.8502E+00	0.1838E+01	-0.5858E+01	0.1088E+01	0.1073E+00	0.1226E+02	0.3058E+02
310	0.8615E+00	0.1908E+01	-0.5817E+01	0.1108E+01	0.1076E+00	0.1275E+02	0.3054E+02
320	0.8724E+00	0.1979E+01	-0.5776E+01	0.1129E+01	0.1078E+00	0.1325E+02	0.3051E+02
330	0.8828E+00	0.2051E+01	-0.5735E+01	0.1149E+01	0.1079E+00	0.1376E+02	0.3047E+02
340	0.8929E+00	0.2122E+01	-0.5693E+01	0.1170E+01	0.1081E+00	0.1429E+02	0.3044E+02
350	0.9026E+00	0.2194E+01	-0.5652E+01	0.1191E+01	0.1082E+00	0.1482E+02	0.3041E+02
360	0.9120E+00	0.2266E+01	-0.5611E+01	0.1212E+01	0.1083E+00	0.1536E+02	0.3038E+02
370	0.9210E+00	0.2338E+01	-0.5570E+01	0.1233E+01	0.1084E+00	0.1592E+02	0.3035E+02
380	0.9297E+00	0.2410E+01	-0.5529E+01	0.1255E+01	0.1085E+00	0.1648E+02	0.3033E+02
390	0.9381E+00	0.2482E+01	-0.5489E+01	0.1276E+01	0.1085E+00	0.1705E+02	0.3030E+02
400	0.9463E+00	0.2555E+01	-0.5448E+01	0.1297E+01	0.1086E+00	0.1763E+02	0.3028E+02
410	0.9541E+00	0.2627E+01	-0.5407E+01	0.1318E+01	0.1086E+00	0.1821E+02	0.3026E+02
420	0.9618E+00	0.2700E+01	-0.5367E+01	0.1339E+01	0.1086E+00	0.1881E+02	0.3024E+02
430	0.9692E+00	0.2773E+01	-0.5327E+01	0.1360E+01	0.1086E+00	0.1941E+02	0.3022E+02
440	0.9763E+00	0.2846E+01	-0.5287E+01	0.1382E+01	0.1086E+00	0.2002E+02	0.3020E+02
450	0.9833E+00	0.2919E+01	-0.5247E+01	0.1403E+01	0.1086E+00	0.2064E+02	0.3018E+02
460	0.9900E+00	0.2992E+01	-0.5207E+01	0.1424E+01	0.1086E+00	0.2126E+02	0.3016E+02
470	0.9966E+00	0.3066E+01	-0.5168E+01	0.1445E+01	0.1086E+00	0.2190E+02	0.3015E+02

480	0.1003E+01	0.3139E+01	-0.5129E+01	0.1466E+01	0.1086E+00	0.2254E+02	0.3013E+02
490	0.1009E+01	0.3213E+01	-0.5090E+01	0.1487E+01	0.1086E+00	0.2318E+02	0.3012E+02
500	0.1015E+01	0.3286E+01	-0.5051E+01	0.1508E+01	0.1086E+00	0.2384E+02	0.3010E+02
510	0.1021E+01	0.3360E+01	-0.5012E+01	0.1529E+01	0.1085E+00	0.2450E+02	0.3009E+02
520	0.1027E+01	0.3434E+01	-0.4973E+01	0.1550E+01	0.1085E+00	0.2517E+02	0.3008E+02
530	0.1032E+01	0.3508E+01	-0.4935E+01	0.1571E+01	0.1085E+00	0.2584E+02	0.3006E+02
540	0.1038E+01	0.3582E+01	-0.4897E+01	0.1592E+01	0.1084E+00	0.2652E+02	0.3005E+02
550	0.1043E+01	0.3656E+01	-0.4859E+01	0.1612E+01	0.1084E+00	0.2721E+02	0.3004E+02
560	0.1048E+01	0.3730E+01	-0.4821E+01	0.1633E+01	0.1084E+00	0.2790E+02	0.3003E+02
570	0.1053E+01	0.3804E+01	-0.4784E+01	0.1654E+01	0.1083E+00	0.2860E+02	0.3002E+02
580	0.1058E+01	0.3878E+01	-0.4746E+01	0.1674E+01	0.1083E+00	0.2930E+02	0.3001E+02
590	0.1063E+01	0.3953E+01	-0.4709E+01	0.1695E+01	0.1082E+00	0.3001E+02	0.3000E+02
600	0.1067E+01	0.4027E+01	-0.4672E+01	0.1715E+01	0.1082E+00	0.3073E+02	0.2999E+02
610	0.1072E+01	0.4102E+01	-0.4635E+01	0.1736E+01	0.1081E+00	0.3145E+02	0.2998E+02
620	0.1076E+01	0.4176E+01	-0.4598E+01	0.1756E+01	0.1081E+00	0.3218E+02	0.2997E+02
630	0.1081E+01	0.4251E+01	-0.4562E+01	0.1776E+01	0.1080E+00	0.3291E+02	0.2996E+02
640	0.1085E+01	0.4325E+01	-0.4526E+01	0.1796E+01	0.1080E+00	0.3365E+02	0.2996E+02
650	0.1089E+01	0.4400E+01	-0.4489E+01	0.1817E+01	0.1080E+00	0.3440E+02	0.2995E+02
660	0.1093E+01	0.4475E+01	-0.4453E+01	0.1837E+01	0.1079E+00	0.3514E+02	0.2994E+02
670	0.1097E+01	0.4549E+01	-0.4418E+01	0.1857E+01	0.1079E+00	0.3590E+02	0.2993E+02
680	0.1101E+01	0.4624E+01	-0.4382E+01	0.1877E+01	0.1078E+00	0.3666E+02	0.2993E+02
690	0.1105E+01	0.4699E+01	-0.4347E+01	0.1896E+01	0.1078E+00	0.3742E+02	0.2992E+02
700	0.1108E+01	0.4774E+01	-0.4311E+01	0.1916E+01	0.1077E+00	0.3819E+02	0.2991E+02
710	0.1112E+01	0.4849E+01	-0.4276E+01	0.1936E+01	0.1077E+00	0.3897E+02	0.2991E+02
720	0.1116E+01	0.4924E+01	-0.4241E+01	0.1956E+01	0.1076E+00	0.3974E+02	0.2990E+02
730	0.1119E+01	0.4999E+01	-0.4206E+01	0.1975E+01	0.1076E+00	0.4053E+02	0.2990E+02
740	0.1123E+01	0.5074E+01	-0.4172E+01	0.1995E+01	0.1075E+00	0.4132E+02	0.2989E+02
750	0.1126E+01	0.5149E+01	-0.4137E+01	0.2014E+01	0.1075E+00	0.4211E+02	0.2988E+02
760	0.1129E+01	0.5224E+01	-0.4103E+01	0.2034E+01	0.1074E+00	0.4291E+02	0.2988E+02
770	0.1133E+01	0.5299E+01	-0.4069E+01	0.2053E+01	0.1074E+00	0.4371E+02	0.2987E+02
780	0.1136E+01	0.5374E+01	-0.4035E+01	0.2072E+01	0.1074E+00	0.4452E+02	0.2987E+02
790	0.1139E+01	0.5450E+01	-0.4001E+01	0.2092E+01	0.1073E+00	0.4533E+02	0.2986E+02
800	0.1142E+01	0.5525E+01	-0.3967E+01	0.2111E+01	0.1073E+00	0.4614E+02	0.2986E+02
810	0.1145E+01	0.5600E+01	-0.3933E+01	0.2130E+01	0.1072E+00	0.4696E+02	0.2986E+02
820	0.1148E+01	0.5676E+01	-0.3900E+01	0.2149E+01	0.1072E+00	0.4779E+02	0.2985E+02
830	0.1151E+01	0.5751E+01	-0.3866E+01	0.2168E+01	0.1071E+00	0.4862E+02	0.2985E+02
840	0.1154E+01	0.5826E+01	-0.3833E+01	0.2187E+01	0.1071E+00	0.4945E+02	0.2984E+02
850	0.1157E+01	0.5902E+01	-0.3800E+01	0.2206E+01	0.1071E+00	0.5029E+02	0.2984E+02
860	0.1160E+01	0.5977E+01	-0.3767E+01	0.2224E+01	0.1070E+00	0.5113E+02	0.2983E+02
870	0.1162E+01	0.6052E+01	-0.3734E+01	0.2243E+01	0.1070E+00	0.5197E+02	0.2983E+02
880	0.1165E+01	0.6128E+01	-0.3702E+01	0.2262E+01	0.1069E+00	0.5282E+02	0.2983E+02
890	0.1168E+01	0.6203E+01	-0.3669E+01	0.2281E+01	0.1069E+00	0.5368E+02	0.2982E+02
900	0.1170E+01	0.6279E+01	-0.3637E+01	0.2299E+01	0.1069E+00	0.5453E+02	0.2982E+02
910	0.1173E+01	0.6354E+01	-0.3605E+01	0.2318E+01	0.1068E+00	0.5539E+02	0.2982E+02
920	0.1175E+01	0.6430E+01	-0.3572E+01	0.2336E+01	0.1068E+00	0.5626E+02	0.2981E+02
930	0.1178E+01	0.6506E+01	-0.3540E+01	0.2354E+01	0.1067E+00	0.5713E+02	0.2981E+02
940	0.1180E+01	0.6581E+01	-0.3508E+01	0.2373E+01	0.1067E+00	0.5800E+02	0.2981E+02
950	0.1183E+01	0.6657E+01	-0.3477E+01	0.2391E+01	0.1067E+00	0.5888E+02	0.2980E+02
960	0.1185E+01	0.6732E+01	-0.3445E+01	0.2409E+01	0.1066E+00	0.5976E+02	0.2980E+02
970	0.1187E+01	0.6808E+01	-0.3413E+01	0.2428E+01	0.1066E+00	0.6064E+02	0.2980E+02
980	0.1190E+01	0.6884E+01	-0.3382E+01	0.2446E+01	0.1065E+00	0.6153E+02	0.2980E+02
990	0.1192E+01	0.6959E+01	-0.3351E+01	0.2464E+01	0.1065E+00	0.6242E+02	0.2979E+02
1000	0.1194E+01	0.7035E+01	-0.3319E+01	0.2482E+01	0.1065E+00	0.6332E+02	0.2979E+02

1010	0.1196E+01	0.7111E+01	-0.3288E+01	0.2500E+01	0.1064E+00	0.6422E+02	0.2979E+02
1020	0.1199E+01	0.7186E+01	-0.3257E+01	0.2518E+01	0.1064E+00	0.6512E+02	0.2978E+02
1030	0.1201E+01	0.7262E+01	-0.3226E+01	0.2535E+01	0.1064E+00	0.6603E+02	0.2978E+02
1040	0.1203E+01	0.7338E+01	-0.3196E+01	0.2553E+01	0.1063E+00	0.6694E+02	0.2978E+02
1050	0.1205E+01	0.7414E+01	-0.3165E+01	0.2571E+01	0.1063E+00	0.6785E+02	0.2978E+02
1060	0.1207E+01	0.7490E+01	-0.3134E+01	0.2589E+01	0.1063E+00	0.6877E+02	0.2977E+02
1070	0.1209E+01	0.7565E+01	-0.3104E+01	0.2606E+01	0.1062E+00	0.6969E+02	0.2977E+02
1080	0.1211E+01	0.7641E+01	-0.3073E+01	0.2624E+01	0.1062E+00	0.7061E+02	0.2977E+02
1090	0.1213E+01	0.7717E+01	-0.3043E+01	0.2642E+01	0.1062E+00	0.7154E+02	0.2977E+02
1100	0.1215E+01	0.7793E+01	-0.3013E+01	0.2659E+01	0.1061E+00	0.7247E+02	0.2977E+02
1110	0.1217E+01	0.7869E+01	-0.2983E+01	0.2677E+01	0.1061E+00	0.7340E+02	0.2976E+02
1120	0.1219E+01	0.7945E+01	-0.2953E+01	0.2694E+01	0.1061E+00	0.7434E+02	0.2976E+02
1130	0.1221E+01	0.8021E+01	-0.2923E+01	0.2711E+01	0.1060E+00	0.7528E+02	0.2976E+02
1140	0.1223E+01	0.8096E+01	-0.2893E+01	0.2729E+01	0.1060E+00	0.7622E+02	0.2976E+02
1150	0.1225E+01	0.8172E+01	-0.2864E+01	0.2746E+01	0.1060E+00	0.7717E+02	0.2976E+02
1160	0.1226E+01	0.8248E+01	-0.2834E+01	0.2763E+01	0.1060E+00	0.7812E+02	0.2975E+02
1170	0.1228E+01	0.8324E+01	-0.2805E+01	0.2781E+01	0.1059E+00	0.7907E+02	0.2975E+02
1180	0.1230E+01	0.8400E+01	-0.2775E+01	0.2798E+01	0.1059E+00	0.8003E+02	0.2975E+02
1190	0.1232E+01	0.8476E+01	-0.2746E+01	0.2815E+01	0.1059E+00	0.8099E+02	0.2975E+02
1200	0.1233E+01	0.8552E+01	-0.2717E+01	0.2832E+01	0.1058E+00	0.8195E+02	0.2975E+02
1210	0.1235E+01	0.8628E+01	-0.2687E+01	0.2849E+01	0.1058E+00	0.8292E+02	0.2974E+02
1216	0.1236E+01	0.8674E+01	-0.2670E+01	0.2859E+01	0.1058E+00	0.8347E+02	0.2974E+02

FSRU Outfall 002 – Case 5 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7350E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1360E-01	0.2967E-03	-0.7363E+01	0.2089E+00	0.2479E+00	0.1040E+01	0.4114E+02
10	0.1075E+00	0.1076E-01	-0.7449E+01	0.2768E+00	0.1817E+00	0.1340E+01	0.3855E+02
20	0.1991E+00	0.3788E-01	-0.7519E+01	0.3663E+00	0.1348E+00	0.1742E+01	0.3649E+02
30	0.2682E+00	0.7722E-01	-0.7560E+01	0.4876E+00	0.1045E+00	0.2395E+01	0.3461E+02
40	0.3168E+00	0.1277E+00	-0.7582E+01	0.6183E+00	0.9127E-01	0.3365E+01	0.3317E+02
50	0.3544E+00	0.1841E+00	-0.7592E+01	0.6891E+00	0.8847E-01	0.4052E+01	0.3256E+02
60	0.3871E+00	0.2433E+00	-0.7597E+01	0.7307E+00	0.8789E-01	0.4528E+01	0.3225E+02
70	0.4170E+00	0.3039E+00	-0.7596E+01	0.7585E+00	0.8805E-01	0.4889E+01	0.3205E+02
80	0.4450E+00	0.3656E+00	-0.7591E+01	0.7784E+00	0.8858E-01	0.5179E+01	0.3192E+02
90	0.4716E+00	0.4281E+00	-0.7582E+01	0.7933E+00	0.8935E-01	0.5426E+01	0.3181E+02
100	0.4971E+00	0.4911E+00	-0.7570E+01	0.8050E+00	0.9029E-01	0.5646E+01	0.3173E+02
110	0.5217E+00	0.5547E+00	-0.7555E+01	0.8147E+00	0.9136E-01	0.5852E+01	0.3165E+02
120	0.5454E+00	0.6187E+00	-0.7536E+01	0.8234E+00	0.9253E-01	0.6054E+01	0.3158E+02
130	0.5683E+00	0.6832E+00	-0.7515E+01	0.8317E+00	0.9377E-01	0.6259E+01	0.3152E+02
140	0.5905E+00	0.7480E+00	-0.7490E+01	0.8402E+00	0.9505E-01	0.6474E+01	0.3145E+02
150	0.6119E+00	0.8133E+00	-0.7464E+01	0.8492E+00	0.9632E-01	0.6703E+01	0.3139E+02
160	0.6326E+00	0.8790E+00	-0.7435E+01	0.8590E+00	0.9757E-01	0.6948E+01	0.3133E+02
170	0.6526E+00	0.9451E+00	-0.7404E+01	0.8699E+00	0.9876E-01	0.7212E+01	0.3126E+02
180	0.6718E+00	0.1012E+01	-0.7372E+01	0.8818E+00	0.9989E-01	0.7495E+01	0.3120E+02
190	0.6902E+00	0.1078E+01	-0.7338E+01	0.8947E+00	0.1009E+00	0.7798E+01	0.3114E+02
200	0.7080E+00	0.1146E+01	-0.7302E+01	0.9087E+00	0.1019E+00	0.8120E+01	0.3108E+02
210	0.7250E+00	0.1213E+01	-0.7266E+01	0.9236E+00	0.1028E+00	0.8461E+01	0.3102E+02
220	0.7413E+00	0.1281E+01	-0.7228E+01	0.9394E+00	0.1036E+00	0.8821E+01	0.3096E+02
230	0.7570E+00	0.1350E+01	-0.7190E+01	0.9560E+00	0.1043E+00	0.9197E+01	0.3090E+02
240	0.7720E+00	0.1419E+01	-0.7151E+01	0.9733E+00	0.1049E+00	0.9591E+01	0.3085E+02
250	0.7864E+00	0.1488E+01	-0.7111E+01	0.9913E+00	0.1054E+00	0.1000E+02	0.3080E+02
260	0.8003E+00	0.1557E+01	-0.7071E+01	0.1010E+01	0.1059E+00	0.1042E+02	0.3075E+02
270	0.8135E+00	0.1627E+01	-0.7031E+01	0.1029E+01	0.1063E+00	0.1086E+02	0.3070E+02
280	0.8263E+00	0.1697E+01	-0.6990E+01	0.1048E+01	0.1067E+00	0.1132E+02	0.3066E+02
290	0.8385E+00	0.1767E+01	-0.6949E+01	0.1068E+01	0.1070E+00	0.1178E+02	0.3062E+02
300	0.8502E+00	0.1838E+01	-0.6908E+01	0.1088E+01	0.1073E+00	0.1226E+02	0.3058E+02
310	0.8615E+00	0.1908E+01	-0.6867E+01	0.1108E+01	0.1076E+00	0.1275E+02	0.3054E+02
320	0.8724E+00	0.1979E+01	-0.6826E+01	0.1129E+01	0.1078E+00	0.1325E+02	0.3051E+02
330	0.8828E+00	0.2051E+01	-0.6785E+01	0.1149E+01	0.1079E+00	0.1376E+02	0.3047E+02
340	0.8929E+00	0.2122E+01	-0.6743E+01	0.1170E+01	0.1081E+00	0.1429E+02	0.3044E+02
350	0.9026E+00	0.2194E+01	-0.6702E+01	0.1191E+01	0.1082E+00	0.1482E+02	0.3041E+02
360	0.9120E+00	0.2266E+01	-0.6661E+01	0.1212E+01	0.1083E+00	0.1536E+02	0.3038E+02
370	0.9210E+00	0.2338E+01	-0.6620E+01	0.1233E+01	0.1084E+00	0.1592E+02	0.3035E+02
380	0.9297E+00	0.2410E+01	-0.6579E+01	0.1255E+01	0.1085E+00	0.1648E+02	0.3033E+02
390	0.9381E+00	0.2482E+01	-0.6539E+01	0.1276E+01	0.1085E+00	0.1705E+02	0.3030E+02
400	0.9463E+00	0.2555E+01	-0.6498E+01	0.1297E+01	0.1086E+00	0.1763E+02	0.3028E+02
410	0.9541E+00	0.2627E+01	-0.6457E+01	0.1318E+01	0.1086E+00	0.1821E+02	0.3026E+02
420	0.9618E+00	0.2700E+01	-0.6417E+01	0.1339E+01	0.1086E+00	0.1881E+02	0.3024E+02
430	0.9692E+00	0.2773E+01	-0.6377E+01	0.1360E+01	0.1086E+00	0.1941E+02	0.3022E+02
440	0.9763E+00	0.2846E+01	-0.6337E+01	0.1382E+01	0.1086E+00	0.2002E+02	0.3020E+02
450	0.9833E+00	0.2919E+01	-0.6297E+01	0.1403E+01	0.1086E+00	0.2064E+02	0.3018E+02
460	0.9900E+00	0.2992E+01	-0.6257E+01	0.1424E+01	0.1086E+00	0.2126E+02	0.3016E+02
470	0.9966E+00	0.3066E+01	-0.6218E+01	0.1445E+01	0.1086E+00	0.2190E+02	0.3015E+02

480	0.1003E+01	0.3139E+01	-0.6179E+01	0.1466E+01	0.1086E+00	0.2254E+02	0.3013E+02
490	0.1009E+01	0.3213E+01	-0.6140E+01	0.1487E+01	0.1086E+00	0.2318E+02	0.3012E+02
500	0.1015E+01	0.3286E+01	-0.6101E+01	0.1508E+01	0.1086E+00	0.2384E+02	0.3010E+02
510	0.1021E+01	0.3360E+01	-0.6062E+01	0.1529E+01	0.1085E+00	0.2450E+02	0.3009E+02
520	0.1027E+01	0.3434E+01	-0.6023E+01	0.1550E+01	0.1085E+00	0.2517E+02	0.3008E+02
530	0.1032E+01	0.3508E+01	-0.5985E+01	0.1571E+01	0.1085E+00	0.2584E+02	0.3006E+02
540	0.1038E+01	0.3582E+01	-0.5947E+01	0.1592E+01	0.1084E+00	0.2652E+02	0.3005E+02
550	0.1043E+01	0.3656E+01	-0.5909E+01	0.1612E+01	0.1084E+00	0.2721E+02	0.3004E+02
560	0.1048E+01	0.3730E+01	-0.5871E+01	0.1633E+01	0.1084E+00	0.2790E+02	0.3003E+02
570	0.1053E+01	0.3804E+01	-0.5834E+01	0.1654E+01	0.1083E+00	0.2860E+02	0.3002E+02
580	0.1058E+01	0.3878E+01	-0.5796E+01	0.1674E+01	0.1083E+00	0.2930E+02	0.3001E+02
590	0.1063E+01	0.3953E+01	-0.5759E+01	0.1695E+01	0.1082E+00	0.3001E+02	0.3000E+02
600	0.1067E+01	0.4027E+01	-0.5722E+01	0.1715E+01	0.1082E+00	0.3073E+02	0.2999E+02
610	0.1072E+01	0.4102E+01	-0.5685E+01	0.1736E+01	0.1081E+00	0.3145E+02	0.2998E+02
620	0.1076E+01	0.4176E+01	-0.5648E+01	0.1756E+01	0.1081E+00	0.3218E+02	0.2997E+02
630	0.1081E+01	0.4251E+01	-0.5612E+01	0.1776E+01	0.1080E+00	0.3291E+02	0.2996E+02
640	0.1085E+01	0.4325E+01	-0.5576E+01	0.1796E+01	0.1080E+00	0.3365E+02	0.2996E+02
650	0.1089E+01	0.4400E+01	-0.5539E+01	0.1817E+01	0.1080E+00	0.3440E+02	0.2995E+02
660	0.1093E+01	0.4475E+01	-0.5503E+01	0.1837E+01	0.1079E+00	0.3514E+02	0.2994E+02
670	0.1097E+01	0.4549E+01	-0.5468E+01	0.1857E+01	0.1079E+00	0.3590E+02	0.2993E+02
680	0.1101E+01	0.4624E+01	-0.5432E+01	0.1877E+01	0.1078E+00	0.3666E+02	0.2993E+02
690	0.1105E+01	0.4699E+01	-0.5397E+01	0.1896E+01	0.1078E+00	0.3742E+02	0.2992E+02
700	0.1108E+01	0.4774E+01	-0.5361E+01	0.1916E+01	0.1077E+00	0.3819E+02	0.2991E+02
710	0.1112E+01	0.4849E+01	-0.5326E+01	0.1936E+01	0.1077E+00	0.3897E+02	0.2991E+02
720	0.1116E+01	0.4924E+01	-0.5291E+01	0.1956E+01	0.1076E+00	0.3974E+02	0.2990E+02
730	0.1119E+01	0.4999E+01	-0.5256E+01	0.1975E+01	0.1076E+00	0.4053E+02	0.2990E+02
740	0.1123E+01	0.5074E+01	-0.5222E+01	0.1995E+01	0.1075E+00	0.4132E+02	0.2989E+02
750	0.1126E+01	0.5149E+01	-0.5187E+01	0.2014E+01	0.1075E+00	0.4211E+02	0.2988E+02
760	0.1129E+01	0.5224E+01	-0.5153E+01	0.2034E+01	0.1074E+00	0.4291E+02	0.2988E+02
770	0.1133E+01	0.5299E+01	-0.5119E+01	0.2053E+01	0.1074E+00	0.4371E+02	0.2987E+02
780	0.1136E+01	0.5374E+01	-0.5085E+01	0.2072E+01	0.1074E+00	0.4452E+02	0.2987E+02
790	0.1139E+01	0.5450E+01	-0.5051E+01	0.2092E+01	0.1073E+00	0.4533E+02	0.2986E+02
800	0.1142E+01	0.5525E+01	-0.5017E+01	0.2111E+01	0.1073E+00	0.4614E+02	0.2986E+02
810	0.1145E+01	0.5600E+01	-0.4983E+01	0.2130E+01	0.1072E+00	0.4696E+02	0.2986E+02
820	0.1148E+01	0.5676E+01	-0.4950E+01	0.2149E+01	0.1072E+00	0.4779E+02	0.2985E+02
830	0.1151E+01	0.5751E+01	-0.4916E+01	0.2168E+01	0.1071E+00	0.4862E+02	0.2985E+02
840	0.1154E+01	0.5826E+01	-0.4883E+01	0.2187E+01	0.1071E+00	0.4945E+02	0.2984E+02
850	0.1157E+01	0.5902E+01	-0.4850E+01	0.2206E+01	0.1071E+00	0.5029E+02	0.2984E+02
860	0.1160E+01	0.5977E+01	-0.4817E+01	0.2224E+01	0.1070E+00	0.5113E+02	0.2983E+02
870	0.1162E+01	0.6052E+01	-0.4784E+01	0.2243E+01	0.1070E+00	0.5197E+02	0.2983E+02
880	0.1165E+01	0.6128E+01	-0.4752E+01	0.2262E+01	0.1069E+00	0.5282E+02	0.2983E+02
890	0.1168E+01	0.6203E+01	-0.4719E+01	0.2281E+01	0.1069E+00	0.5368E+02	0.2982E+02
900	0.1170E+01	0.6279E+01	-0.4687E+01	0.2299E+01	0.1069E+00	0.5453E+02	0.2982E+02
910	0.1173E+01	0.6354E+01	-0.4655E+01	0.2318E+01	0.1068E+00	0.5539E+02	0.2982E+02
920	0.1175E+01	0.6430E+01	-0.4622E+01	0.2336E+01	0.1068E+00	0.5626E+02	0.2981E+02
930	0.1178E+01	0.6506E+01	-0.4590E+01	0.2354E+01	0.1067E+00	0.5713E+02	0.2981E+02
940	0.1180E+01	0.6581E+01	-0.4558E+01	0.2373E+01	0.1067E+00	0.5800E+02	0.2981E+02
950	0.1183E+01	0.6657E+01	-0.4527E+01	0.2391E+01	0.1067E+00	0.5888E+02	0.2980E+02
960	0.1185E+01	0.6732E+01	-0.4495E+01	0.2409E+01	0.1066E+00	0.5976E+02	0.2980E+02
970	0.1187E+01	0.6808E+01	-0.4463E+01	0.2428E+01	0.1066E+00	0.6064E+02	0.2980E+02
980	0.1190E+01	0.6884E+01	-0.4432E+01	0.2446E+01	0.1065E+00	0.6153E+02	0.2980E+02
990	0.1192E+01	0.6959E+01	-0.4401E+01	0.2464E+01	0.1065E+00	0.6242E+02	0.2979E+02
1000	0.1194E+01	0.7035E+01	-0.4369E+01	0.2482E+01	0.1065E+00	0.6332E+02	0.2979E+02

1010	0.1196E+01	0.7111E+01	-0.4338E+01	0.2500E+01	0.1064E+00	0.6422E+02	0.2979E+02
1020	0.1199E+01	0.7186E+01	-0.4307E+01	0.2518E+01	0.1064E+00	0.6512E+02	0.2978E+02
1030	0.1201E+01	0.7262E+01	-0.4276E+01	0.2535E+01	0.1064E+00	0.6603E+02	0.2978E+02
1040	0.1203E+01	0.7338E+01	-0.4246E+01	0.2553E+01	0.1063E+00	0.6694E+02	0.2978E+02
1050	0.1205E+01	0.7414E+01	-0.4215E+01	0.2571E+01	0.1063E+00	0.6785E+02	0.2978E+02
1060	0.1207E+01	0.7490E+01	-0.4184E+01	0.2589E+01	0.1063E+00	0.6877E+02	0.2977E+02
1070	0.1209E+01	0.7565E+01	-0.4154E+01	0.2606E+01	0.1062E+00	0.6969E+02	0.2977E+02
1080	0.1211E+01	0.7641E+01	-0.4123E+01	0.2624E+01	0.1062E+00	0.7061E+02	0.2977E+02
1090	0.1213E+01	0.7717E+01	-0.4093E+01	0.2642E+01	0.1062E+00	0.7154E+02	0.2977E+02
1100	0.1215E+01	0.7793E+01	-0.4063E+01	0.2659E+01	0.1061E+00	0.7247E+02	0.2977E+02
1110	0.1217E+01	0.7869E+01	-0.4033E+01	0.2677E+01	0.1061E+00	0.7340E+02	0.2976E+02
1120	0.1219E+01	0.7945E+01	-0.4003E+01	0.2694E+01	0.1061E+00	0.7434E+02	0.2976E+02
1130	0.1221E+01	0.8021E+01	-0.3973E+01	0.2711E+01	0.1060E+00	0.7528E+02	0.2976E+02
1140	0.1223E+01	0.8096E+01	-0.3943E+01	0.2729E+01	0.1060E+00	0.7622E+02	0.2976E+02
1150	0.1225E+01	0.8172E+01	-0.3914E+01	0.2746E+01	0.1060E+00	0.7717E+02	0.2976E+02
1160	0.1226E+01	0.8248E+01	-0.3884E+01	0.2763E+01	0.1060E+00	0.7812E+02	0.2975E+02
1170	0.1228E+01	0.8324E+01	-0.3855E+01	0.2781E+01	0.1059E+00	0.7907E+02	0.2975E+02
1180	0.1230E+01	0.8400E+01	-0.3825E+01	0.2798E+01	0.1059E+00	0.8003E+02	0.2975E+02
1190	0.1232E+01	0.8476E+01	-0.3796E+01	0.2815E+01	0.1059E+00	0.8099E+02	0.2975E+02
1200	0.1233E+01	0.8552E+01	-0.3767E+01	0.2832E+01	0.1058E+00	0.8195E+02	0.2975E+02
1210	0.1235E+01	0.8628E+01	-0.3737E+01	0.2849E+01	0.1058E+00	0.8292E+02	0.2974E+02
1220	0.1237E+01	0.8704E+01	-0.3708E+01	0.2866E+01	0.1058E+00	0.8389E+02	0.2974E+02
1230	0.1239E+01	0.8780E+01	-0.3679E+01	0.2883E+01	0.1058E+00	0.8486E+02	0.2974E+02
1240	0.1240E+01	0.8856E+01	-0.3651E+01	0.2900E+01	0.1057E+00	0.8584E+02	0.2974E+02
1250	0.1242E+01	0.8932E+01	-0.3622E+01	0.2917E+01	0.1057E+00	0.8681E+02	0.2974E+02
1260	0.1243E+01	0.9008E+01	-0.3593E+01	0.2933E+01	0.1057E+00	0.8780E+02	0.2974E+02
1270	0.1245E+01	0.9084E+01	-0.3564E+01	0.2950E+01	0.1057E+00	0.8878E+02	0.2974E+02
1280	0.1247E+01	0.9160E+01	-0.3536E+01	0.2967E+01	0.1056E+00	0.8977E+02	0.2973E+02
1290	0.1248E+01	0.9236E+01	-0.3507E+01	0.2984E+01	0.1056E+00	0.9076E+02	0.2973E+02
1300	0.1250E+01	0.9313E+01	-0.3479E+01	0.3000E+01	0.1056E+00	0.9175E+02	0.2973E+02
1310	0.1251E+01	0.9389E+01	-0.3451E+01	0.3017E+01	0.1055E+00	0.9275E+02	0.2973E+02
1320	0.1253E+01	0.9465E+01	-0.3423E+01	0.3033E+01	0.1055E+00	0.9375E+02	0.2973E+02
1330	0.1254E+01	0.9541E+01	-0.3394E+01	0.3050E+01	0.1055E+00	0.9475E+02	0.2973E+02
1340	0.1256E+01	0.9617E+01	-0.3366E+01	0.3066E+01	0.1055E+00	0.9576E+02	0.2973E+02
1350	0.1257E+01	0.9693E+01	-0.3338E+01	0.3083E+01	0.1054E+00	0.9676E+02	0.2972E+02
1360	0.1259E+01	0.9769E+01	-0.3310E+01	0.3099E+01	0.1054E+00	0.9777E+02	0.2972E+02
1370	0.1260E+01	0.9845E+01	-0.3283E+01	0.3116E+01	0.1054E+00	0.9879E+02	0.2972E+02
1380	0.1262E+01	0.9921E+01	-0.3255E+01	0.3132E+01	0.1054E+00	0.9980E+02	0.2972E+02
1390	0.1263E+01	0.9998E+01	-0.3227E+01	0.3148E+01	0.1054E+00	0.1008E+03	0.2972E+02
1400	0.1264E+01	0.1007E+02	-0.3199E+01	0.3165E+01	0.1053E+00	0.1018E+03	0.2972E+02
1410	0.1266E+01	0.1015E+02	-0.3172E+01	0.3181E+01	0.1053E+00	0.1029E+03	0.2972E+02
1420	0.1267E+01	0.1023E+02	-0.3144E+01	0.3197E+01	0.1053E+00	0.1039E+03	0.2972E+02
1430	0.1268E+01	0.1030E+02	-0.3117E+01	0.3213E+01	0.1053E+00	0.1049E+03	0.2971E+02
1440	0.1270E+01	0.1038E+02	-0.3090E+01	0.3229E+01	0.1052E+00	0.1060E+03	0.2971E+02
1450	0.1271E+01	0.1045E+02	-0.3062E+01	0.3245E+01	0.1052E+00	0.1070E+03	0.2971E+02
1452	0.1271E+01	0.1047E+02	-0.3057E+01	0.3247E+01	0.1052E+00	0.1071E+03	0.2971E+02

FSRU Outfall 002 – Case 6 (Table 5)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.8400E+01	0.2000E+00	0.2600E+00	0.1000E+01	0.4160E+02
2	0.1360E-01	0.2967E-03	-0.8413E+01	0.2089E+00	0.2479E+00	0.1040E+01	0.4114E+02
10	0.1075E+00	0.1076E-01	-0.8499E+01	0.2768E+00	0.1817E+00	0.1340E+01	0.3855E+02
20	0.1991E+00	0.3788E-01	-0.8569E+01	0.3663E+00	0.1348E+00	0.1742E+01	0.3649E+02
30	0.2682E+00	0.7722E-01	-0.8610E+01	0.4876E+00	0.1045E+00	0.2395E+01	0.3461E+02
40	0.3168E+00	0.1277E+00	-0.8632E+01	0.6183E+00	0.9127E-01	0.3365E+01	0.3317E+02
50	0.3544E+00	0.1841E+00	-0.8642E+01	0.6891E+00	0.8847E-01	0.4052E+01	0.3256E+02
60	0.3871E+00	0.2433E+00	-0.8647E+01	0.7307E+00	0.8789E-01	0.4528E+01	0.3225E+02
70	0.4170E+00	0.3039E+00	-0.8646E+01	0.7585E+00	0.8805E-01	0.4889E+01	0.3205E+02
80	0.4450E+00	0.3656E+00	-0.8641E+01	0.7784E+00	0.8858E-01	0.5179E+01	0.3192E+02
90	0.4716E+00	0.4281E+00	-0.8632E+01	0.7933E+00	0.8935E-01	0.5426E+01	0.3181E+02
100	0.4971E+00	0.4911E+00	-0.8620E+01	0.8050E+00	0.9029E-01	0.5646E+01	0.3173E+02
110	0.5217E+00	0.5547E+00	-0.8605E+01	0.8147E+00	0.9136E-01	0.5852E+01	0.3165E+02
120	0.5454E+00	0.6187E+00	-0.8586E+01	0.8234E+00	0.9253E-01	0.6054E+01	0.3158E+02
130	0.5683E+00	0.6832E+00	-0.8565E+01	0.8317E+00	0.9377E-01	0.6259E+01	0.3152E+02
140	0.5905E+00	0.7480E+00	-0.8540E+01	0.8402E+00	0.9505E-01	0.6474E+01	0.3145E+02
150	0.6119E+00	0.8133E+00	-0.8514E+01	0.8492E+00	0.9632E-01	0.6703E+01	0.3139E+02
160	0.6326E+00	0.8790E+00	-0.8485E+01	0.8590E+00	0.9757E-01	0.6948E+01	0.3133E+02
170	0.6526E+00	0.9451E+00	-0.8454E+01	0.8699E+00	0.9876E-01	0.7212E+01	0.3126E+02
180	0.6718E+00	0.1012E+01	-0.8422E+01	0.8818E+00	0.9989E-01	0.7495E+01	0.3120E+02
190	0.6902E+00	0.1078E+01	-0.8388E+01	0.8947E+00	0.1009E+00	0.7798E+01	0.3114E+02
200	0.7080E+00	0.1146E+01	-0.8352E+01	0.9087E+00	0.1019E+00	0.8120E+01	0.3108E+02
210	0.7250E+00	0.1213E+01	-0.8316E+01	0.9236E+00	0.1028E+00	0.8461E+01	0.3102E+02
220	0.7413E+00	0.1281E+01	-0.8278E+01	0.9394E+00	0.1036E+00	0.8821E+01	0.3096E+02
230	0.7570E+00	0.1350E+01	-0.8240E+01	0.9560E+00	0.1043E+00	0.9197E+01	0.3090E+02
240	0.7720E+00	0.1419E+01	-0.8201E+01	0.9733E+00	0.1049E+00	0.9591E+01	0.3085E+02
250	0.7864E+00	0.1488E+01	-0.8161E+01	0.9913E+00	0.1054E+00	0.1000E+02	0.3080E+02
260	0.8003E+00	0.1557E+01	-0.8121E+01	0.1010E+01	0.1059E+00	0.1042E+02	0.3075E+02
270	0.8135E+00	0.1627E+01	-0.8081E+01	0.1029E+01	0.1063E+00	0.1086E+02	0.3070E+02
280	0.8263E+00	0.1697E+01	-0.8040E+01	0.1048E+01	0.1067E+00	0.1132E+02	0.3066E+02
290	0.8385E+00	0.1767E+01	-0.7999E+01	0.1068E+01	0.1070E+00	0.1178E+02	0.3062E+02
300	0.8502E+00	0.1838E+01	-0.7958E+01	0.1088E+01	0.1073E+00	0.1226E+02	0.3058E+02
310	0.8615E+00	0.1908E+01	-0.7917E+01	0.1108E+01	0.1076E+00	0.1275E+02	0.3054E+02
320	0.8724E+00	0.1979E+01	-0.7876E+01	0.1129E+01	0.1078E+00	0.1325E+02	0.3051E+02
330	0.8828E+00	0.2051E+01	-0.7835E+01	0.1149E+01	0.1079E+00	0.1376E+02	0.3047E+02
340	0.8929E+00	0.2122E+01	-0.7793E+01	0.1170E+01	0.1081E+00	0.1429E+02	0.3044E+02
350	0.9026E+00	0.2194E+01	-0.7752E+01	0.1191E+01	0.1082E+00	0.1482E+02	0.3041E+02
360	0.9120E+00	0.2266E+01	-0.7711E+01	0.1212E+01	0.1083E+00	0.1536E+02	0.3038E+02
370	0.9210E+00	0.2338E+01	-0.7670E+01	0.1233E+01	0.1084E+00	0.1592E+02	0.3035E+02
380	0.9297E+00	0.2410E+01	-0.7629E+01	0.1255E+01	0.1085E+00	0.1648E+02	0.3033E+02
390	0.9381E+00	0.2482E+01	-0.7589E+01	0.1276E+01	0.1085E+00	0.1705E+02	0.3030E+02
400	0.9463E+00	0.2555E+01	-0.7548E+01	0.1297E+01	0.1086E+00	0.1763E+02	0.3028E+02
410	0.9541E+00	0.2627E+01	-0.7507E+01	0.1318E+01	0.1086E+00	0.1821E+02	0.3026E+02
420	0.9618E+00	0.2700E+01	-0.7467E+01	0.1339E+01	0.1086E+00	0.1881E+02	0.3024E+02
430	0.9692E+00	0.2773E+01	-0.7427E+01	0.1360E+01	0.1086E+00	0.1941E+02	0.3022E+02
440	0.9763E+00	0.2846E+01	-0.7387E+01	0.1382E+01	0.1086E+00	0.2002E+02	0.3020E+02
450	0.9833E+00	0.2919E+01	-0.7347E+01	0.1403E+01	0.1086E+00	0.2064E+02	0.3018E+02
460	0.9900E+00	0.2992E+01	-0.7307E+01	0.1424E+01	0.1086E+00	0.2126E+02	0.3016E+02
470	0.9966E+00	0.3066E+01	-0.7268E+01	0.1445E+01	0.1086E+00	0.2190E+02	0.3015E+02

480	0.1003E+01	0.3139E+01	-0.7229E+01	0.1466E+01	0.1086E+00	0.2254E+02	0.3013E+02
490	0.1009E+01	0.3213E+01	-0.7190E+01	0.1487E+01	0.1086E+00	0.2318E+02	0.3012E+02
500	0.1015E+01	0.3286E+01	-0.7151E+01	0.1508E+01	0.1086E+00	0.2384E+02	0.3010E+02
510	0.1021E+01	0.3360E+01	-0.7112E+01	0.1529E+01	0.1085E+00	0.2450E+02	0.3009E+02
520	0.1027E+01	0.3434E+01	-0.7073E+01	0.1550E+01	0.1085E+00	0.2517E+02	0.3008E+02
530	0.1032E+01	0.3508E+01	-0.7035E+01	0.1571E+01	0.1085E+00	0.2584E+02	0.3006E+02
540	0.1038E+01	0.3582E+01	-0.6997E+01	0.1592E+01	0.1084E+00	0.2652E+02	0.3005E+02
550	0.1043E+01	0.3656E+01	-0.6959E+01	0.1612E+01	0.1084E+00	0.2721E+02	0.3004E+02
560	0.1048E+01	0.3730E+01	-0.6921E+01	0.1633E+01	0.1084E+00	0.2790E+02	0.3003E+02
570	0.1053E+01	0.3804E+01	-0.6884E+01	0.1654E+01	0.1083E+00	0.2860E+02	0.3002E+02
580	0.1058E+01	0.3878E+01	-0.6846E+01	0.1674E+01	0.1083E+00	0.2930E+02	0.3001E+02
590	0.1063E+01	0.3953E+01	-0.6809E+01	0.1695E+01	0.1082E+00	0.3001E+02	0.3000E+02
600	0.1067E+01	0.4027E+01	-0.6772E+01	0.1715E+01	0.1082E+00	0.3073E+02	0.2999E+02
610	0.1072E+01	0.4102E+01	-0.6735E+01	0.1736E+01	0.1081E+00	0.3145E+02	0.2998E+02
620	0.1076E+01	0.4176E+01	-0.6698E+01	0.1756E+01	0.1081E+00	0.3218E+02	0.2997E+02
630	0.1081E+01	0.4251E+01	-0.6662E+01	0.1776E+01	0.1080E+00	0.3291E+02	0.2996E+02
640	0.1085E+01	0.4325E+01	-0.6626E+01	0.1796E+01	0.1080E+00	0.3365E+02	0.2996E+02
650	0.1089E+01	0.4400E+01	-0.6589E+01	0.1817E+01	0.1080E+00	0.3440E+02	0.2995E+02
660	0.1093E+01	0.4475E+01	-0.6553E+01	0.1837E+01	0.1079E+00	0.3514E+02	0.2994E+02
670	0.1097E+01	0.4549E+01	-0.6518E+01	0.1857E+01	0.1079E+00	0.3590E+02	0.2993E+02
680	0.1101E+01	0.4624E+01	-0.6482E+01	0.1877E+01	0.1078E+00	0.3666E+02	0.2993E+02
690	0.1105E+01	0.4699E+01	-0.6447E+01	0.1896E+01	0.1078E+00	0.3742E+02	0.2992E+02
700	0.1108E+01	0.4774E+01	-0.6411E+01	0.1916E+01	0.1077E+00	0.3819E+02	0.2991E+02
710	0.1112E+01	0.4849E+01	-0.6376E+01	0.1936E+01	0.1077E+00	0.3897E+02	0.2991E+02
720	0.1116E+01	0.4924E+01	-0.6341E+01	0.1956E+01	0.1076E+00	0.3974E+02	0.2990E+02
730	0.1119E+01	0.4999E+01	-0.6306E+01	0.1975E+01	0.1076E+00	0.4053E+02	0.2990E+02
740	0.1123E+01	0.5074E+01	-0.6272E+01	0.1995E+01	0.1075E+00	0.4132E+02	0.2989E+02
750	0.1126E+01	0.5149E+01	-0.6237E+01	0.2014E+01	0.1075E+00	0.4211E+02	0.2988E+02
760	0.1129E+01	0.5224E+01	-0.6203E+01	0.2034E+01	0.1074E+00	0.4291E+02	0.2988E+02
770	0.1133E+01	0.5299E+01	-0.6169E+01	0.2053E+01	0.1074E+00	0.4371E+02	0.2987E+02
780	0.1136E+01	0.5374E+01	-0.6135E+01	0.2072E+01	0.1074E+00	0.4452E+02	0.2987E+02
790	0.1139E+01	0.5450E+01	-0.6101E+01	0.2092E+01	0.1073E+00	0.4533E+02	0.2986E+02
800	0.1142E+01	0.5525E+01	-0.6067E+01	0.2111E+01	0.1073E+00	0.4614E+02	0.2986E+02
810	0.1145E+01	0.5600E+01	-0.6033E+01	0.2130E+01	0.1072E+00	0.4696E+02	0.2986E+02
820	0.1148E+01	0.5676E+01	-0.6000E+01	0.2149E+01	0.1072E+00	0.4779E+02	0.2985E+02
830	0.1151E+01	0.5751E+01	-0.5966E+01	0.2168E+01	0.1071E+00	0.4862E+02	0.2985E+02
840	0.1154E+01	0.5826E+01	-0.5933E+01	0.2187E+01	0.1071E+00	0.4945E+02	0.2984E+02
850	0.1157E+01	0.5902E+01	-0.5900E+01	0.2206E+01	0.1071E+00	0.5029E+02	0.2984E+02
860	0.1160E+01	0.5977E+01	-0.5867E+01	0.2224E+01	0.1070E+00	0.5113E+02	0.2983E+02
870	0.1162E+01	0.6052E+01	-0.5834E+01	0.2243E+01	0.1070E+00	0.5197E+02	0.2983E+02
880	0.1165E+01	0.6128E+01	-0.5802E+01	0.2262E+01	0.1069E+00	0.5282E+02	0.2983E+02
890	0.1168E+01	0.6203E+01	-0.5769E+01	0.2281E+01	0.1069E+00	0.5368E+02	0.2982E+02
900	0.1170E+01	0.6279E+01	-0.5737E+01	0.2299E+01	0.1069E+00	0.5453E+02	0.2982E+02
910	0.1173E+01	0.6354E+01	-0.5705E+01	0.2318E+01	0.1068E+00	0.5539E+02	0.2982E+02
920	0.1175E+01	0.6430E+01	-0.5672E+01	0.2336E+01	0.1068E+00	0.5626E+02	0.2981E+02
930	0.1178E+01	0.6506E+01	-0.5640E+01	0.2354E+01	0.1067E+00	0.5713E+02	0.2981E+02
940	0.1180E+01	0.6581E+01	-0.5608E+01	0.2373E+01	0.1067E+00	0.5800E+02	0.2981E+02
950	0.1183E+01	0.6657E+01	-0.5577E+01	0.2391E+01	0.1067E+00	0.5888E+02	0.2980E+02
960	0.1185E+01	0.6732E+01	-0.5545E+01	0.2409E+01	0.1066E+00	0.5976E+02	0.2980E+02
970	0.1187E+01	0.6808E+01	-0.5513E+01	0.2428E+01	0.1066E+00	0.6064E+02	0.2980E+02
980	0.1190E+01	0.6884E+01	-0.5482E+01	0.2446E+01	0.1065E+00	0.6153E+02	0.2980E+02
990	0.1192E+01	0.6959E+01	-0.5451E+01	0.2464E+01	0.1065E+00	0.6242E+02	0.2979E+02
1000	0.1194E+01	0.7035E+01	-0.5419E+01	0.2482E+01	0.1065E+00	0.6332E+02	0.2979E+02

1010	0.1196E+01	0.7111E+01	-0.5388E+01	0.2500E+01	0.1064E+00	0.6422E+02	0.2979E+02
1020	0.1199E+01	0.7186E+01	-0.5357E+01	0.2518E+01	0.1064E+00	0.6512E+02	0.2978E+02
1030	0.1201E+01	0.7262E+01	-0.5326E+01	0.2535E+01	0.1064E+00	0.6603E+02	0.2978E+02
1040	0.1203E+01	0.7338E+01	-0.5296E+01	0.2553E+01	0.1063E+00	0.6694E+02	0.2978E+02
1050	0.1205E+01	0.7414E+01	-0.5265E+01	0.2571E+01	0.1063E+00	0.6785E+02	0.2978E+02
1060	0.1207E+01	0.7490E+01	-0.5234E+01	0.2589E+01	0.1063E+00	0.6877E+02	0.2977E+02
1070	0.1209E+01	0.7565E+01	-0.5204E+01	0.2606E+01	0.1062E+00	0.6969E+02	0.2977E+02
1080	0.1211E+01	0.7641E+01	-0.5173E+01	0.2624E+01	0.1062E+00	0.7061E+02	0.2977E+02
1090	0.1213E+01	0.7717E+01	-0.5143E+01	0.2642E+01	0.1062E+00	0.7154E+02	0.2977E+02
1100	0.1215E+01	0.7793E+01	-0.5113E+01	0.2659E+01	0.1061E+00	0.7247E+02	0.2977E+02
1110	0.1217E+01	0.7869E+01	-0.5083E+01	0.2677E+01	0.1061E+00	0.7340E+02	0.2976E+02
1120	0.1219E+01	0.7945E+01	-0.5053E+01	0.2694E+01	0.1061E+00	0.7434E+02	0.2976E+02
1130	0.1221E+01	0.8021E+01	-0.5023E+01	0.2711E+01	0.1060E+00	0.7528E+02	0.2976E+02
1140	0.1223E+01	0.8096E+01	-0.4993E+01	0.2729E+01	0.1060E+00	0.7622E+02	0.2976E+02
1150	0.1225E+01	0.8172E+01	-0.4964E+01	0.2746E+01	0.1060E+00	0.7717E+02	0.2976E+02
1160	0.1226E+01	0.8248E+01	-0.4934E+01	0.2763E+01	0.1060E+00	0.7812E+02	0.2975E+02
1170	0.1228E+01	0.8324E+01	-0.4905E+01	0.2781E+01	0.1059E+00	0.7907E+02	0.2975E+02
1180	0.1230E+01	0.8400E+01	-0.4875E+01	0.2798E+01	0.1059E+00	0.8003E+02	0.2975E+02
1190	0.1232E+01	0.8476E+01	-0.4846E+01	0.2815E+01	0.1059E+00	0.8099E+02	0.2975E+02
1200	0.1233E+01	0.8552E+01	-0.4817E+01	0.2832E+01	0.1058E+00	0.8195E+02	0.2975E+02
1210	0.1235E+01	0.8628E+01	-0.4787E+01	0.2849E+01	0.1058E+00	0.8292E+02	0.2974E+02
1220	0.1237E+01	0.8704E+01	-0.4758E+01	0.2866E+01	0.1058E+00	0.8389E+02	0.2974E+02
1230	0.1239E+01	0.8780E+01	-0.4729E+01	0.2883E+01	0.1058E+00	0.8486E+02	0.2974E+02
1240	0.1240E+01	0.8856E+01	-0.4701E+01	0.2900E+01	0.1057E+00	0.8584E+02	0.2974E+02
1250	0.1242E+01	0.8932E+01	-0.4672E+01	0.2917E+01	0.1057E+00	0.8681E+02	0.2974E+02
1260	0.1243E+01	0.9008E+01	-0.4643E+01	0.2933E+01	0.1057E+00	0.8780E+02	0.2974E+02
1270	0.1245E+01	0.9084E+01	-0.4614E+01	0.2950E+01	0.1057E+00	0.8878E+02	0.2974E+02
1280	0.1247E+01	0.9160E+01	-0.4586E+01	0.2967E+01	0.1056E+00	0.8977E+02	0.2973E+02
1290	0.1248E+01	0.9236E+01	-0.4557E+01	0.2984E+01	0.1056E+00	0.9076E+02	0.2973E+02
1300	0.1250E+01	0.9313E+01	-0.4529E+01	0.3000E+01	0.1056E+00	0.9175E+02	0.2973E+02
1310	0.1251E+01	0.9389E+01	-0.4501E+01	0.3017E+01	0.1055E+00	0.9275E+02	0.2973E+02
1320	0.1253E+01	0.9465E+01	-0.4473E+01	0.3033E+01	0.1055E+00	0.9375E+02	0.2973E+02
1330	0.1254E+01	0.9541E+01	-0.4444E+01	0.3050E+01	0.1055E+00	0.9475E+02	0.2973E+02
1340	0.1256E+01	0.9617E+01	-0.4416E+01	0.3066E+01	0.1055E+00	0.9576E+02	0.2973E+02
1350	0.1257E+01	0.9693E+01	-0.4388E+01	0.3083E+01	0.1054E+00	0.9676E+02	0.2972E+02
1360	0.1259E+01	0.9769E+01	-0.4360E+01	0.3099E+01	0.1054E+00	0.9777E+02	0.2972E+02
1370	0.1260E+01	0.9845E+01	-0.4333E+01	0.3116E+01	0.1054E+00	0.9879E+02	0.2972E+02
1380	0.1262E+01	0.9921E+01	-0.4305E+01	0.3132E+01	0.1054E+00	0.9980E+02	0.2972E+02
1390	0.1263E+01	0.9998E+01	-0.4277E+01	0.3148E+01	0.1054E+00	0.1008E+03	0.2972E+02
1400	0.1264E+01	0.1007E+02	-0.4249E+01	0.3165E+01	0.1053E+00	0.1018E+03	0.2972E+02
1410	0.1266E+01	0.1015E+02	-0.4222E+01	0.3181E+01	0.1053E+00	0.1029E+03	0.2972E+02
1420	0.1267E+01	0.1023E+02	-0.4194E+01	0.3197E+01	0.1053E+00	0.1039E+03	0.2972E+02
1430	0.1268E+01	0.1030E+02	-0.4167E+01	0.3213E+01	0.1053E+00	0.1049E+03	0.2971E+02
1440	0.1270E+01	0.1038E+02	-0.4140E+01	0.3229E+01	0.1052E+00	0.1060E+03	0.2971E+02
1450	0.1271E+01	0.1045E+02	-0.4112E+01	0.3245E+01	0.1052E+00	0.1070E+03	0.2971E+02
1460	0.1272E+01	0.1053E+02	-0.4085E+01	0.3261E+01	0.1052E+00	0.1080E+03	0.2971E+02
1470	0.1274E+01	0.1061E+02	-0.4058E+01	0.3277E+01	0.1052E+00	0.1091E+03	0.2971E+02
1480	0.1275E+01	0.1068E+02	-0.4031E+01	0.3293E+01	0.1052E+00	0.1101E+03	0.2971E+02
1490	0.1276E+01	0.1076E+02	-0.4004E+01	0.3309E+01	0.1051E+00	0.1112E+03	0.2971E+02
1500	0.1278E+01	0.1084E+02	-0.3977E+01	0.3325E+01	0.1051E+00	0.1122E+03	0.2971E+02
1510	0.1279E+01	0.1091E+02	-0.3950E+01	0.3341E+01	0.1051E+00	0.1133E+03	0.2971E+02
1520	0.1280E+01	0.1099E+02	-0.3923E+01	0.3357E+01	0.1051E+00	0.1143E+03	0.2970E+02
1530	0.1281E+01	0.1106E+02	-0.3897E+01	0.3373E+01	0.1051E+00	0.1154E+03	0.2970E+02

1540	0.1283E+01	0.1114E+02	-0.3870E+01	0.3389E+01	0.1050E+00	0.1164E+03	0.2970E+02
1550	0.1284E+01	0.1122E+02	-0.3843E+01	0.3404E+01	0.1050E+00	0.1175E+03	0.2970E+02
1560	0.1285E+01	0.1129E+02	-0.3817E+01	0.3420E+01	0.1050E+00	0.1186E+03	0.2970E+02
1570	0.1286E+01	0.1137E+02	-0.3790E+01	0.3436E+01	0.1050E+00	0.1196E+03	0.2970E+02
1580	0.1287E+01	0.1145E+02	-0.3764E+01	0.3451E+01	0.1050E+00	0.1207E+03	0.2970E+02
1590	0.1288E+01	0.1152E+02	-0.3737E+01	0.3467E+01	0.1049E+00	0.1218E+03	0.2970E+02
1600	0.1290E+01	0.1160E+02	-0.3711E+01	0.3483E+01	0.1049E+00	0.1229E+03	0.2970E+02
1610	0.1291E+01	0.1167E+02	-0.3685E+01	0.3498E+01	0.1049E+00	0.1239E+03	0.2970E+02
1620	0.1292E+01	0.1175E+02	-0.3659E+01	0.3514E+01	0.1049E+00	0.1250E+03	0.2970E+02
1630	0.1293E+01	0.1183E+02	-0.3633E+01	0.3529E+01	0.1049E+00	0.1261E+03	0.2970E+02
1640	0.1294E+01	0.1190E+02	-0.3607E+01	0.3545E+01	0.1048E+00	0.1272E+03	0.2969E+02
1650	0.1295E+01	0.1198E+02	-0.3581E+01	0.3560E+01	0.1048E+00	0.1283E+03	0.2969E+02
1660	0.1296E+01	0.1206E+02	-0.3555E+01	0.3575E+01	0.1048E+00	0.1294E+03	0.2969E+02
1670	0.1297E+01	0.1213E+02	-0.3529E+01	0.3591E+01	0.1048E+00	0.1305E+03	0.2969E+02
1680	0.1299E+01	0.1221E+02	-0.3503E+01	0.3606E+01	0.1048E+00	0.1316E+03	0.2969E+02
1690	0.1300E+01	0.1229E+02	-0.3477E+01	0.3621E+01	0.1048E+00	0.1327E+03	0.2969E+02
1700	0.1301E+01	0.1236E+02	-0.3451E+01	0.3637E+01	0.1047E+00	0.1338E+03	0.2969E+02
1702	0.1301E+01	0.1238E+02	-0.3446E+01	0.3638E+01	0.1047E+00	0.1339E+03	0.2969E+02

LNGC Thermal Discharge - Case 1 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.5300E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4872E-01	0.0000E+00	-0.5349E+01	0.7112E+00	0.2677E+01	0.1016E+01	0.3255E+02
10	0.4142E+00	0.0000E+00	-0.5714E+01	0.7952E+00	0.2394E+01	0.1136E+01	0.3224E+02
20	0.8236E+00	0.0000E+00	-0.6123E+01	0.8890E+00	0.2140E+01	0.1269E+01	0.3196E+02
30	0.1194E+01	0.0000E+00	-0.6492E+01	0.9738E+00	0.1953E+01	0.1390E+01	0.3176E+02
40	0.1535E+01	0.0000E+00	-0.6832E+01	0.1052E+01	0.1808E+01	0.1501E+01	0.3160E+02
50	0.1853E+01	0.0000E+00	-0.7148E+01	0.1124E+01	0.1691E+01	0.1604E+01	0.3147E+02
60	0.2152E+01	0.0000E+00	-0.7444E+01	0.1193E+01	0.1593E+01	0.1701E+01	0.3136E+02
70	0.2434E+01	0.0000E+00	-0.7725E+01	0.1257E+01	0.1511E+01	0.1792E+01	0.3127E+02
80	0.2703E+01	0.0000E+00	-0.7991E+01	0.1318E+01	0.1441E+01	0.1879E+01	0.3120E+02
90	0.2960E+01	0.0000E+00	-0.8246E+01	0.1377E+01	0.1379E+01	0.1962E+01	0.3113E+02
100	0.3207E+01	0.0000E+00	-0.8490E+01	0.1433E+01	0.1324E+01	0.2041E+01	0.3107E+02
110	0.3445E+01	0.0000E+00	-0.8724E+01	0.1487E+01	0.1276E+01	0.2118E+01	0.3102E+02
120	0.3674E+01	0.0000E+00	-0.8951E+01	0.1539E+01	0.1232E+01	0.2191E+01	0.3097E+02
130	0.3896E+01	0.0000E+00	-0.9169E+01	0.1590E+01	0.1193E+01	0.2262E+01	0.3093E+02
140	0.4111E+01	0.0000E+00	-0.9381E+01	0.1638E+01	0.1157E+01	0.2331E+01	0.3089E+02
150	0.4320E+01	0.0000E+00	-0.9586E+01	0.1686E+01	0.1124E+01	0.2398E+01	0.3085E+02
160	0.4524E+01	0.0000E+00	-0.9786E+01	0.1732E+01	0.1094E+01	0.2463E+01	0.3082E+02
170	0.4722E+01	0.0000E+00	-0.9980E+01	0.1777E+01	0.1066E+01	0.2526E+01	0.3079E+02
180	0.4915E+01	0.0000E+00	-0.1017E+02	0.1821E+01	0.1040E+01	0.2588E+01	0.3076E+02
190	0.5104E+01	0.0000E+00	-0.1035E+02	0.1863E+01	0.1016E+01	0.2648E+01	0.3073E+02
200	0.5289E+01	0.0000E+00	-0.1053E+02	0.1905E+01	0.9931E+00	0.2706E+01	0.3071E+02
210	0.5470E+01	0.0000E+00	-0.1071E+02	0.1946E+01	0.9720E+00	0.2763E+01	0.3069E+02
220	0.5647E+01	0.0000E+00	-0.1088E+02	0.1986E+01	0.9521E+00	0.2819E+01	0.3066E+02
230	0.5820E+01	0.0000E+00	-0.1105E+02	0.2025E+01	0.9333E+00	0.2874E+01	0.3064E+02
240	0.5991E+01	0.0000E+00	-0.1122E+02	0.2064E+01	0.9157E+00	0.2928E+01	0.3062E+02
250	0.6158E+01	0.0000E+00	-0.1138E+02	0.2102E+01	0.8989E+00	0.2981E+01	0.3061E+02
260	0.6323E+01	0.0000E+00	-0.1154E+02	0.2139E+01	0.8831E+00	0.3032E+01	0.3059E+02
270	0.6484E+01	0.0000E+00	-0.1170E+02	0.2175E+01	0.8680E+00	0.3083E+01	0.3057E+02
280	0.6644E+01	0.0000E+00	-0.1185E+02	0.2211E+01	0.8537E+00	0.3133E+01	0.3056E+02
290	0.6800E+01	0.0000E+00	-0.1200E+02	0.2246E+01	0.8400E+00	0.3182E+01	0.3054E+02
300	0.6954E+01	0.0000E+00	-0.1215E+02	0.2281E+01	0.8270E+00	0.3230E+01	0.3053E+02
310	0.7106E+01	0.0000E+00	-0.1230E+02	0.2315E+01	0.8145E+00	0.3278E+01	0.3052E+02
320	0.7256E+01	0.0000E+00	-0.1244E+02	0.2349E+01	0.8026E+00	0.3325E+01	0.3050E+02
330	0.7404E+01	0.0000E+00	-0.1258E+02	0.2382E+01	0.7912E+00	0.3371E+01	0.3049E+02
340	0.7550E+01	0.0000E+00	-0.1272E+02	0.2415E+01	0.7802E+00	0.3416E+01	0.3048E+02
350	0.7694E+01	0.0000E+00	-0.1286E+02	0.2447E+01	0.7697E+00	0.3461E+01	0.3047E+02
360	0.7836E+01	0.0000E+00	-0.1300E+02	0.2479E+01	0.7595E+00	0.3505E+01	0.3046E+02
370	0.7976E+01	0.0000E+00	-0.1313E+02	0.2511E+01	0.7498E+00	0.3548E+01	0.3045E+02
380	0.8115E+01	0.0000E+00	-0.1326E+02	0.2542E+01	0.7404E+00	0.3591E+01	0.3044E+02
390	0.8251E+01	0.0000E+00	-0.1339E+02	0.2572E+01	0.7313E+00	0.3633E+01	0.3043E+02
400	0.8387E+01	0.0000E+00	-0.1352E+02	0.2603E+01	0.7226E+00	0.3675E+01	0.3042E+02
410	0.8521E+01	0.0000E+00	-0.1365E+02	0.2633E+01	0.7142E+00	0.3716E+01	0.3041E+02
420	0.8653E+01	0.0000E+00	-0.1378E+02	0.2662E+01	0.7060E+00	0.3757E+01	0.3040E+02
430	0.8784E+01	0.0000E+00	-0.1390E+02	0.2692E+01	0.6981E+00	0.3797E+01	0.3039E+02
440	0.8914E+01	0.0000E+00	-0.1402E+02	0.2720E+01	0.6905E+00	0.3837E+01	0.3038E+02
450	0.9042E+01	0.0000E+00	-0.1414E+02	0.2749E+01	0.6831E+00	0.3876E+01	0.3037E+02
460	0.9169E+01	0.0000E+00	-0.1426E+02	0.2778E+01	0.6759E+00	0.3915E+01	0.3037E+02
470	0.9295E+01	0.0000E+00	-0.1438E+02	0.2806E+01	0.6689E+00	0.3953E+01	0.3036E+02

480	0.9419E+01	0.0000E+00	-0.1450E+02	0.2833E+01	0.6622E+00	0.3991E+01	0.3035E+02
490	0.9543E+01	0.0000E+00	-0.1462E+02	0.2861E+01	0.6556E+00	0.4029E+01	0.3034E+02
500	0.9665E+01	0.0000E+00	-0.1473E+02	0.2888E+01	0.6492E+00	0.4066E+01	0.3034E+02
510	0.9786E+01	0.0000E+00	-0.1485E+02	0.2915E+01	0.6430E+00	0.4103E+01	0.3033E+02
520	0.9906E+01	0.0000E+00	-0.1496E+02	0.2942E+01	0.6370E+00	0.4139E+01	0.3032E+02
530	0.1003E+02	0.0000E+00	-0.1507E+02	0.2968E+01	0.6311E+00	0.4175E+01	0.3032E+02
540	0.1014E+02	0.0000E+00	-0.1518E+02	0.2995E+01	0.6254E+00	0.4211E+01	0.3031E+02
550	0.1026E+02	0.0000E+00	-0.1529E+02	0.3021E+01	0.6198E+00	0.4246E+01	0.3031E+02
560	0.1038E+02	0.0000E+00	-0.1540E+02	0.3046E+01	0.6144E+00	0.4281E+01	0.3030E+02
570	0.1049E+02	0.0000E+00	-0.1551E+02	0.3072E+01	0.6091E+00	0.4316E+01	0.3030E+02
580	0.1061E+02	0.0000E+00	-0.1561E+02	0.3097E+01	0.6039E+00	0.4350E+01	0.3029E+02
590	0.1072E+02	0.0000E+00	-0.1572E+02	0.3123E+01	0.5989E+00	0.4384E+01	0.3028E+02
600	0.1083E+02	0.0000E+00	-0.1582E+02	0.3148E+01	0.5940E+00	0.4418E+01	0.3028E+02
610	0.1094E+02	0.0000E+00	-0.1592E+02	0.3172E+01	0.5891E+00	0.4452E+01	0.3027E+02
620	0.1105E+02	0.0000E+00	-0.1603E+02	0.3197E+01	0.5844E+00	0.4485E+01	0.3027E+02
630	0.1116E+02	0.0000E+00	-0.1613E+02	0.3221E+01	0.5799E+00	0.4518E+01	0.3026E+02
640	0.1127E+02	0.0000E+00	-0.1623E+02	0.3245E+01	0.5754E+00	0.4550E+01	0.3026E+02
650	0.1138E+02	0.0000E+00	-0.1633E+02	0.3269E+01	0.5710E+00	0.4582E+01	0.3025E+02
660	0.1149E+02	0.0000E+00	-0.1643E+02	0.3293E+01	0.5667E+00	0.4614E+01	0.3025E+02
670	0.1160E+02	0.0000E+00	-0.1653E+02	0.3317E+01	0.5625E+00	0.4646E+01	0.3025E+02
680	0.1170E+02	0.0000E+00	-0.1663E+02	0.3340E+01	0.5584E+00	0.4678E+01	0.3024E+02
690	0.1181E+02	0.0000E+00	-0.1672E+02	0.3364E+01	0.5543E+00	0.4709E+01	0.3024E+02

LNGC Thermal Discharge - Case 2 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6350E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4872E-01	0.0000E+00	-0.6399E+01	0.7112E+00	0.2677E+01	0.1016E+01	0.3255E+02
10	0.4142E+00	0.0000E+00	-0.6764E+01	0.7952E+00	0.2394E+01	0.1136E+01	0.3224E+02
20	0.8236E+00	0.0000E+00	-0.7173E+01	0.8890E+00	0.2140E+01	0.1269E+01	0.3196E+02
30	0.1194E+01	0.0000E+00	-0.7542E+01	0.9738E+00	0.1953E+01	0.1390E+01	0.3176E+02
40	0.1535E+01	0.0000E+00	-0.7882E+01	0.1052E+01	0.1808E+01	0.1501E+01	0.3160E+02
50	0.1853E+01	0.0000E+00	-0.8198E+01	0.1124E+01	0.1691E+01	0.1604E+01	0.3147E+02
60	0.2152E+01	0.0000E+00	-0.8494E+01	0.1193E+01	0.1593E+01	0.1701E+01	0.3136E+02
70	0.2434E+01	0.0000E+00	-0.8775E+01	0.1257E+01	0.1511E+01	0.1792E+01	0.3127E+02
80	0.2703E+01	0.0000E+00	-0.9041E+01	0.1318E+01	0.1441E+01	0.1879E+01	0.3120E+02
90	0.2960E+01	0.0000E+00	-0.9296E+01	0.1377E+01	0.1379E+01	0.1962E+01	0.3113E+02
100	0.3207E+01	0.0000E+00	-0.9540E+01	0.1433E+01	0.1324E+01	0.2041E+01	0.3107E+02
110	0.3445E+01	0.0000E+00	-0.9774E+01	0.1487E+01	0.1276E+01	0.2118E+01	0.3102E+02
120	0.3674E+01	0.0000E+00	-0.1000E+02	0.1539E+01	0.1232E+01	0.2191E+01	0.3097E+02
130	0.3896E+01	0.0000E+00	-0.1022E+02	0.1590E+01	0.1193E+01	0.2262E+01	0.3093E+02
140	0.4111E+01	0.0000E+00	-0.1043E+02	0.1638E+01	0.1157E+01	0.2331E+01	0.3089E+02
150	0.4320E+01	0.0000E+00	-0.1064E+02	0.1686E+01	0.1124E+01	0.2398E+01	0.3085E+02
160	0.4524E+01	0.0000E+00	-0.1084E+02	0.1732E+01	0.1094E+01	0.2463E+01	0.3082E+02
170	0.4722E+01	0.0000E+00	-0.1103E+02	0.1777E+01	0.1066E+01	0.2526E+01	0.3079E+02
180	0.4915E+01	0.0000E+00	-0.1122E+02	0.1821E+01	0.1040E+01	0.2588E+01	0.3076E+02
190	0.5104E+01	0.0000E+00	-0.1140E+02	0.1863E+01	0.1016E+01	0.2648E+01	0.3073E+02
200	0.5289E+01	0.0000E+00	-0.1158E+02	0.1905E+01	0.9931E+00	0.2706E+01	0.3071E+02
210	0.5470E+01	0.0000E+00	-0.1176E+02	0.1946E+01	0.9720E+00	0.2763E+01	0.3069E+02
220	0.5647E+01	0.0000E+00	-0.1193E+02	0.1986E+01	0.9521E+00	0.2819E+01	0.3066E+02
230	0.5820E+01	0.0000E+00	-0.1210E+02	0.2025E+01	0.9333E+00	0.2874E+01	0.3064E+02
240	0.5991E+01	0.0000E+00	-0.1227E+02	0.2064E+01	0.9157E+00	0.2928E+01	0.3062E+02
250	0.6158E+01	0.0000E+00	-0.1243E+02	0.2102E+01	0.8989E+00	0.2981E+01	0.3061E+02
260	0.6323E+01	0.0000E+00	-0.1259E+02	0.2139E+01	0.8831E+00	0.3032E+01	0.3059E+02
270	0.6484E+01	0.0000E+00	-0.1275E+02	0.2175E+01	0.8680E+00	0.3083E+01	0.3057E+02
280	0.6644E+01	0.0000E+00	-0.1290E+02	0.2211E+01	0.8537E+00	0.3133E+01	0.3056E+02
290	0.6800E+01	0.0000E+00	-0.1305E+02	0.2246E+01	0.8400E+00	0.3182E+01	0.3054E+02
300	0.6954E+01	0.0000E+00	-0.1320E+02	0.2281E+01	0.8270E+00	0.3230E+01	0.3053E+02
310	0.7106E+01	0.0000E+00	-0.1335E+02	0.2315E+01	0.8145E+00	0.3278E+01	0.3052E+02
320	0.7256E+01	0.0000E+00	-0.1349E+02	0.2349E+01	0.8026E+00	0.3325E+01	0.3050E+02
330	0.7404E+01	0.0000E+00	-0.1363E+02	0.2382E+01	0.7912E+00	0.3371E+01	0.3049E+02
340	0.7550E+01	0.0000E+00	-0.1377E+02	0.2415E+01	0.7802E+00	0.3416E+01	0.3048E+02
350	0.7694E+01	0.0000E+00	-0.1391E+02	0.2447E+01	0.7697E+00	0.3461E+01	0.3047E+02
360	0.7836E+01	0.0000E+00	-0.1405E+02	0.2479E+01	0.7595E+00	0.3505E+01	0.3046E+02
370	0.7976E+01	0.0000E+00	-0.1418E+02	0.2511E+01	0.7498E+00	0.3548E+01	0.3045E+02
380	0.8115E+01	0.0000E+00	-0.1431E+02	0.2542E+01	0.7404E+00	0.3591E+01	0.3044E+02
390	0.8251E+01	0.0000E+00	-0.1444E+02	0.2572E+01	0.7313E+00	0.3633E+01	0.3043E+02
400	0.8387E+01	0.0000E+00	-0.1457E+02	0.2603E+01	0.7226E+00	0.3675E+01	0.3042E+02
410	0.8521E+01	0.0000E+00	-0.1470E+02	0.2633E+01	0.7142E+00	0.3716E+01	0.3041E+02
420	0.8653E+01	0.0000E+00	-0.1483E+02	0.2662E+01	0.7060E+00	0.3757E+01	0.3040E+02
430	0.8784E+01	0.0000E+00	-0.1495E+02	0.2692E+01	0.6981E+00	0.3797E+01	0.3039E+02
440	0.8914E+01	0.0000E+00	-0.1507E+02	0.2720E+01	0.6905E+00	0.3837E+01	0.3038E+02
450	0.9042E+01	0.0000E+00	-0.1519E+02	0.2749E+01	0.6831E+00	0.3876E+01	0.3037E+02
460	0.9169E+01	0.0000E+00	-0.1531E+02	0.2778E+01	0.6759E+00	0.3915E+01	0.3037E+02
470	0.9295E+01	0.0000E+00	-0.1543E+02	0.2806E+01	0.6689E+00	0.3953E+01	0.3036E+02

480	0.9419E+01	0.0000E+00	-0.1555E+02	0.2833E+01	0.6622E+00	0.3991E+01	0.3035E+02
490	0.9543E+01	0.0000E+00	-0.1567E+02	0.2861E+01	0.6556E+00	0.4029E+01	0.3034E+02
500	0.9665E+01	0.0000E+00	-0.1578E+02	0.2888E+01	0.6492E+00	0.4066E+01	0.3034E+02
510	0.9786E+01	0.0000E+00	-0.1590E+02	0.2915E+01	0.6430E+00	0.4103E+01	0.3033E+02
520	0.9906E+01	0.0000E+00	-0.1601E+02	0.2942E+01	0.6370E+00	0.4139E+01	0.3032E+02
530	0.1003E+02	0.0000E+00	-0.1612E+02	0.2968E+01	0.6311E+00	0.4175E+01	0.3032E+02
540	0.1014E+02	0.0000E+00	-0.1623E+02	0.2995E+01	0.6254E+00	0.4211E+01	0.3031E+02
550	0.1026E+02	0.0000E+00	-0.1634E+02	0.3021E+01	0.6198E+00	0.4246E+01	0.3031E+02
560	0.1038E+02	0.0000E+00	-0.1645E+02	0.3046E+01	0.6144E+00	0.4281E+01	0.3030E+02
570	0.1049E+02	0.0000E+00	-0.1656E+02	0.3072E+01	0.6091E+00	0.4316E+01	0.3030E+02
580	0.1061E+02	0.0000E+00	-0.1666E+02	0.3097E+01	0.6039E+00	0.4350E+01	0.3029E+02
590	0.1072E+02	0.0000E+00	-0.1677E+02	0.3123E+01	0.5989E+00	0.4384E+01	0.3028E+02
600	0.1083E+02	0.0000E+00	-0.1687E+02	0.3148E+01	0.5940E+00	0.4418E+01	0.3028E+02
602	0.1085E+02	0.0000E+00	-0.1689E+02	0.3152E+01	0.5930E+00	0.4425E+01	0.3028E+02

LNGC Thermal Discharge - Case 3 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7400E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4872E-01	0.0000E+00	-0.7449E+01	0.7112E+00	0.2677E+01	0.1016E+01	0.3255E+02
10	0.4142E+00	0.0000E+00	-0.7814E+01	0.7952E+00	0.2394E+01	0.1136E+01	0.3224E+02
20	0.8236E+00	0.0000E+00	-0.8223E+01	0.8890E+00	0.2140E+01	0.1269E+01	0.3196E+02
30	0.1194E+01	0.0000E+00	-0.8592E+01	0.9738E+00	0.1953E+01	0.1390E+01	0.3176E+02
40	0.1535E+01	0.0000E+00	-0.8932E+01	0.1052E+01	0.1808E+01	0.1501E+01	0.3160E+02
50	0.1853E+01	0.0000E+00	-0.9248E+01	0.1124E+01	0.1691E+01	0.1604E+01	0.3147E+02
60	0.2152E+01	0.0000E+00	-0.9544E+01	0.1193E+01	0.1593E+01	0.1701E+01	0.3136E+02
70	0.2434E+01	0.0000E+00	-0.9825E+01	0.1257E+01	0.1511E+01	0.1792E+01	0.3127E+02
80	0.2703E+01	0.0000E+00	-0.1009E+02	0.1318E+01	0.1441E+01	0.1879E+01	0.3120E+02
90	0.2960E+01	0.0000E+00	-0.1035E+02	0.1377E+01	0.1379E+01	0.1962E+01	0.3113E+02
100	0.3207E+01	0.0000E+00	-0.1059E+02	0.1433E+01	0.1324E+01	0.2041E+01	0.3107E+02
110	0.3445E+01	0.0000E+00	-0.1082E+02	0.1487E+01	0.1276E+01	0.2118E+01	0.3102E+02
120	0.3674E+01	0.0000E+00	-0.1105E+02	0.1539E+01	0.1232E+01	0.2191E+01	0.3097E+02
130	0.3896E+01	0.0000E+00	-0.1127E+02	0.1590E+01	0.1193E+01	0.2262E+01	0.3093E+02
140	0.4111E+01	0.0000E+00	-0.1148E+02	0.1638E+01	0.1157E+01	0.2331E+01	0.3089E+02
150	0.4320E+01	0.0000E+00	-0.1169E+02	0.1686E+01	0.1124E+01	0.2398E+01	0.3085E+02
160	0.4524E+01	0.0000E+00	-0.1189E+02	0.1732E+01	0.1094E+01	0.2463E+01	0.3082E+02
170	0.4722E+01	0.0000E+00	-0.1208E+02	0.1777E+01	0.1066E+01	0.2526E+01	0.3079E+02
180	0.4915E+01	0.0000E+00	-0.1227E+02	0.1821E+01	0.1040E+01	0.2588E+01	0.3076E+02
190	0.5104E+01	0.0000E+00	-0.1245E+02	0.1863E+01	0.1016E+01	0.2648E+01	0.3073E+02
200	0.5289E+01	0.0000E+00	-0.1263E+02	0.1905E+01	0.9931E+00	0.2706E+01	0.3071E+02
210	0.5470E+01	0.0000E+00	-0.1281E+02	0.1946E+01	0.9720E+00	0.2763E+01	0.3069E+02
220	0.5647E+01	0.0000E+00	-0.1298E+02	0.1986E+01	0.9521E+00	0.2819E+01	0.3066E+02
230	0.5820E+01	0.0000E+00	-0.1315E+02	0.2025E+01	0.9333E+00	0.2874E+01	0.3064E+02
240	0.5991E+01	0.0000E+00	-0.1332E+02	0.2064E+01	0.9157E+00	0.2928E+01	0.3062E+02
250	0.6158E+01	0.0000E+00	-0.1348E+02	0.2102E+01	0.8989E+00	0.2981E+01	0.3061E+02
260	0.6323E+01	0.0000E+00	-0.1364E+02	0.2139E+01	0.8831E+00	0.3032E+01	0.3059E+02
270	0.6484E+01	0.0000E+00	-0.1380E+02	0.2175E+01	0.8680E+00	0.3083E+01	0.3057E+02
280	0.6644E+01	0.0000E+00	-0.1395E+02	0.2211E+01	0.8537E+00	0.3133E+01	0.3056E+02
290	0.6800E+01	0.0000E+00	-0.1410E+02	0.2246E+01	0.8400E+00	0.3182E+01	0.3054E+02
300	0.6954E+01	0.0000E+00	-0.1425E+02	0.2281E+01	0.8270E+00	0.3230E+01	0.3053E+02
310	0.7106E+01	0.0000E+00	-0.1440E+02	0.2315E+01	0.8145E+00	0.3278E+01	0.3052E+02
320	0.7256E+01	0.0000E+00	-0.1454E+02	0.2349E+01	0.8026E+00	0.3325E+01	0.3050E+02
330	0.7404E+01	0.0000E+00	-0.1468E+02	0.2382E+01	0.7912E+00	0.3371E+01	0.3049E+02
340	0.7550E+01	0.0000E+00	-0.1482E+02	0.2415E+01	0.7802E+00	0.3416E+01	0.3048E+02
350	0.7694E+01	0.0000E+00	-0.1496E+02	0.2447E+01	0.7697E+00	0.3461E+01	0.3047E+02
360	0.7836E+01	0.0000E+00	-0.1510E+02	0.2479E+01	0.7595E+00	0.3505E+01	0.3046E+02
370	0.7976E+01	0.0000E+00	-0.1523E+02	0.2511E+01	0.7498E+00	0.3548E+01	0.3045E+02
380	0.8115E+01	0.0000E+00	-0.1536E+02	0.2542E+01	0.7404E+00	0.3591E+01	0.3044E+02
390	0.8251E+01	0.0000E+00	-0.1549E+02	0.2572E+01	0.7313E+00	0.3633E+01	0.3043E+02
400	0.8387E+01	0.0000E+00	-0.1562E+02	0.2603E+01	0.7226E+00	0.3675E+01	0.3042E+02
410	0.8521E+01	0.0000E+00	-0.1575E+02	0.2633E+01	0.7142E+00	0.3716E+01	0.3041E+02
420	0.8653E+01	0.0000E+00	-0.1588E+02	0.2662E+01	0.7060E+00	0.3757E+01	0.3040E+02
430	0.8784E+01	0.0000E+00	-0.1600E+02	0.2692E+01	0.6981E+00	0.3797E+01	0.3039E+02
440	0.8914E+01	0.0000E+00	-0.1612E+02	0.2720E+01	0.6905E+00	0.3837E+01	0.3038E+02
450	0.9042E+01	0.0000E+00	-0.1624E+02	0.2749E+01	0.6831E+00	0.3876E+01	0.3037E+02
460	0.9169E+01	0.0000E+00	-0.1636E+02	0.2778E+01	0.6759E+00	0.3915E+01	0.3037E+02
470	0.9295E+01	0.0000E+00	-0.1648E+02	0.2806E+01	0.6689E+00	0.3953E+01	0.3036E+02

480	0.9419E+01	0.0000E+00	-0.1660E+02	0.2833E+01	0.6622E+00	0.3991E+01	0.3035E+02
490	0.9543E+01	0.0000E+00	-0.1672E+02	0.2861E+01	0.6556E+00	0.4029E+01	0.3034E+02
500	0.9665E+01	0.0000E+00	-0.1683E+02	0.2888E+01	0.6492E+00	0.4066E+01	0.3034E+02
510	0.9786E+01	0.0000E+00	-0.1695E+02	0.2915E+01	0.6430E+00	0.4103E+01	0.3033E+02
520	0.9906E+01	0.0000E+00	-0.1706E+02	0.2942E+01	0.6370E+00	0.4139E+01	0.3032E+02

LNGC Thermal Discharge - Case 4 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.5300E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4861E-01	0.4630E-04	-0.5349E+01	0.7128E+00	0.2671E+01	0.1018E+01	0.3255E+02
10	0.4101E+00	0.1839E-02	-0.5710E+01	0.8091E+00	0.2352E+01	0.1156E+01	0.3220E+02
20	0.8093E+00	0.6821E-02	-0.6108E+01	0.9170E+00	0.2075E+01	0.1309E+01	0.3189E+02
30	0.1166E+01	0.1399E-01	-0.6464E+01	0.1015E+01	0.1874E+01	0.1449E+01	0.3167E+02
40	0.1492E+01	0.2279E-01	-0.6789E+01	0.1106E+01	0.1720E+01	0.1578E+01	0.3150E+02
50	0.1793E+01	0.3287E-01	-0.7088E+01	0.1190E+01	0.1597E+01	0.1699E+01	0.3137E+02
60	0.2074E+01	0.4400E-01	-0.7367E+01	0.1271E+01	0.1496E+01	0.1813E+01	0.3126E+02
70	0.2339E+01	0.5599E-01	-0.7630E+01	0.1347E+01	0.1411E+01	0.1921E+01	0.3116E+02
80	0.2589E+01	0.6871E-01	-0.7878E+01	0.1420E+01	0.1338E+01	0.2024E+01	0.3108E+02
90	0.2827E+01	0.8207E-01	-0.8113E+01	0.1490E+01	0.1275E+01	0.2124E+01	0.3101E+02
100	0.3054E+01	0.9598E-01	-0.8338E+01	0.1557E+01	0.1219E+01	0.2219E+01	0.3095E+02
110	0.3272E+01	0.1104E+00	-0.8553E+01	0.1622E+01	0.1170E+01	0.2312E+01	0.3090E+02
120	0.3482E+01	0.1252E+00	-0.8760E+01	0.1686E+01	0.1126E+01	0.2402E+01	0.3085E+02
130	0.3684E+01	0.1404E+00	-0.8959E+01	0.1747E+01	0.1086E+01	0.2489E+01	0.3081E+02
140	0.3879E+01	0.1560E+00	-0.9151E+01	0.1807E+01	0.1050E+01	0.2573E+01	0.3077E+02
150	0.4068E+01	0.1719E+00	-0.9337E+01	0.1865E+01	0.1017E+01	0.2656E+01	0.3073E+02
160	0.4252E+01	0.1881E+00	-0.9517E+01	0.1922E+01	0.9865E+00	0.2737E+01	0.3070E+02
170	0.4430E+01	0.2046E+00	-0.9691E+01	0.1978E+01	0.9585E+00	0.2815E+01	0.3067E+02
180	0.4603E+01	0.2213E+00	-0.9861E+01	0.2033E+01	0.9326E+00	0.2892E+01	0.3064E+02
190	0.4772E+01	0.2383E+00	-0.1003E+02	0.2086E+01	0.9085E+00	0.2968E+01	0.3061E+02
200	0.4936E+01	0.2555E+00	-0.1019E+02	0.2138E+01	0.8860E+00	0.3042E+01	0.3059E+02
210	0.5097E+01	0.2729E+00	-0.1034E+02	0.2190E+01	0.8650E+00	0.3115E+01	0.3056E+02
220	0.5254E+01	0.2905E+00	-0.1050E+02	0.2241E+01	0.8453E+00	0.3186E+01	0.3054E+02
230	0.5407E+01	0.3082E+00	-0.1065E+02	0.2290E+01	0.8268E+00	0.3256E+01	0.3052E+02
240	0.5557E+01	0.3261E+00	-0.1079E+02	0.2339E+01	0.8093E+00	0.3325E+01	0.3050E+02
250	0.5705E+01	0.3442E+00	-0.1093E+02	0.2388E+01	0.7928E+00	0.3394E+01	0.3048E+02
260	0.5849E+01	0.3624E+00	-0.1107E+02	0.2435E+01	0.7771E+00	0.3461E+01	0.3047E+02
270	0.5990E+01	0.3808E+00	-0.1121E+02	0.2482E+01	0.7623E+00	0.3527E+01	0.3045E+02
280	0.6129E+01	0.3993E+00	-0.1135E+02	0.2529E+01	0.7482E+00	0.3592E+01	0.3044E+02
290	0.6266E+01	0.4180E+00	-0.1148E+02	0.2574E+01	0.7348E+00	0.3656E+01	0.3042E+02
300	0.6400E+01	0.4367E+00	-0.1161E+02	0.2619E+01	0.7220E+00	0.3719E+01	0.3041E+02
310	0.6532E+01	0.4556E+00	-0.1173E+02	0.2664E+01	0.7098E+00	0.3782E+01	0.3039E+02
320	0.6661E+01	0.4746E+00	-0.1186E+02	0.2708E+01	0.6981E+00	0.3844E+01	0.3038E+02
330	0.6789E+01	0.4937E+00	-0.1198E+02	0.2751E+01	0.6870E+00	0.3905E+01	0.3037E+02
340	0.6915E+01	0.5129E+00	-0.1210E+02	0.2794E+01	0.6763E+00	0.3965E+01	0.3036E+02
350	0.7039E+01	0.5322E+00	-0.1222E+02	0.2837E+01	0.6660E+00	0.4025E+01	0.3035E+02
360	0.7161E+01	0.5516E+00	-0.1234E+02	0.2879E+01	0.6562E+00	0.4084E+01	0.3033E+02
370	0.7281E+01	0.5711E+00	-0.1245E+02	0.2921E+01	0.6467E+00	0.4143E+01	0.3032E+02
380	0.7399E+01	0.5906E+00	-0.1257E+02	0.2962E+01	0.6376E+00	0.4201E+01	0.3031E+02
390	0.7516E+01	0.6103E+00	-0.1268E+02	0.3003E+01	0.6288E+00	0.4258E+01	0.3030E+02
400	0.7632E+01	0.6300E+00	-0.1279E+02	0.3044E+01	0.6203E+00	0.4315E+01	0.3030E+02
410	0.7746E+01	0.6499E+00	-0.1290E+02	0.3084E+01	0.6121E+00	0.4371E+01	0.3029E+02
420	0.7858E+01	0.6697E+00	-0.1300E+02	0.3124E+01	0.6042E+00	0.4426E+01	0.3028E+02
430	0.7969E+01	0.6897E+00	-0.1311E+02	0.3163E+01	0.5966E+00	0.4482E+01	0.3027E+02
440	0.8079E+01	0.7097E+00	-0.1321E+02	0.3202E+01	0.5892E+00	0.4536E+01	0.3026E+02
450	0.8187E+01	0.7298E+00	-0.1331E+02	0.3241E+01	0.5821E+00	0.4591E+01	0.3025E+02
460	0.8294E+01	0.7500E+00	-0.1342E+02	0.3279E+01	0.5752E+00	0.4644E+01	0.3025E+02
470	0.8400E+01	0.7702E+00	-0.1352E+02	0.3318E+01	0.5684E+00	0.4698E+01	0.3024E+02

480	0.8505E+01	0.7905E+00	-0.1361E+02	0.3355E+01	0.5619E+00	0.4751E+01	0.3023E+02
490	0.8609E+01	0.8109E+00	-0.1371E+02	0.3393E+01	0.5556E+00	0.4803E+01	0.3022E+02
500	0.8711E+01	0.8313E+00	-0.1381E+02	0.3430E+01	0.5495E+00	0.4855E+01	0.3022E+02
510	0.8812E+01	0.8517E+00	-0.1390E+02	0.3467E+01	0.5436E+00	0.4907E+01	0.3021E+02
520	0.8913E+01	0.8723E+00	-0.1400E+02	0.3504E+01	0.5378E+00	0.4958E+01	0.3021E+02
530	0.9012E+01	0.8928E+00	-0.1409E+02	0.3541E+01	0.5321E+00	0.5009E+01	0.3020E+02
540	0.9110E+01	0.9135E+00	-0.1418E+02	0.3577E+01	0.5267E+00	0.5060E+01	0.3019E+02
550	0.9208E+01	0.9341E+00	-0.1427E+02	0.3613E+01	0.5213E+00	0.5110E+01	0.3019E+02
560	0.9304E+01	0.9549E+00	-0.1436E+02	0.3649E+01	0.5161E+00	0.5160E+01	0.3018E+02
570	0.9399E+01	0.9756E+00	-0.1445E+02	0.3684E+01	0.5111E+00	0.5210E+01	0.3018E+02
580	0.9494E+01	0.9965E+00	-0.1454E+02	0.3720E+01	0.5062E+00	0.5259E+01	0.3017E+02
590	0.9588E+01	0.1017E+01	-0.1463E+02	0.3755E+01	0.5014E+00	0.5308E+01	0.3017E+02
600	0.9680E+01	0.1038E+01	-0.1471E+02	0.3790E+01	0.4967E+00	0.5356E+01	0.3016E+02
610	0.9772E+01	0.1059E+01	-0.1480E+02	0.3825E+01	0.4921E+00	0.5405E+01	0.3016E+02
620	0.9863E+01	0.1080E+01	-0.1488E+02	0.3859E+01	0.4876E+00	0.5453E+01	0.3015E+02
630	0.9954E+01	0.1101E+01	-0.1497E+02	0.3893E+01	0.4833E+00	0.5500E+01	0.3015E+02
640	0.1004E+02	0.1122E+01	-0.1505E+02	0.3927E+01	0.4790E+00	0.5548E+01	0.3014E+02
650	0.1013E+02	0.1143E+01	-0.1513E+02	0.3961E+01	0.4748E+00	0.5595E+01	0.3014E+02
660	0.1022E+02	0.1165E+01	-0.1521E+02	0.3995E+01	0.4707E+00	0.5642E+01	0.3013E+02
670	0.1031E+02	0.1186E+01	-0.1529E+02	0.4029E+01	0.4668E+00	0.5689E+01	0.3013E+02
680	0.1039E+02	0.1207E+01	-0.1537E+02	0.4062E+01	0.4629E+00	0.5735E+01	0.3012E+02
690	0.1048E+02	0.1228E+01	-0.1545E+02	0.4095E+01	0.4590E+00	0.5781E+01	0.3012E+02
700	0.1057E+02	0.1250E+01	-0.1553E+02	0.4128E+01	0.4553E+00	0.5827E+01	0.3011E+02
710	0.1065E+02	0.1271E+01	-0.1561E+02	0.4161E+01	0.4517E+00	0.5873E+01	0.3011E+02
720	0.1073E+02	0.1292E+01	-0.1568E+02	0.4194E+01	0.4481E+00	0.5918E+01	0.3011E+02
730	0.1082E+02	0.1314E+01	-0.1576E+02	0.4227E+01	0.4446E+00	0.5963E+01	0.3010E+02
740	0.1090E+02	0.1335E+01	-0.1584E+02	0.4259E+01	0.4411E+00	0.6008E+01	0.3010E+02
750	0.1098E+02	0.1357E+01	-0.1591E+02	0.4291E+01	0.4377E+00	0.6053E+01	0.3010E+02
757	0.1104E+02	0.1372E+01	-0.1596E+02	0.4312E+01	0.4356E+00	0.6082E+01	0.3009E+02

LNGC Thermal Discharge - Case 5 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.6350E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4861E-01	0.4630E-04	-0.6399E+01	0.7128E+00	0.2671E+01	0.1018E+01	0.3255E+02
10	0.4101E+00	0.1839E-02	-0.6760E+01	0.8091E+00	0.2352E+01	0.1156E+01	0.3220E+02
20	0.8093E+00	0.6821E-02	-0.7158E+01	0.9170E+00	0.2075E+01	0.1309E+01	0.3189E+02
30	0.1166E+01	0.1399E-01	-0.7514E+01	0.1015E+01	0.1874E+01	0.1449E+01	0.3167E+02
40	0.1492E+01	0.2279E-01	-0.7839E+01	0.1106E+01	0.1720E+01	0.1578E+01	0.3150E+02
50	0.1793E+01	0.3287E-01	-0.8138E+01	0.1190E+01	0.1597E+01	0.1699E+01	0.3137E+02
60	0.2074E+01	0.4400E-01	-0.8417E+01	0.1271E+01	0.1496E+01	0.1813E+01	0.3126E+02
70	0.2339E+01	0.5599E-01	-0.8680E+01	0.1347E+01	0.1411E+01	0.1921E+01	0.3116E+02
80	0.2589E+01	0.6871E-01	-0.8928E+01	0.1420E+01	0.1338E+01	0.2024E+01	0.3108E+02
90	0.2827E+01	0.8207E-01	-0.9163E+01	0.1490E+01	0.1275E+01	0.2124E+01	0.3101E+02
100	0.3054E+01	0.9598E-01	-0.9388E+01	0.1557E+01	0.1219E+01	0.2219E+01	0.3095E+02
110	0.3272E+01	0.1104E+00	-0.9603E+01	0.1622E+01	0.1170E+01	0.2312E+01	0.3090E+02
120	0.3482E+01	0.1252E+00	-0.9810E+01	0.1686E+01	0.1126E+01	0.2402E+01	0.3085E+02
130	0.3684E+01	0.1404E+00	-0.1001E+02	0.1747E+01	0.1086E+01	0.2489E+01	0.3081E+02
140	0.3879E+01	0.1560E+00	-0.1020E+02	0.1807E+01	0.1050E+01	0.2573E+01	0.3077E+02
150	0.4068E+01	0.1719E+00	-0.1039E+02	0.1865E+01	0.1017E+01	0.2656E+01	0.3073E+02
160	0.4252E+01	0.1881E+00	-0.1057E+02	0.1922E+01	0.9865E+00	0.2737E+01	0.3070E+02
170	0.4430E+01	0.2046E+00	-0.1074E+02	0.1978E+01	0.9585E+00	0.2815E+01	0.3067E+02
180	0.4603E+01	0.2213E+00	-0.1091E+02	0.2033E+01	0.9326E+00	0.2892E+01	0.3064E+02
190	0.4772E+01	0.2383E+00	-0.1108E+02	0.2086E+01	0.9085E+00	0.2968E+01	0.3061E+02
200	0.4936E+01	0.2555E+00	-0.1124E+02	0.2138E+01	0.8860E+00	0.3042E+01	0.3059E+02
210	0.5097E+01	0.2729E+00	-0.1139E+02	0.2190E+01	0.8650E+00	0.3115E+01	0.3056E+02
220	0.5254E+01	0.2905E+00	-0.1155E+02	0.2241E+01	0.8453E+00	0.3186E+01	0.3054E+02
230	0.5407E+01	0.3082E+00	-0.1170E+02	0.2290E+01	0.8268E+00	0.3256E+01	0.3052E+02
240	0.5557E+01	0.3261E+00	-0.1184E+02	0.2339E+01	0.8093E+00	0.3325E+01	0.3050E+02
250	0.5705E+01	0.3442E+00	-0.1198E+02	0.2388E+01	0.7928E+00	0.3394E+01	0.3048E+02
260	0.5849E+01	0.3624E+00	-0.1212E+02	0.2435E+01	0.7771E+00	0.3461E+01	0.3047E+02
270	0.5990E+01	0.3808E+00	-0.1226E+02	0.2482E+01	0.7623E+00	0.3527E+01	0.3045E+02
280	0.6129E+01	0.3993E+00	-0.1240E+02	0.2529E+01	0.7482E+00	0.3592E+01	0.3044E+02
290	0.6266E+01	0.4180E+00	-0.1253E+02	0.2574E+01	0.7348E+00	0.3656E+01	0.3042E+02
300	0.6400E+01	0.4367E+00	-0.1266E+02	0.2619E+01	0.7220E+00	0.3719E+01	0.3041E+02
310	0.6532E+01	0.4556E+00	-0.1278E+02	0.2664E+01	0.7098E+00	0.3782E+01	0.3039E+02
320	0.6661E+01	0.4746E+00	-0.1291E+02	0.2708E+01	0.6981E+00	0.3844E+01	0.3038E+02
330	0.6789E+01	0.4937E+00	-0.1303E+02	0.2751E+01	0.6870E+00	0.3905E+01	0.3037E+02
340	0.6915E+01	0.5129E+00	-0.1315E+02	0.2794E+01	0.6763E+00	0.3965E+01	0.3036E+02
350	0.7039E+01	0.5322E+00	-0.1327E+02	0.2837E+01	0.6660E+00	0.4025E+01	0.3035E+02
360	0.7161E+01	0.5516E+00	-0.1339E+02	0.2879E+01	0.6562E+00	0.4084E+01	0.3033E+02
370	0.7281E+01	0.5711E+00	-0.1350E+02	0.2921E+01	0.6467E+00	0.4143E+01	0.3032E+02
380	0.7399E+01	0.5906E+00	-0.1362E+02	0.2962E+01	0.6376E+00	0.4201E+01	0.3031E+02
390	0.7516E+01	0.6103E+00	-0.1373E+02	0.3003E+01	0.6288E+00	0.4258E+01	0.3030E+02
400	0.7632E+01	0.6300E+00	-0.1384E+02	0.3044E+01	0.6203E+00	0.4315E+01	0.3030E+02
410	0.7746E+01	0.6499E+00	-0.1395E+02	0.3084E+01	0.6121E+00	0.4371E+01	0.3029E+02
420	0.7858E+01	0.6697E+00	-0.1405E+02	0.3124E+01	0.6042E+00	0.4426E+01	0.3028E+02
430	0.7969E+01	0.6897E+00	-0.1416E+02	0.3163E+01	0.5966E+00	0.4482E+01	0.3027E+02
440	0.8079E+01	0.7097E+00	-0.1426E+02	0.3202E+01	0.5892E+00	0.4536E+01	0.3026E+02
450	0.8187E+01	0.7298E+00	-0.1436E+02	0.3241E+01	0.5821E+00	0.4591E+01	0.3025E+02
460	0.8294E+01	0.7500E+00	-0.1447E+02	0.3279E+01	0.5752E+00	0.4644E+01	0.3025E+02
470	0.8400E+01	0.7702E+00	-0.1457E+02	0.3318E+01	0.5684E+00	0.4698E+01	0.3024E+02

480	0.8505E+01	0.7905E+00	-0.1466E+02	0.3355E+01	0.5619E+00	0.4751E+01	0.3023E+02
490	0.8609E+01	0.8109E+00	-0.1476E+02	0.3393E+01	0.5556E+00	0.4803E+01	0.3022E+02
500	0.8711E+01	0.8313E+00	-0.1486E+02	0.3430E+01	0.5495E+00	0.4855E+01	0.3022E+02
510	0.8812E+01	0.8517E+00	-0.1495E+02	0.3467E+01	0.5436E+00	0.4907E+01	0.3021E+02
520	0.8913E+01	0.8723E+00	-0.1505E+02	0.3504E+01	0.5378E+00	0.4958E+01	0.3021E+02
530	0.9012E+01	0.8928E+00	-0.1514E+02	0.3541E+01	0.5321E+00	0.5009E+01	0.3020E+02
540	0.9110E+01	0.9135E+00	-0.1523E+02	0.3577E+01	0.5267E+00	0.5060E+01	0.3019E+02
550	0.9208E+01	0.9341E+00	-0.1532E+02	0.3613E+01	0.5213E+00	0.5110E+01	0.3019E+02
560	0.9304E+01	0.9549E+00	-0.1541E+02	0.3649E+01	0.5161E+00	0.5160E+01	0.3018E+02
570	0.9399E+01	0.9756E+00	-0.1550E+02	0.3684E+01	0.5111E+00	0.5210E+01	0.3018E+02
580	0.9494E+01	0.9965E+00	-0.1559E+02	0.3720E+01	0.5062E+00	0.5259E+01	0.3017E+02
590	0.9588E+01	0.1017E+01	-0.1568E+02	0.3755E+01	0.5014E+00	0.5308E+01	0.3017E+02
600	0.9680E+01	0.1038E+01	-0.1576E+02	0.3790E+01	0.4967E+00	0.5356E+01	0.3016E+02
610	0.9772E+01	0.1059E+01	-0.1585E+02	0.3825E+01	0.4921E+00	0.5405E+01	0.3016E+02
620	0.9863E+01	0.1080E+01	-0.1593E+02	0.3859E+01	0.4876E+00	0.5453E+01	0.3015E+02
630	0.9954E+01	0.1101E+01	-0.1602E+02	0.3893E+01	0.4833E+00	0.5500E+01	0.3015E+02
640	0.1004E+02	0.1122E+01	-0.1610E+02	0.3927E+01	0.4790E+00	0.5548E+01	0.3014E+02
650	0.1013E+02	0.1143E+01	-0.1618E+02	0.3961E+01	0.4748E+00	0.5595E+01	0.3014E+02
657	0.1019E+02	0.1158E+01	-0.1624E+02	0.3983E+01	0.4722E+00	0.5625E+01	0.3013E+02

LNGC Thermal Discharge - Case 6 (Table 7)

NE	XJ	YJ	ZJ	RJ	QJ	DIL	TEMP
1	0.0000E+00	0.0000E+00	-0.7400E+01	0.7000E+00	0.2720E+01	0.1000E+01	0.3260E+02
2	0.4861E-01	0.4630E-04	-0.7449E+01	0.7128E+00	0.2671E+01	0.1018E+01	0.3255E+02
10	0.4101E+00	0.1839E-02	-0.7810E+01	0.8091E+00	0.2352E+01	0.1156E+01	0.3220E+02
20	0.8093E+00	0.6821E-02	-0.8208E+01	0.9170E+00	0.2075E+01	0.1309E+01	0.3189E+02
30	0.1166E+01	0.1399E-01	-0.8564E+01	0.1015E+01	0.1874E+01	0.1449E+01	0.3167E+02
40	0.1492E+01	0.2279E-01	-0.8889E+01	0.1106E+01	0.1720E+01	0.1578E+01	0.3150E+02
50	0.1793E+01	0.3287E-01	-0.9188E+01	0.1190E+01	0.1597E+01	0.1699E+01	0.3137E+02
60	0.2074E+01	0.4400E-01	-0.9467E+01	0.1271E+01	0.1496E+01	0.1813E+01	0.3126E+02
70	0.2339E+01	0.5599E-01	-0.9730E+01	0.1347E+01	0.1411E+01	0.1921E+01	0.3116E+02
80	0.2589E+01	0.6871E-01	-0.9978E+01	0.1420E+01	0.1338E+01	0.2024E+01	0.3108E+02
90	0.2827E+01	0.8207E-01	-0.1021E+02	0.1490E+01	0.1275E+01	0.2124E+01	0.3101E+02
100	0.3054E+01	0.9598E-01	-0.1044E+02	0.1557E+01	0.1219E+01	0.2219E+01	0.3095E+02
110	0.3272E+01	0.1104E+00	-0.1065E+02	0.1622E+01	0.1170E+01	0.2312E+01	0.3090E+02
120	0.3482E+01	0.1252E+00	-0.1086E+02	0.1686E+01	0.1126E+01	0.2402E+01	0.3085E+02
130	0.3684E+01	0.1404E+00	-0.1106E+02	0.1747E+01	0.1086E+01	0.2489E+01	0.3081E+02
140	0.3879E+01	0.1560E+00	-0.1125E+02	0.1807E+01	0.1050E+01	0.2573E+01	0.3077E+02
150	0.4068E+01	0.1719E+00	-0.1144E+02	0.1865E+01	0.1017E+01	0.2656E+01	0.3073E+02
160	0.4252E+01	0.1881E+00	-0.1162E+02	0.1922E+01	0.9865E+00	0.2737E+01	0.3070E+02
170	0.4430E+01	0.2046E+00	-0.1179E+02	0.1978E+01	0.9585E+00	0.2815E+01	0.3067E+02
180	0.4603E+01	0.2213E+00	-0.1196E+02	0.2033E+01	0.9326E+00	0.2892E+01	0.3064E+02
190	0.4772E+01	0.2383E+00	-0.1213E+02	0.2086E+01	0.9085E+00	0.2968E+01	0.3061E+02
200	0.4936E+01	0.2555E+00	-0.1229E+02	0.2138E+01	0.8860E+00	0.3042E+01	0.3059E+02
210	0.5097E+01	0.2729E+00	-0.1244E+02	0.2190E+01	0.8650E+00	0.3115E+01	0.3056E+02
220	0.5254E+01	0.2905E+00	-0.1260E+02	0.2241E+01	0.8453E+00	0.3186E+01	0.3054E+02
230	0.5407E+01	0.3082E+00	-0.1275E+02	0.2290E+01	0.8268E+00	0.3256E+01	0.3052E+02
240	0.5557E+01	0.3261E+00	-0.1289E+02	0.2339E+01	0.8093E+00	0.3325E+01	0.3050E+02
250	0.5705E+01	0.3442E+00	-0.1303E+02	0.2388E+01	0.7928E+00	0.3394E+01	0.3048E+02
260	0.5849E+01	0.3624E+00	-0.1317E+02	0.2435E+01	0.7771E+00	0.3461E+01	0.3047E+02
270	0.5990E+01	0.3808E+00	-0.1331E+02	0.2482E+01	0.7623E+00	0.3527E+01	0.3045E+02
280	0.6129E+01	0.3993E+00	-0.1345E+02	0.2529E+01	0.7482E+00	0.3592E+01	0.3044E+02
290	0.6266E+01	0.4180E+00	-0.1358E+02	0.2574E+01	0.7348E+00	0.3656E+01	0.3042E+02
300	0.6400E+01	0.4367E+00	-0.1371E+02	0.2619E+01	0.7220E+00	0.3719E+01	0.3041E+02
310	0.6532E+01	0.4556E+00	-0.1383E+02	0.2664E+01	0.7098E+00	0.3782E+01	0.3039E+02
320	0.6661E+01	0.4746E+00	-0.1396E+02	0.2708E+01	0.6981E+00	0.3844E+01	0.3038E+02
330	0.6789E+01	0.4937E+00	-0.1408E+02	0.2751E+01	0.6870E+00	0.3905E+01	0.3037E+02
340	0.6915E+01	0.5129E+00	-0.1420E+02	0.2794E+01	0.6763E+00	0.3965E+01	0.3036E+02
350	0.7039E+01	0.5322E+00	-0.1432E+02	0.2837E+01	0.6660E+00	0.4025E+01	0.3035E+02
360	0.7161E+01	0.5516E+00	-0.1444E+02	0.2879E+01	0.6562E+00	0.4084E+01	0.3033E+02
370	0.7281E+01	0.5711E+00	-0.1455E+02	0.2921E+01	0.6467E+00	0.4143E+01	0.3032E+02
380	0.7399E+01	0.5906E+00	-0.1467E+02	0.2962E+01	0.6376E+00	0.4201E+01	0.3031E+02
390	0.7516E+01	0.6103E+00	-0.1478E+02	0.3003E+01	0.6288E+00	0.4258E+01	0.3030E+02
400	0.7632E+01	0.6300E+00	-0.1489E+02	0.3044E+01	0.6203E+00	0.4315E+01	0.3030E+02
410	0.7746E+01	0.6499E+00	-0.1500E+02	0.3084E+01	0.6121E+00	0.4371E+01	0.3029E+02
420	0.7858E+01	0.6697E+00	-0.1510E+02	0.3124E+01	0.6042E+00	0.4426E+01	0.3028E+02
430	0.7969E+01	0.6897E+00	-0.1521E+02	0.3163E+01	0.5966E+00	0.4482E+01	0.3027E+02
440	0.8079E+01	0.7097E+00	-0.1531E+02	0.3202E+01	0.5892E+00	0.4536E+01	0.3026E+02
450	0.8187E+01	0.7298E+00	-0.1541E+02	0.3241E+01	0.5821E+00	0.4591E+01	0.3025E+02
460	0.8294E+01	0.7500E+00	-0.1552E+02	0.3279E+01	0.5752E+00	0.4644E+01	0.3025E+02
470	0.8400E+01	0.7702E+00	-0.1562E+02	0.3318E+01	0.5684E+00	0.4698E+01	0.3024E+02

480	0.8505E+01	0.7905E+00	-0.1571E+02	0.3355E+01	0.5619E+00	0.4751E+01	0.3023E+02
490	0.8609E+01	0.8109E+00	-0.1581E+02	0.3393E+01	0.5556E+00	0.4803E+01	0.3022E+02
500	0.8711E+01	0.8313E+00	-0.1591E+02	0.3430E+01	0.5495E+00	0.4855E+01	0.3022E+02
510	0.8812E+01	0.8517E+00	-0.1600E+02	0.3467E+01	0.5436E+00	0.4907E+01	0.3021E+02
520	0.8913E+01	0.8723E+00	-0.1610E+02	0.3504E+01	0.5378E+00	0.4958E+01	0.3021E+02
530	0.9012E+01	0.8928E+00	-0.1619E+02	0.3541E+01	0.5321E+00	0.5009E+01	0.3020E+02
540	0.9110E+01	0.9135E+00	-0.1628E+02	0.3577E+01	0.5267E+00	0.5060E+01	0.3019E+02
550	0.9208E+01	0.9341E+00	-0.1637E+02	0.3613E+01	0.5213E+00	0.5110E+01	0.3019E+02
560	0.9304E+01	0.9549E+00	-0.1646E+02	0.3649E+01	0.5161E+00	0.5160E+01	0.3018E+02
564	0.9342E+01	0.9632E+00	-0.1650E+02	0.3661E+01	0.5144E+00	0.5177E+01	0.3018E+02